

2 4 6 8 10 12 14 16 18 20 22 24

2 : 1

Technical drawing of a mechanical part, likely a bracket or support, showing dimensions in millimeters. The drawing includes a cross-section of the part and a side view. Dimensions are indicated by arrows and numbers:

- Overall width: 5 (=10)
- Distance from the left edge to the center of the first hole: 2,5
- Distance from the center of the first hole to the center of the second hole: 2,5
- Distance from the center of the second hole to the center of the third hole: 2,5
- Distance from the center of the third hole to the center of the fourth hole: 2,5
- Distance from the center of the fourth hole to the right edge: 2,5
- Distance from the top edge to the center of the first hole: 2,5
- Distance from the center of the first hole to the top edge: 0,2

Technical drawing of a multi-pin assembly. The drawing shows a series of pins of varying lengths and diameters, arranged vertically. The dimensions are given in millimeters (mm) and are as follows:

- Voreiler / Preleading Pin 1,75mm
- Voreiler / Preleading Pin 1,25mm
- Voreiler / Preleading Pin 0,6mm
- Standard / Standard Pin
- Nacheiler / Lagging Pin 0,6mm
- Nacheiler / Lagging Pin 1,5mm

The drawing also includes a dimension of 6 -0,4 mm for the distance between the pins. The pins are shown in cross-section, with the outer diameter and the inner hole diameter indicated. The pins are arranged in a staggered pattern, with the outer diameter of one pin aligned with the inner hole of the next pin.

[illegible]