

VPX3000

3 Slot chassis for conduction cooled 3U VPX payloads

■ Embedded Computing for
Business-Critical Continuity™


Small form factor 3U 3 slot OpenVPX chassis

- 3 Slot VITA 65 compliant backplane with full mesh data plane
- 1000BaseX control plane
- Supports conduction cooled 3U VPX modules
- Natural convection cooled enclosure
- Customizable Interface Adapter Board (IAB)
- Optional SATA SSD mounted on IAB
- Built in DC power supply

VPX3000 is a convection cooled, fanless enclosure that accepts up to three 3U conduction cooled VPX modules. It includes a configurable I/O Adapter Board (IAB) that is designed to mate with Emerson's iVPX7225 processor blade, itself based on the Intel (R) 3rd generation Core mobile chipset. The IAB routes I/O from the payloads to the front of the enclosure and is designed to be customizable. VPX3000 includes a VITA-62 compliant power supply slot fitted with a DC power supply with a MIL-38999 power input connector and a front panel switch.

Two Data Plane Fat Pipes from each slot are connected in a full mesh configuration. Two Control Plane Ultra Thin Pipes from each slot are routed to the IAB as 1000Base-T interfaces. USB 2.0 and a Display Port interface is also routed to the IAB in all variants.

VPX3000 has been designed to minimise Size, Weight and Power (SWaP) and yet provide an intensely powerful system level solution including power, storage and processor elements. A rugged variant, targeted at Mil/Aero/Government applications includes three MIL-38999 connectors for I/O from each slot. An alternative variant includes commercial connectors on the IAB and is intended for development use.



POWER SUPPLY

- Power supplies in Rugged variants designed to MIL-STD 461F for susceptibility and emissions
- Power supplies in all variants compliant to Class A susceptibility and emissions for the locale (FCC, VCCI, CE, KC, AS/NZ) [EN55022 or equivalent]
- DC supply compliant to MIL-STD 1275D
 - ▲ 19-36VDC, 400W
- Outputs following subset of VITA 62 defined power rails:
 - ▲ +5V (VS3) output @200W
 - ▲ +12V (VS1) output @ 200W
 - ▲ +3V (VBAT)

BACKPLANE

- 1" slot pitch
- Compliant to following VITA 65 Payload/Peripheral Slot Profiles
 - ▲ SLT3-PAY-2F2U-14.2.3
 - ▲ SLT3-PAY-1F1F2U-14.2.4
 - ▲ SLT3-PAY-2F-14.2.7
 - ▲ SLT3-PER-2F-14.3.1
 - ▲ SLT3-PER-1F-14.3.2
 - ▲ SLT3-PER-1U-14.3.3
- Full mesh connectivity between 2F Data Plane ports
- 2U (1000Base-X) Control Plane routed to IAB
- Supports 3 SBC's in peer-peer configuration
- Supports 1 SBC and up to 2 Peripheral Modules
- Supports 1 VITA 62-compliant power supply slot

OTHER BACKPLANE CONNECTIVITY

- SM0, SM1 bussed between Payload and PSU slots
- +3VBAT, +5V, +12V routed from PSU slot to all Payload slots
- All other signals on each Payload slot routed to IAB

INTERFACE ADAPTER BOARD (IAB) DETAILS

- 6x 1000BASE-X to 1000Base-T PHY's (2 from each Payload slot)
- 3x DisplayPort re-drivers
- 3x SATA ports terminated on-board for optional SSD (1x from each slot)
- All other signals routed to front panel connectors

STORAGE

- Option for up to 3 SATA SSD drives, one to each payload slot
- Minimum/maximum 48GB/96GB per slot

RUGGED IAB FRONT PANEL CONNECTIONS

- 3 Meritec Hercules MIL-38999 with 44 10Gb differential pairs. One per slot, aligned with IVPX7225 I/O:
 - ▲ 2x 1000BaseT
 - ▲ 2x RS-232/422/485 (4-wire)
 - ▲ 3x USB 2.0
 - ▲ 1x DisplayPort
 - ▲ 2x SATA
 - ▲ 24x (12 diff pairs) XMC I/O
 - ▲ 7x GPIO
- 1x MIL-38999 for DC power input
- On/Off switch with finger guard

COMMERCIAL IAB FRONT PANEL CONNECTIONS

- 6x RJ45 1000BASE-T – 2x per slot
- 3x USB 2.0 Type A – 1x per slot
- 3x Mini DisplayPort – 1x per slot
- 4x RJ45 RS-232/422/485
 - ▲ 2x from Slot 1 (COM0/1)
 - ▲ 1x from each of Slot2/3
- 1x MIL-38999 for DC Power
- On/Off switch with finger guard

MECHANICAL

- Blade insertion vertical from top of enclosure
- 4x baseplate holes support vertical mounting

EMC COMPLIANCE

- Rugged variants:
 - ▲ MIL-STD-461F
 - ▲ CE102
 - ▲ CS101, CS114, CS115, CS116
 - ▲ RE102
 - ▲ RS101, RS103
- Commercial variants:
 - ▲ Class A (FCC, VCCI, CE, KC, AS/NZ) [EN55022 or equivalent]

SAFETY STANDARDS

- UL/CSA EN60950
- CE product safety marking

ROHS COMPLIANCE

- All variants designed to be RoHS 2 compliant with exclusion for out-of-scope applications
- All variants are RoHS 5/6 (lead solder) and may employ non-RoHS VPX backplane connectors and/or 38999 connectors
- Commercial variants are designed to be RoHS 6/6. (MOQ and extended lead times apply for RoHS compliance)

COMMERCIAL AND RUGGED VARIANTS ARE AVAILABLE FOR THIS PRODUCT LINE.

Environmental Specifications		
Ruggedization Level	Commercial Variant (With IAB2)	Rugged Variant (With IAB1)
Cooling Method	Natural Convection	Natural Convection
Operating Temperature	-0°C to +26°C ambient (at 117W) ¹ -0°C to +48°C ambient (at 48W) ²	-40°C to +26°C ambient (at 117W) ¹ -40°C to +48°C ambient (at 48W) ²
Storage Temperature	-40°C to +85°C	-50°C to +100°C
Vibration Sine (10 min/Axis)	5G, 15 to 2000Hz	5G, 15 to 2000Hz
Vibration Random (1 Hr/Axis)	0.02g ² /Hz, 15 to 2000Hz (2GRMS)	0.04g ² /Hz, 15 to 2000Hz (8GRMS)
Shock	30g/11ms in each of 3 axes	40g/11ms in each of 3 axes
Humidity	to 95% RH non-condensing	to 95% RH non-condensing

Note 1: Tested with three iVPX7225 boards, average processor frequency of 2.0GHz (80% utilization)

Note 2: Tested with one iVPX7225 board, average processor frequency of 2.0GHz (80% utilization)

Ordering Information

Part Number	Description
VPX3000-DC-IAB1	3 Slot Rugged Chassis for conduction cooled 3U VPX Payloads, DC power
VPX3000-DC-IAB2	3 Slot Commercial Chassis for conduction cooled 3U VPX Payloads, DC power
VPX3000-CBL-IO-S	MIL-38999 to I/O breakout cable assembly, shielded 0.6m
VPX3000-CBL-DC	MIL-38999, DC keying to pigtail leads (1m)
IVPX7225-02250813	3U VPX, Conduction, cooled processor payload based on Dual-Core 2.5GHz 3555LE, 8GB DDR3L, .85" PITCH, ENP3

SOLUTION SERVICES

Emerson Network Power provides a portfolio of solution services optimized to meet your needs throughout the product lifecycle. Design services help speed time-to-market. Deployment services include global 24x7 technical support. Renewal services enable product longevity and technology refresh.

PowerPC is a trademark of IBM Corp. and used under license. All other product or service names are the property of their respective owners.

This document identifies products, their specifications, and their characteristics, which may be suitable for certain applications. It does not constitute an offer to sell or a commitment of present or future availability, and should not be relied upon to state the terms and conditions, including warranties and disclaimers thereof, on which Emerson Network Power may sell products. A prospective buyer should exercise its own independent judgment to confirm the suitability of the products for particular applications. Emerson Network Power reserves the right to make changes, without notice, to any products or information herein which will, in its sole discretion, improve reliability, function, or design. Emerson Network Power does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent or other intellectual property rights or under others. This disclaimer extends to any prospective buyer, and it includes Emerson Network Power's licensee, licensee's transferees, and licensee's customers and users. Availability of some of the products and services described herein may be restricted in some locations.

Emerson Network Power.
The global leader in enabling
Business-Critical Continuity™.

AC Power
Connectivity
DC Power
Embedded Computing

Embedded Power
Infrastructure Management & Monitoring
Outside Plant
Power Switching & Controls

Precision Cooling
Racks & Integrated Cabinets
Services
Surge Protection

Emerson Network Power

Offices: Tempe, AZ U.S.A. 1 800 759 1107 or +1 602 438 5720
Paris, France +33 1 60 92 31 20 • Munich, Germany +49 8996 082564 • Tel Aviv, Israel +972 9 9560361
Hong Kong +852 2176 3540 • Shanghai, China +86 21 3395 0289 • Tokyo, Japan +81 3 5403 2730 • Seoul, Korea +82 2 3483 1500

EmersonNetworkPower.com/EmbeddedComputing

Emerson and the Emerson Network Power logo are trademarks of Emerson Electric Co.
©2013 Emerson Electric Co. All rights reserved.

VPX3000 11/25/13