


NLV25T-470J-EFD



Applications	Automotive Grade
Feature	AEC-Q200
	No Directivity
	Wire Wound
	Ferrite Core
Series Type	NLV25-EFD
Status	Production
Brand	TDK



Size	
Length(L)	2.50mm ±0.20mm
Width(W)	2.00mm ±0.10mm
Thickness Height	1.80mm ±0.10mm
Recommended Land Pattern (A)	1.00mm Nom.
Recommended Land Pattern (B)	1.50mm Nom.
Recommended Land Pattern (C)	1.50mm Nom.

Electrical Characteristics	
Inductance	47μH ±5% at 2.52MHz
Rated Current	80mA
DC Resistance [Typ.]	
DC Resistance [Max.]	11.1Ω
Self Resonant Frequency [Min.]	17MHz
Self Resonant Frequency [Typ.]	
Q [Min.]	20 at 2.52MHz
Q [Typ.]	







Other	
Operating Temp. Range	-40 to 105°C (Including Self-Temp. Rise)
Soldering Method	Wave (Flow)
	Reflow
	Iron Soldering
AEC-Q200	YES
Packing	Embossed (Plastic)Taping [180mm Reel]
Package Quantity	2000pcs
Weight	0.025g

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

NLV25T-470J-EFD



Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)





Associated Images

