

DEK 6 FWZ 11-20




Weidmüller Interface GmbH & Co. KG

1

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com









The dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a large range of ready-printed markers. Strips for fast installation in one work step. The printing is easy to read, rich in contrast, and is available in five widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terimal markers, suitable for all Weidmüller cable connectors
- Available as blank cards, MultiCard or as cards with standard printing

General ordering data

Version	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, white
Order No.	<u>0518960011</u>
Туре	DEK 6 FWZ 11-20
GTIN (EAN)	4008190104948
Qty.	500 items

DEK 6 FWZ 11-20



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Aр	pr	ov	a	s
----	----	----	---	---

ROHS	Conform

Dimensions and weights

Height	5 mm	Height (inches)	0.1968 inch
Width	6 mm	Width (inches)	0.2362 inch
Net weight	0.05 g		

Temperatures

Operating temperature range -40...100 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption		
REACH SVHC	No SVHC above 0.1 wt%		
Product Carbon Footprint	Cradle to gate	0.001 kg CO2 eq.	

General data

Material colour according to resistance code	9	
Orientation of print	horizontal	
Printing method	MC Laser	
Width	6 mm	
UL 94 flammability rating	V-2	
Operating temperature range, max.	100 °C	
Operating temperature range, min.	-40 °C	
Colour	white	
Halogen	No	
Basic material	Polyamide 66	
Colour of printing	black	
Printed characters	Numbers	
Number of markers per packaging unit	Form of supply	Card
Number of markers per combination	1 Card = Terminal marker	
Operating temperature range	-40100 °C	
Application/manufacturer	Weidmueller	

Connector markers

Pitch in mm (P)	6.00 mm	

Classifications

EC000761	ETIM 7.0	EC000761
EC000761	ETIM 9.0	EC000761
EC000761	ECLASS 9.0	27-14-11-37
27-14-11-37	ECLASS 10.0	27-14-11-37
27-28-11-01	ECLASS 12.0	27-28-11-01
27-28-11-01	ECLASS 14.0	27-28-11-01
27-28-11-01		
	EC000761 EC000761 27-14-11-37 27-28-11-01 27-28-11-01	EC000761 ETIM 9.0 EC000761 ECLASS 9.0 27-14-11-37 ECLASS 10.0 27-28-11-01 ECLASS 12.0 27-28-11-01 ECLASS 14.0

Creation date 01.10.2025 01:02:55 MEZ