

Specification Sheet

Part Number: ET660



PVC Tape is ideal for general purpose electrical applications.
Economical way to splice, terminate and insulate wire and cables.
Meets Mil-Std. MIL-1-7798-A.

Article Number	904-00008
Type	ET66
Color	Black (BK)
Quantity Per	reel
Product Description	PVC electrical tape provides fast and easy color coding, cable splicing, terminating, and wire insulating. These conformable high quality tapes have exceptional surface and adhesive characteristics. Tape is applied by overlapping each layer 50% and using tension. After the tape is adhered, the memory of the tape returns, tightening the seal and making the taped area even more waterproof.
Short Description	Electrical Tape, 0.75" x 66' Roll, 7.0 mil Thick, PVC, Black, 10 rolls/pkg
Global Part Name	ET66-PVC-BK

Minimum Tensile Strength (Imperial)	15.4
Length L (Imperial)	66.0
Length L (Metric)	20.12
Width W (Imperial)	0.75
Width W (Metric)	19.05
Thickness T (Imperial)	7.0
Material	Flexible Polyvinyl Chloride (PVC)
Material Shortcut	PVC
US MIL SPEC	MIL-1-7798-A
UV Resistant (Yes/No)	No
Operating Temperature	+20°F to 176°F (-7°C to +80°C)
Reach Compliant (Article 33)	No
Package Quantity (Imperial)	10
Package Quantity (Metric)	10

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)