

MICRO SWITCH

A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR COMPANY
PROSPERITY, ILLINOIS
FED. MFR. CODE 91929

SWITCH - BASIC

CATALOG LISTING

IHS38

5

(M) IHS38
ISSUE 3

REPLACES

RELEASE NO.

CHECK

REVISIONS

A CO14269

12 JAN 60

B CO14585

28 DEC 60

C CO15761

3 APR 61

D CO16599

11 JAN 62

E CO16599

6 FEB 63

F CO55162-J

20 JUN 85

G CO58121

27 AUG 85

H CO65768

12 JUN 89

J CO-6043

20 SEP 89

K CO

76375

31 AUG 93

WES

31 AUG 93

WES

31 AUG 93

WES

31 AUG 93

WES

31 AUG 93

WES

31 AUG 93

WES

31 AUG 93

WES

31 AUG 93

WES

31 AUG 93

WES

31 AUG 93

WES

31 AUG 93

WES

31 AUG 93

WES

31 AUG 93

WES

31 AUG 93

CORROSION RESISTANT STEEL,
6-32 UNC X .219 REF BINDING
HEAD, COMBINATION DRIVE, TERMINAL
SCREW AND LOCKWASHER (SEMS) (3)

- ① - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON 1.000 ± .002 CENTERS
- 2 - SWITCH SIDES SUPPORTED AT MOUNTING HOLES BY RIGID INSERTS
- ③ - ROLLER IS PARALLEL TO PLANE OF MTG HOLES WITHIN .015 PER INCH
- ④ - FOR USE IN AMBIENT TEMPERATURE RANGE FROM MINUS 65° TO PLUS 250° F

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS		ELECTRICAL DATA			SCALE FULL
OPERATING FORCE — — — — — 10-22 OZ		CONTACT ARRANGEMENT S P D T			DO NOT SCALE PRINT
RELEASE FORCE — — — — — 4 OZ MIN		LINE VOLTAGE	INDUCTIVE LOAD	RESISTIVE LOAD	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: ONE PLACE (.0) ±.030 TWO PLACE (.00) ±.015 THREE PLACE (.000) ±.005 ANGLES ±
DIFFERENTIAL TRAVEL — — — — — .013 MAX					
OVERTRAVEL — — — — — .028 MIN		28 V.D.C.	5 AMP	15 AMP	