


Product Search Data Sheet

XRCGB27M000FAN00R0

In Production RoHS REACH

Appearance & Shape





Note: This datasheet may be out of date. Please download the latest datasheet of XRCGB27M000FAN00R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=XRCGB27M000FAN00R0

Features

The crystal unit that realized small package and highly accurate frequency.

Based on Murata's excellent package technology and high grade quartz crystal elements, achieving small size and high accuracy resonators.

Features

1. The series is available in the applications to be necessary for high accuracy resonator. Especially, it is the best for the

communication clocks such as S-ATAand USB2.0. 2. The resonator is extremerly small size (2.0 x 1.6 x 0.7 (mm)),

and contribute to reduction in mounting area.

3. The series complies to RoHS directive, being lead-free (phase 3).



Other Usage

Consumer



Packaging Information

Packaging	Specifications	Standard Packing Quantity
R0	180mm Plastic Tape	3000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





XRCGB27M000FAN00R0

Note: This datasheet may be out of date. Please download the latest datasheet of XRCGB27M000FAN00R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=XRCGB27M000FAN00R0

Specifications

Product Type	Crystal Unit	
Series	XRCGB	
Туре	HCR2016	
Frequency	27.0000MHz	
Frequency Tolerance	+/-25ppm max. (25+/-3°C)	
Operating Temperature Range	-10°C~70°C	
Frequency Shift by Temperature	+/-25ppm max.	
Frequency Aging	+/-5ppm max./year	
Equivalent Series Resistance (ESR)	150ohm max.	
Drive Level (DL)	150µW (300µW max.)	
Load Capacitance (Cs)	6pF	
Shape	SMD	
Wash	Not available	
L x W (size)	2.0x1.6mm	
Mass	6.9mg	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






Product Search Data Sheet

XRCGB27M000FAN00R0

Note: This datasheet may be out of date. Please download the latest datasheet of XRCGB27M000FAN00R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=XRCGB27M000FAN00R0





Temperature Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

