

PB Busway Tap Off Unit, 1x1 pole 3 Wire, Phase B, 1 Drop cord, IEC 309 20A, 240V

PBP4A11IEC20B

! Discontinued on: Jul 2, 2025

① Discontinued

Overview

Presentation	Factory-assembled and tested, the tap off units house standard circuit breakers and a pre-terminated cord set. No tools required for installation on any iBusway for Data Center busway straight section.
I ead time	Liqually Shine within 6 Weeks

Main

Main Output Voltage	240 V
Provided Equipment	Installation quido

Physical

Color	Black
Height	14.02 in (35.6 cm)
Width	8.5 in (21.5 cm)
Depth	5.7 in (14.5 cm)
Net Weight	17.99 lb(US) (8.16 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Frequency 60 Hz

Output

Maximum Total Current Draw per Phase	20 A
Number of power socket outlets	1 IEC 60309 20 A
Cord Length	3 ft (0.9 m)

Conformance

5 1 10 15 15		
Product Certifications	cUL Listed	
	CSA	
	III Listed	

Environmental

Ambient air temperature for operation	14104 °F (-1040 °C)
Relative Humidity	095 %

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 7, 2025 Life Is On Schneider

Operating altitude	010000 ft
Ambient Air Temperature for Storage	-22158 °F (-3070 °C)
Storage Relative Humidity	095 %
Storage altitude	015000 ft (04572 m)

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Contractual warranty

Warranty 1 year (parts only)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

EU RoHS Directive

Under investigation

Image of product / Alternate images

Alternative

