

APC IT Power Distribution Module 2 Pole 3 Wire 30A L3-L1 L6-30 740CM

PDM2330L6-31-740

Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks

Main

Main Input Voltage	208 V
Main Output Voltage	208 V
Provided equipment	Installation guide

Physical

Colour	Black
Height	12.7 cm
Width	44.4 cm
Depth	40.6 cm
Net weight	4.29 kg

Input

Network frequency	60 Hz
Max line current	30 A

Output

Max current draw	30 A
Number of power socket outlets	1 NEMA L6-30R

Conformance

Product certifications	III listed	

Environmental

Ambient air temperature for operation	030 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1540 °C
Storage Relative Humidity	095 %

Storage altitude 0...4572 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.7 cm
Package 1 Width	40.6 cm
Package 1 Length	44.4 cm
Package 1 Weight	5.2 kg

Contractual warranty

Warranty 1 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

Q	Environmental	footprint
2	Environmental	tootprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture		
End of life manual availability	End of Life Information	
Take-back	No	
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Oct 14, 2025

Image of product / Alternate images

Alternative

