

2A, 400V ESD Capability Rectifier

FEATURES

- AEC-Q101 qualified
- High ESD capability
- Glass passivated chip junction
- Ideal for automated placement
- Low forward voltage drop
- High surge current capability
- Moisture sensitivity level: level 1, per J-STD-020
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
I_F	2	A
V_{RRM}	400	V
I_{FSM}	50	A
$T_{J\ MAX}$	175	°C
Package	DO-214AA (SMB)	
Configuration	Single die	

APPLICATIONS

- DC to DC converter
- Automotive application
- Car lighting
- Snubber



DO-214AA (SMB)



SOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TSD2GH	UNIT
Marking code on the device		TSD2G	
Repetitive peak reverse voltage	V_{RRM}	400	V
Reverse voltage, total rms value	$V_{R(RMS)}$	280	V
Forward current	I_F	2	A
Surge peak forward current, 8.3 ms single half sine-wave superimposed on rated load	I_{FSM}	50	A
Junction temperature	T_J	- 55 to +175	°C
Storage temperature	T_{STG}	- 55 to +175	°C

THERMAL PERFORMANCE

PARAMETER	SYMBOL	TYP	UNIT
Junction-to-lead thermal resistance	$R_{\Theta JL}$	26	°C/W
Junction-to-ambient thermal resistance	$R_{\Theta JA}$	73	°C/W
Junction-to-case thermal resistance	$R_{\Theta JC}$	27	°C/W

Thermal Performance Note: Units mounted on PCB (10mm x 10mm Cu pad test board)

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ C$ unless otherwise noted)

PARAMETER	CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage ⁽¹⁾	$I_F = 1A, T_J = 25^\circ C$	V_F	0.87	0.95	V
	$I_F = 2A, T_J = 25^\circ C$		0.90	1.00	V
	$I_F = 1A, T_J = 125^\circ C$		0.80	0.90	V
	$I_F = 2A, T_J = 125^\circ C$		0.75	0.85	V
Reverse current @ rated V_R ⁽²⁾	$T_J = 25^\circ C$	I_R	-	1	μA
	$T_J = 125^\circ C$		-	50	μA
Junction capacitance	1MHz, $V_R=4.0V$	C_J	20	-	pF

Notes:

1. Pulse test with PW = 0.3ms
2. Pulse test with PW = 30ms

IMMUNITY TO ELECTRICAL STATIC DISCHARGE TO THE FOLLOWING STANDARDS ($T_A = 25^\circ C$ unless otherwise noted)

STANDARD	TEST TYPE	TEST CONDITION	SYMBOL	CLASS	VALUE	TYPICAL
AEC-Q101-001	Human body model(contact mode)	$C=100pF, R=1.5k\Omega$	V_C	H3B	$\geq 8kV$	N/A
IEC 61000-4-2	Contact mode	$C=150pF, R=330\Omega$		4	$\geq 8kV$	25kV
	Air-discharge mode	$C=150pF, R=330\Omega$		4	$\geq 15kV$	30kV
ISO 10605	Contact mode	$C=330pF, R=330\Omega$		L4	$\geq 15kV$	25kV
	Air-discharge mode	$C=330pF, R=330\Omega$		L4	$\geq 25kV$	30kV

ORDERING INFORMATION

ORDERING CODE	PACKAGE	PACKING
TSD2GH	DO-214AA (SMB)	3,000 / Tape & Reel

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics






Fig.4 Typical Forward Characteristics




PACKAGE OUTLINE DIMENSIONS

DO-214AA (SMB)


DIM.	Unit (mm)		Unit (inch)	
	Min.	Max.	Min.	Max.
A	1.95	2.65	0.077	0.104
A1	0.05	0.20	0.002	0.008
b	1.95	2.20	0.077	0.087
c	0.15	0.31	0.006	0.012
D	3.30	3.95	0.130	0.156
E	5.10	5.60	0.201	0.220
E1	4.05	4.60	0.159	0.181
L	0.75	1.60	0.030	0.063

SUGGESTED PAD LAYOUT



Symbol	Unit (mm)	Unit (inch)
A	2.30	0.091
B	2.50	0.098
C	4.30	0.169
D	1.80	0.071
E	6.80	0.268

MARKING DIAGRAM



P/N = Marking Code
 G = Green Compound
 YW = Date Code
 F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.