

DELPHI Connection Systems

Catalog

Customer Service

Comparison List (0)

Samples Request

Find by Feature

Browse by Category

Browse by Application

Share

15496531

Search

Enter part number or keyword

Search Results (1)

Search

Options

1 Result(s): [All] - 15496531


☐ Compare

15496531 - GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2

☐ Compare

GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2

Part # 15496531



Question about this product?

Attributes		Documents (3)	
Part # :	15496531		
Part # :	15496531		
Part # :	15496531		
Part # :	 15496531		
Part # :	15496531		
Part # :	15496531		
Part # :	15496531		
Part # :	15496531		
Part # :	15496531		
Part # :	15496531		
Part # :	15496531		
Part # :	15496531		
Part # :	15496531		
Part # :	15496531		
Part # :	15496531		
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2		
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2		
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2		
Description :	 GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2		
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2		
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2		
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2		
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2		

Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2
Description :	GT Flex Beam 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	✔ Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Status :	Active
Status :	Active
Status :	Active
Status :	✔ Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5


Blade size [mm] :	 1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Blade size [mm] :	1.5
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	 GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Terminal Family :	GT FBT
Series :	150
Series :	150
Series :	150
Series :	 150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Gender :	Female
Gender :	Female

Weight [g] :	0
Weight [g] :	 0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	 Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Minimum Cable Diameter [mm] :	1.70
Minimum Cable Diameter [mm] :	1.70
Minimum Cable Diameter [mm] :	1.70
Minimum Cable Diameter [mm] :	 1.70
Minimum Cable Diameter [mm] :	1.70
Minimum Cable Diameter [mm] :	1.70
Minimum Cable Diameter [mm] :	1.70
Minimum Cable Diameter [mm] :	1.70
Minimum Cable Diameter [mm] :	1.70
Minimum Cable Diameter [mm] :	1.70
Minimum Cable Diameter [mm] :	1.70
Minimum Cable Diameter [mm] :	1.70
Minimum Cable Diameter [mm] :	1.70
Minimum Cable Diameter [mm] :	1.70
Maximum Cable Diameter [mm] :	2.25

Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	 2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Maximum Cable Diameter [mm] :	2.25
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	 0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Minimum Cable Core Cross Section [mm2] :	0.75
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	 1.00

Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
RoHs compliant :	 Yes
ELV compliant :	 Yes

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.



[Suppliers](#) | [Terms of Use](#) | [Privacy](#) | [Mexico Privacy Statement](#) | [Cookie Policy](#) | [Sitemap](#) | [European Safe Harbor](#) | [California Supply Chains Act](#)

© Delphi Automotive LLP. All rights reserved.