

Quick Links

Cross reference

RoHS/LF P/M Search

Industry Standards

Alphabetical List

Documentation

3D model search

Customer drawing search

Multi Selection Search

Search by category

Start > Search=10127819-0211GLF\* > 10127819-0211GLF

10127819-0211GLF

10127819-0211GLF - Minitex® Pwr4.2 : Minitex® Pwr4.2 header, Dual row, Right-Angle Through hole, Gold Flash plating, Natural Color, 2 positions, Glow Wire Compatible

ACTIVE

RoHS Compliant

Distributor Stock

Print Datasheet

FCI Brings You More

Contact our sales/technical support

Sample request

Customer drawing

Environmental Compliance Report

Specifications

Download document

| Dimensional                | General | Electrical | Mechanical | Physical | Mounting                                         | Other Features |
|----------------------------|---------|------------|------------|----------|--------------------------------------------------|----------------|
| Dimensional                |         |            |            |          |                                                  |                |
| Pitch                      |         |            |            |          | 4.2                                              |                |
| General                    |         |            |            |          |                                                  |                |
| Number of contacts         |         |            |            |          | 2                                                |                |
| Orientation                |         |            |            |          | Right Angle                                      |                |
| Series                     |         |            |            |          | 10127819                                         |                |
| Electrical                 |         |            |            |          |                                                  |                |
| Withstanding Voltage       |         |            |            |          | 1500 Vac, No breakdown.<br>Current leakage < 5mA |                |
| Current rating             |         |            |            |          | UP to 9 Amps                                     |                |
| Resistance (Contact)       |         |            |            |          | 10 milliohm max.                                 |                |
| Resistance (Insulation)    |         |            |            |          | 1000M ΩMin                                       |                |
| Voltage rating             |         |            |            |          | 600V                                             |                |
| Mechanical                 |         |            |            |          |                                                  |                |
| Durability (Mating cycles) |         |            |            |          | 30 Cycles                                        |                |
| Insertion force            |         |            |            |          | 14.7N max.                                       |                |
| Withdrawal Force           |         |            |            |          | 1 N min.                                         |                |
| Glow Wire Compatible       |         |            |            |          | Yes                                              |                |
| Physical                   |         |            |            |          |                                                  |                |
| Color (Housing)            |         |            |            |          | Natural                                          |                |
| Material (Contact)         |         |            |            |          | Brass                                            |                |
| Material (Housing)         |         |            |            |          | Nylon 66                                         |                |
| Plating (Contact area)     |         |            |            |          | Gold Flash                                       |                |
| Temperature (Range)        |         |            |            |          | -40°C to +105°C                                  |                |
| Mounting                   |         |            |            |          |                                                  |                |
| Mounting style (Board)     |         |            |            |          | Through Hole                                     |                |
| Other Features             |         |            |            |          |                                                  |                |
| Packaging (Type)           |         |            |            |          | Tray                                             |                |

Disclaimer : The information above is for reference only. For more technical details, refer to product specification and application specification.