

#### **PRODUCT BRIEF**

Intel® Tri-Band Wireless-AC 18260

WiGig (802.11ad) & Wi-Fi (802.11ac/agn) + Bluetooth\* Combo Module Intel® Wireless Gigabit Antenna-M 10041R

WiGig (802.11ad) Antenna Module



# Intel® Tri-Band Wireless-AC 18260 Intel® Wireless Gigabit Antenna-M 10041R



Intel® Tri-Band Wireless-AC 18260



Intel® Wireless Gigabit Antenna-M 10041R

#### **Product Description**

The Intel® Tri-Band Wireless-AC 18260 delivers high-speed, 60 GHz WiGig (802.11ad) wireless docking connectivity for mobile client device (2 in 1, tablet, laptop) with up to 4.7 Gbps of bidirectional throughput. It's available in the smaller M.2 Type 2230 form factor optimized for thinner and lighter mobile device designs. Complemented with the Intel® Wireless Gigabit Sink-M 13100, it enables wire-equivalent user experience for wireless docking, peripherals access and device-to-device communications.

The Intel® Tri-Band Wireless-AC 18260 includes Intel® Dual Band Wireless-AC 8260 for 802.11ac, dual-band, 2×2 Wi-Fi + Bluetooth\* connectivity for Wi-Fi speeds up to 867 Mbps¹, higher capacity, broader coverage and longer battery life. Intel® Tri-Band Wireless-AC 18260 supports innovative Intel-only features including Intel® Wireless Gigabit Docking, Intel® Wireless Display and Intel® vPro™ Technology.

Intel® Wireless Gigabit (802.11ad)	Benefits
Wireless Gigabit Docking (Client)	Allows wire-equivalent quality for up to two full HD displays, low-latency human interface (HID) devices, and multi-Gbps IO for on-desk productivity experience.
Wireless Access to Peripherials	Enables wire-free multi-Gbps connectivity for any USB 3.0 device, such as storage or HD camera that is WiGig-enabled or connected to a Wireless Gigabit dock station
Device to Device	Allows multi-Gbps connectivity between devices
WiGig Display Extension (WDE)	WiGig Wireless Display Extension, for visually-lossless, low latency, robust video and HD audio
WiGig Serial Extension (WSE)	WiGig Wireless Serial Extension, for efficient, native USB 3.0 transfers including Bulk and Isochronous
Client Dock Management	Dedicated, user-friendly Intel® Wireless Gigabit Dock Manager utility on the client to configure the dock settings (password protectable)
Dock Lock	Whitelist to allow OEM's control of client-dock connectivity capabilities.
Intel Dual Band Wireless-AC 8260 (802.11ac + Bluetooth)	Benefits
More Speed Better Coverage Larger Capacity 802.11ac, Dual Band, 80 MHz, 2×2	Delivers dramatically faster Wi-Fi speeds (up to 867 Mbps¹) than 802.11n, with more bandwidth per stream 433 Mbps), more capacity for more users (extended channel bonding 80 MHz), broader coverage and better battery life (more data transmit efficiencies reduces power consumption).
Bluetooth* 4.1	Dual-mode Bluetooth* 4.1 connects to the newest low-energy Bluetooth* products, as well as your familiar devices, such as headsets, keyboard, mice and more.
Experience the Intel Difference	
Wire-Like Desktop Connectivity Intel® Wireless Gigabit Docking	Allows wire-equivalent quality for up to two full HD displays, low-latency human interface (HID) devices, and multi-Gbps IO for on-desk productivity experience. Enables seamless connectivity to desktop devices and the Intel® Wireless Gigabit Dock Manager to easily configure Intel® Wireless Gigabit Docking from the client.
Intel <sup>®</sup> -vPro™ Technology <sup>2</sup>	Supports Intel's hardware-based security and management features built into Intel® Core™ vPro™ processors and chipsets that enables IT to manage PCs virtually anywhere, anytime while reducing deployment costs, improving security and ROI.
intel® Active Management Technology³	Using integrated platform capabilities and popular third-party management and security applications, Intel® AMT allows IT or managed service providers to better discover, repair, and protect their networked computing assets. Intel AMT is a feature of Intel® Core™ processors with Intel® vPro™ technology.
Intel Location Based Service <sup>4</sup>	Enables seamless and accurate Wi-Fi indoor location service for employees to see campus maps with reference to their location, locate the nearest resource (printer, conference, room, elevator, etc.), or for asset tracking.

#### Intel® Tri-Band Wireless-AC 18260 Module Specifications

Dimensions (H x W x D) M.2 2230: 22 mm  $\times$  30 mm  $\times$  S3 [1.5mm Max (Top Side)/ 0.1mm max (bottom side)] Weight 3.7gr Supported

Downloaded from Arrow.com.

Radio ON/OFF Control Supported in both hardware and software. One HW control is shared between Wi-Fi and WiGig, another

one is dedicated for Bluetooth

Connector interface M.2 Key 1-DP: 2xPCIe, USB, DP. Interface to Intel® Wireless Gigabit-Antenna M10041 Module using X-FL

(single coax cable to carry power, IF and control)

On/Off

Operating Temperature (Adapter Shield)

LED Output

0º to +80°C **Humidity Non-Operating** 50% to 90% RH non-condensing (at temperatures of 25°C to 35°C) Operating Systems Microsoft Windows 7\*, Microsoft Windows 8.1\* with connected standby

Wi-Fi Alliance Wi-Fi CERTIFIED\* for 802.11ac, Wi-Fi CERTIFIED\* a/b/g, Wi-Fi CERTIFIED\* n, WMM\*, WPA\*, WPA2\*, and WPS, WPS 2.0, Protected Management Frames, Wi-Fi Direct\* for peer to peer device connections.

IEEE 802.11abgn, 802.11ac, 802.11ad, 802.11d, 802.11e, 802.11i, 802.11h, 802.11w

IEEE WLAN Standard Dual Mode Bluetooth\* 2.1, 2.1+EDR, 3.0, 3.0+HS, 4.0 (BLE), 4.1

Bluetooth\*

### Intel® Wireless Gigabit Antenna-M10041R Module Specifications

Dimensions (H x W x D)  $9 \text{ mm} \times 25 \text{ mm} \times 2.45 \text{ mm}$ 

Weight 1g X.FL Connector interface Operating Temperature (Adapter Shield) 0º to +80°C

**Humidity Non-Operating** 50% to 90% RH non-condensing (at temperatures of 25°C to 35°C)

#### **Product Name Model Number** Version Intel® Tri-Band Wireless-AC 18260 18260NGW 802.11ad (Channels 1,2,3), 802.11ac 2x2, LTE Coex, Bluetooth 4.1, M.2 2230 1-DP 10041RRFW 802.11ad radio module Intel® Wireless Gigabit Antenna M10041R Intel® Wireless Gigabit Antenna M10042R 10042RRFW 802.11ad radio module



## For more information on Intel® Wireless products, visit intel.com/wireless

Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including without limitation, liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, lifesaving, or life sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice. For the most current product information, please visit: http://www.intel.com/wireless Intel, the Intel logo, Intel, and Intel Centrino are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

\*Other names and brands may be claimed as the property of others

Copyright © 2015 Intel Corporation. All rights reserved.



332933-002EN

Based on the theoretical maximum bandwidth enabled by 2x2 802.11acand 802.11ad implementations. Actual wireless throughput and/or range will vary depending on your specific operating system, hardware and software configurations. Check with your PC manufacturer for details.

<sup>2</sup> Intel® vPro™ Technology is sophisticated and requires setup and activation. Availability of features and results will depend upon the setup and configuration of your hardware, software and IT environment. To learn more visit: http://www.intel.com/technology/vpro

<sup>&</sup>lt;sup>3</sup> Requires activation and a system with a corporate network connection, an Intel® AMT-enabled chipset, network hardware and software. For notebooks, Intel® AMT may be unavailable or limited over a host OS-based VPN, when connecting wirelessly, on battery power, sleeping, hibernating or powered off. Results dependent upon hardware, setup & configuration. For more information, visit http://www.intel.com/technology/platform-technology/intel-amt

<sup>4</sup> Intel Location Based Service requires selected Intel wireless adapters and Intel® PROSet/Wireless WiFi Software v15.6 or later on Intel® 4th Gen Core processor-based PCs only