



CX-413-P-Z | Compact Photoelectric Sensor CX-400 Ver.2

DOWNLOAD
CAD data

Catalogs

Manuals


Software

HELP
FAQ

Print This Page



Email This Page



*Photo may vary from actual product.

[Dimensions](#)[Accessories \(Option\)](#)

Product Number	CX-413-P-Z	+ Favorite
Part Number	CX-413-P-Z	
Product Name	Compact Photoelectric Sensor	
Details	Thru-beam(Long sensing range)	
Series	Compact Photoelectric Sensor CX-400 Ver.2	
Features	Upgrade CX-400 series are environmentally and user friendly.	

CONTACT US
BY EMAIL

Please click your area to select country or region.

- ☒ Europe
- ☐ Africa
- ☐ Middle East
- ☐ Asia-Pacific
- ☐ East Asia
- ☐ The Americas

Albania

BY PHONE

U.S.A. +1-800-344-2112

Europe +49-8024-648-0

China +86-10-59255988

Singapore +65-6299-9181

[Global Sales Network](#)

FAQ

Spec Detail

As of July 29, 2015

Item	Specifications
Product Number	CX-413-P-Z
Part Number	CX-413-P-Z
Features	Upgrade CX-400 series are environmentally and user friendly.
Sensing range	30 m 98.425 ft
Sensing object	dia. 12 mm dia. 0.472 in or more opaque object (Note) If slit masks (optional) are fitted, an object of dia. 0.5 mm dia. 0.020 in (using round slit mask) can be detected.
Hysteresis	-
Repeatability(perpendicular to sensing axis)	0.5 mm 0.020 in or less
Supply voltage	12 to 24 V DC plus or minus 10 % Ripple P-P 10 % or less
Current consumption	Emitter: 25 mA or less Receiver: 10 mA or less
Output	PNP open-collector transistor - Maximum source current: 100 mA - Applied voltage: 30 V DC or less (between output and +V) - Residual voltage: 2 V or less (at 100 mA source current), 1 V or less (at 16 mA source current)
Output:Output operation	Switchable either Light-ON or Dark-ON
Output:Short-circuit protection	Incorporated
Response time	2 ms or less

RECOMMENDS

[Introduction to Automation Controls](#)

FEATURES

[A Vital Piece to the EV and HEV Puzzles](#)[Panasonic Relays for Photovoltaic Power Solutions](#)[TOUGH for Mobiles](#)[MID Solutions \(MIPTC/LDS\)](#)

Operation indicator	Orange LED(lights up when the output is ON) (incorporated on the receiver for thru-beam type)
Stability indicator	Green LED(lights up under stable light received condition or stable dark condition) (incorporated on the receiver for thru-beam type)
Power indicator	Green LED(lights up when the power is ON) (incorporated on the emitter)
Sensitivity adjuster	Continuously variable adjuster(incorporated on the receiver for thru-beam type)
Automatic interference prevention function	-
Protection	IP67 (IEC)
Ambient temperature	- 25 to +55 degrees -13 to +131 degrees Fahrenheit (No dew condensation or icing allowed), Storage: -30 to +70 degrees -22 to +158 degrees Fahrenheit
Ambient humidity	35 to 85 % RH, Storage: 35 to 85 % RH
Ambient illuminance	Incandescent light: 3,000 lx at the light-receiving face
Voltage withstandability	1,000 V AC for one min. between all supply terminals connected together and enclosure
Insulation resistance	20 MOhm , or more, with 250 V DC megger between all supply terminals connected together and enclosure
Vibration resistance	10 to 500 Hz frequency, 1.5 mm 0.059 in amplitude (10 G max.) in X, Y and Z directions for two hours each
Shock resistance	500 m/s2 acceleration (50 G approx.) in X, Y and Z directions for three times each
Emitting element (modulated)	Infrared LED
Emitting element (modulated):Peak emission wavelength	850 nm 0.033 mil
Material	Enclosure: PBT (polybutylene terephthalate) Lens: acrylic Indicator cover: acrylic
Accessory	-

[→ Dimensions](#)[↓ Accessories \(Option\)](#)[↑ Return to top](#)

Accessories (Option)

	+ Favorite		+ Favorite		+ Favorite
Product Number	CHX-SC2	Product Number	CN-24A-C2	Product Number	CN-24A-C5
Part Number	CHX-SC2	Part Number	CN-24A-C2	Part Number	CN-24A-C5
Series	Sensor Checker CHX-SC2	Series	Cable	Series	Cable

[→ More](#)[↑ Return to top](#)

CONTACT US If you have any questions, please select the option below to contact us or find answers.

[CONTACT BY EMAIL / PHONE](#)[FIND LOCAL OFFICE](#)[SEARCH FAQ](#)[↑ Return to top](#)

Customer Satisfaction Survey Questionnaire

Please help us improve Panasonic Automation Controls website by completing our online survey.

We are always looking to make our website more user-friendly and comfortable for you.

We aim to use feedback positively to improve our website, please give us comments or requests you may have.

Please take a few moments to answer these questions about our website. Thank you.

Easy to understand : ☐ yes ☐ no

Easy to find the information you need : ☐ yes ☐ no

Practical for your work : ☐ yes ☐ no

► [Comments about our website.](#)

Clear

Submit

 [Business](#) > [Industrial Devices](#) > [Automation Controls Top](#) > [FA Devices](#) > [Sensors](#) > [Photoelectric Sensors / Laser Sensors](#) > [Compact Photoelectric Sensor CX-400 Ver.2](#) > [Part Number](#) > [CX-413-P-Z](#)

Business Solutions

[Communication Solutions](#) [Security Systems](#) [Personal Computer](#) [Professional AV](#) [Document & Imaging Solutions](#)
[Terminal Solutions](#) [IT Solutions](#) [Recording Media](#)

Eco Solutions

[Eco Solutions](#)

Healthcare

[In Vitro Diagnostics](#) [Medical Imaging](#) [Hospital Systems](#) [Home / Personal Use](#) [Dental clinic / Dental Laboratory](#)

Industrial Devices

[Passive Components](#) [Connecting Components](#) [Sensors](#) [Speakers / others](#) [Industrial Devices](#) [Printed Wiring Board / Modules](#)
[Materials](#) [Semiconductors](#) [Storages, Supplies](#) [Batteries & Energy Products](#) [Factory Automation](#) [Motors, Compressors, Others](#)

Consumer

 [Print](#)

 [Page top](#)

[Area / Country](#)

Copyright © 2015 Panasonic Corporation
[Site Map](#) | [Terms of Use](#) | [Privacy](#) | [Global Home](#)