


FP1308

High frequency, high current power inductors



SMD Device

Product features

- 13.7 x 12.9 x 8.0mm surface mount package
- High current handling capability
- Ferrite core material
- Inductance range from 0.110 μ H to 0.440 μ H
- Current range from 32 to 120A
- Frequency range up to 2MHz
- Halogen free, lead free, RoHS compliant

Applications

- Voltage regulator modules (VRMs) for servers and microprocessors
- Multi-phase buck converters
- High frequency, high current switching power supplies

Environmental

- Storage temperature range (component): -40 °C to +125 °C
- Operating temperature range: -40 °C to +125 °C (ambient plus self-temperature rise)
- Solder reflow temperature: 260 °C
- I-S-0020 (latest revision) compliant



Product Specifications

Part Number ⁵	Rated Inductance (μ H)	OCL ¹ $\pm$ 10% (μ H)	I_{rms} ² (Amps)	I_{sat} ³ (Amps)	DCR (m Ω) @ 25°C Typical	DCR (m Ω) @ 25°C Max	K-factor ⁴
FP1308-R11-R	0.110	0.110	68	120	0.20	0.24	21.330
FP1308-R21-R	0.210	0.210	68	72	0.20	0.24	21.333
FP1308-R26-R	0.260	0.260	68	60	0.20	0.24	21.335
FP1308-R32-R	0.320	0.320	68	45	0.20	0.24	21.340
FP1308-R44-R	0.440	0.440	68	32	0.20	0.24	21.366

1 Open Circuit Inductance (OCL) Test Parameters: 100kHz, 1.0V_{rms}, 0.0Adc

2 I_{rms} : DC current for an approximate temperature rise of 40°C without core loss. Derating is necessary for AC currents. PCB pad layout, trace thickness and width, air-flow and proximity of other heat generating components will affect the temperature rise. It is recommended the part temperature not exceed 125°C under worst case operating conditions verified in the end application.

3 I_{sat} : Peak current for approximately 20% rolloff at +25°C.

4 K-factor: Used to determine B_{p-p} for core loss (see graph). $B_{p-p} = K \cdot L \cdot \Delta I$. B_{p-p} (mT): (Gauss), K: (K-factor from table), L: (inductance in μ H), ΔI (peak-to-peak ripple current in amps).


5 Part Number Definition: FP1308-xxx-R

- FP1308 = Product code and size
- xxx= Inductance value in μ H, R = decimal point. If no "R" is present, then third character = # of zeros.
- "-R" suffix = RoHS compliant



Powering Business Worldwide

Dimensions - mm




Part Marking: FP1308

xxx = Inductance value in μH . (R = Decimal point). If no "R" is present, then last character is # Of zeros

wwlyy = Date code


R = Revision level

Packaging Information - mm




Supplied in tape-and-reel packaging, 400 parts per reel, 13" diameter reel.


Temperature Rise vs. Total Loss



Core Loss



Inductance Characterist



Solder Reflow Profile




Table 1 - Standard SnPb Solder (T_P)

Package Thickness	Volume mm^3 <350	Volume mm^3 ≥ 350
<2.5mm	235°C	220°C
$\geq 2.5\text{mm}$	220°C	

Table 2 - Lead Free Solder (T_P)

Package Thickness	Volume mm^3 <350	Volume mm^3 350 - 2000	Volume mm^3 >2000
<1.6mm	260°C	260°C	260°C
1.6 - 2.5mm	260°C	250°C	245°C
$\geq 2.5\text{mm}$	260°C	245°C	245°C

Reference JDEC J-STD-020

Profile Feature	Standard SnPb Solder	Lead Free Solder
Preheat and Soak		
• Temperature min. (T_{smin})	100°C	150°C
• Temperature max. (T_{smax})	250°C	200°C
• Time (T_{smin} to T_{smax}) (t_s)	60-120 Seconds	60-120 Seconds
Average ramp up rate T_{smax} to T_P	3°C/ Second Max.	3°C/ Second Max.
Liquidous temperature (T_L)	217°C	217°C
Time at liquidous (t_L)	60-150 Seconds	60-150 Seconds
Peak package body temperature (T_P)*	Table 1	Table 2
Time (t_p)** within 5 °C of the specified classification temperature (T_P)	30 Seconds**	30 Seconds**
Average ramp-down rate (T_P to T_{smax})	6°C/ Second Max.	6°C/ Second Max.
Time 25°C to Peak Temperature	8 Minutes Max.	8 Minutes Max.

* Tolerance for peak profile temperature (T_P) is specified as a supplier minimum and a user maximum.

** Tolerance for time at peak profile temperature is specified as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
www.eaton.com/electronics

© 2017 Eaton
All Rights Reserved
Printed in USA
Publication No. DS4313 BU-SB111090
June 2017