



Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in-locking receptacles. These locking connectors reduce the probability of accidentally-disconnecting cords and dropping loads.
Lead time	Usually in Stock

Main

Product or Component Type	Power cord
Input Connection Type	IEC 60320 C20
Cable length	6 Ft (1.8 m)
Number of cables	6

Physical

Color	Black
Height	11.81 In (30 cm)
Width	3.15 In (8 cm)
Depth	2.76 In (7 cm)
Net Weight	4.76 Lb(US) (2.16 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Max line current	16 A
Input current limits	16 A

Output

Maximum Total Current Draw per Phase	16 A
Number of power socket outlets	1 IEC 60320 C19
Cord Length	6 Ft (1.8 m)

Conformance

Product Certifications	CCC[RETURN]CSA[RETURN]PSE[RETURN]UL Listed[RETURN]VDE
------------------------	---

Environmental

Ambient air temperature for operation	32...167 °F (0...75 °C)
Relative Humidity	20...80 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...167 °F (-25...75 °C)
Storage Relative Humidity	20...80 %
Storage altitude	0...50000 Ft (0...15240 m)

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304279723
Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	11.81 In (30 cm)
Package 1 Width	3.15 In (8 cm)
Package 1 Length	2.76 In (7 cm)
Package weight(Lbs)	4.76 Lb(US) (2.16 kg)
SCC14	10731304279720

Environmental data

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
Total lifecycle Carbon footprint	680 kg CO2 eq.
Carbon footprint of the manufacturing-phase [A1 to A3]	8.1359071787
Carbon footprint of the manufacturing-phase [A1 to A3]	8 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1616616909
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	671.0744306724
Carbon footprint of the use phase [B2, B3, B4, B6]	671 kg CO2 eq.
REACH free of SVHC	Yes
Lead free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.1424501289
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint (kg CO2 eq, Total Life cycle)	680
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant EU RoHS Declaration

REACH Regulation	REACH Declaration
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
Halogen content performance	Product contains halogen above thresholds
Circularity Profile	End Of Life Information
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status :	Commercialised
-----------------------	----------------