

PLT09HN2003R0P1#

Note: This datasheet may be out of date.

Please download the latest datasheet of PLT09HN2003R0P1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=PLT09HN2003R0P1%23

"#" indicates a package specification code.








< List of part numbers with package codes > PLT09HN2003R0P1B



Appearance & Shape







Features

PLT09H series is a common mode choke coil for DC lines. It is effective against the common mode noise that can cause radiative noise in power supply lines and interface lines. The additional normal mode inductance enables high suppression effect to radiation noise.

Features

- This is a wide frequency range type, applicable in applications ranging from a few MHz to several 100MHz
- 2. It features a low-profile design.

Applications

- 1. Noise suppression of SW power supply, DC-DC converter
- 2. DC power lines in AC adapter of Portable equipment



Applications

Other Usage For general



Packaging Information

Packaging	Specifications	Standard
		Packing
		Quantity
В	Вох	100

1 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





PLT09HN2003R0P1#

Note: This datasheet may be out of date.

Please download the latest datasheet of PLT09HN2003R0P1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=PLT09HN2003R0P1%23

"#" indicates a package specification code.



Specifications

Shape	Lead
Length	14.0mm
Length Tolerance	max.
Width	13.0mm
Width Tolerance	max.
Thickness	8.0mm
Thickness Tolerance	max.
Rated Current	3A
Derating of Rated Current	No
Rated Voltage	50Vdc
Withstanding Voltage	125Vdc
DC Resistance(max.)	0.03Ω
DC Resistance	0.03Ω max.
Insulation Resistance(min.)	10ΜΩ
Operating Temperature Range	-40°C to 85°C
Mass(typ.)	2.1g
Number of Circuit	1
Common Mode Inductance	20μHmin.
Operating Temperature Range(Self-temperature rise is included)	No
Brand	Murata

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



PLT09HN2003R0P1#


Note: This datasheet may be out of date.


Please download the latest datasheet of PLT09HN2003R0P1# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=PLT09HN2003R0P1%23

"#" indicates a package specification code.







Insertion Loss Characteristics

Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

