

# Ha-Vis EtherRail 4xAWG22/7 bl CAT5 500m



Part number	09 45 600 1430
Specification	Ha-Vis EtherRail 4xAWG22/7 bl CAT5 500m
HARTING eCatalogue	https://harting.com/09456001430

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	System cabling
Element	Bulk cables
Specification	Not assembled
Type of cable	Copper cable (round)
Description of the cable	for railway applications

### Version

Cable length	500 m
Number of cores	4
Core structure	4x AWG 22/7

### Technical characteristics

Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s
Limiting temperature	-40 +85 °C unmoved -25 +70 °C moved
Cable diameter	6.6 mm ± 0.2 mm
Minimum bending radius	6x Cable diameter
Test voltage U <sub>r.m.s.</sub>	1 kV Wire / wire / shielding
Coupling attenuation @ 20 °C / 10 MHz	8 mΩ/m
Conductor resistance @ 20 °C	≤54.4 Ω/km
Insulation resistance @ 20 °C	≥5,000 MΩ x km
Signal run time @ 20 °C	≤4.4 ns/m

Page 1 / 2 | Creation date 2025-03-25 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany

Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com



### Technical characteristics

|--|

## Material properties

Material (cable)	Polyolefin copolymer electron beam crosslinked Comp 752
Colour (cable)	Blue
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

## Specifications and approvals

Specifications	EN 45545-2 Fire protection on railway vehicles EN 50264-1 Fire protection on railway vehicles EN 50306-1 Fire protection on railway vehicles NFPA 130 Fire protection on railway vehicles UN/ECE-R 118 fire protection for rolling stock EN 50306-4 Resistance to ozone EN 60811-504 High low temperature resistance EN 60811-404 High oil resistance EN 60811-404 Alkali resistance EN 60811-404 Acid resistance EN 60811-404 Acid resistance EN 60811-404 Acid resistance
----------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Commercial data

Packaging size	1
Net weight	47,000 g
Net weight	61 g/m
Country of origin	Switzerland
European customs tariff number	85444290
GTIN	5713140062344
eCl@ss	27061801 Data and communication cable (copper)
ETIM	EC003249
UNSPSC 24.0	26121609

Page 2 / 2 | Creation date 2025-03-25 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany

Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com