CMPS5061 CMPS5062 CMPS5063 CMPS5064

SURFACE MOUNT SILICON CONTROLLED RECTIFIER



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMPS5061 Series types are epoxy molded PNPN Silicon Controlled Rectifiers manufactured in an SOT-23 case, designed for control systems and sensing circuit applications.



CMPS5062: P2B CMPS5063: P2C CMPS5064: P2D



MAXIMUM RATINGS: (T _A =25°C)	SYMBOL	CMPS5061	CMPS5062	CMPS5063	CMPS5064	UNITS
Peak Repetitive Off-State Voltage	V_{DRM}	100	200	300	400	V
Peak Repetitive Reverse Voltage	V_{RRM}	100	200	300	400	V
RMS On-State Current	I _T (RMS)		0.2		Α	
Average On-State Current	$I_{T(AV)}$		0.16			
Power Dissipation	P_{D}			mW		
Operating Junction Temperature	TJ	-65 to +125				°C
Storage Temperature	T _{stg}		-65 to	+150		°C
Thermal Resistance	Θ_{JA}	286				°C/W

	CAL CHARACTERISTICS: (T _A =25°C) TEST CONDITIONS		S5061 MAX		S5062 MAX		S5063 MAX		S5064 MAX	UNITS
IDRM	V_D =Rated V_{DRM} , R_{GK} =1.0 $K\Omega$	-	1.0	-	1.0	-	1.0	-	1.0	μΑ
IRRM	V_D =Rated V_{DRM} , R_{GK} =1.0 $K\Omega$	-	1.0	-	1.0	-	1.0	-	1.0	μΑ
I _{DRM}	V_D =Rated V_{DRM} , R_{GK} =1.0K Ω , T_C =125°C	-	50	-	50	-	50	-	50	μΑ
^I RRM	V_D =Rated V_{DRM} , R_{GK} =1.0 $K\Omega$, T_C =125 $^{\circ}C$	-	50	-	50	-	50	-	50	μΑ
V_{TM}	I _T =1.2A	-	1.7	-	1.7	-	1.7	-	1.7	V
l _{GT}	$V_D = 7.0V, R_L = 100\Omega$	-	200	-	200	-	200	-	200	μΑ
V_{GT}	$V_D = 7.0V, R_L = 100\Omega$	-	8.0	-	8.0	-	8.0	-	8.0	V
V_{GD}	V_D = Rated V_{DRM} , R_L =100 Ω , T_C =125°C	0.1	-	0.1	-	0.1	-	0.1	-	V
lΗ	R_{GK} =1.0 $K\Omega$	-	5.0	-	5.0	-	5.0	-	5.0	mA
ton	V_D = Rated V_{DRM} , I_{GT} =1.0mA, R_{GK} =1.0K Ω , di/dt=6.0A/ μ s	2	.8 TYP	2	.8 TYP	2	8 TYP	2	.8 TYP	μs


R10 (11-February 2011)


CMPS5061 CMPS5062 CMPS5063 CMPS5064

SURFACE MOUNT SILICON CONTROLLED RECTIFIER



SOT-23 CASE - MECHANICAL OUTLINE





LEAD CODE:

- 1) Cathode
- 2) Gate
- 3) Anode

MARKING CODES: CMPS5061: P2A CMPS5062: P2B CMPS5063: P2C CMPS5064: P2D

DIMENSIONS						
	INCHES		MILLIMETERS			
SYMBOL	MIN	MAX	MIN	MAX		
Α	0.003	0.007	0.08	0.18		
В	0.006	-	0.15	-		
С	-	0.005	-	0.13		
D	0.035	0.043	0.89	1.09		
E	0.110	0.120	2.80	3.05		
F	0.0)75	1.90			
G	0.0)37	0.95			
Н	0.047	0.055	1.19	1.40		
	0.083	0.098	2.10	2.49		
J	0.014	0.020	0.35	0.50		

SOT-23 (REV: R3)

R10 (11-February 2011)

www.centralsemi.com

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms



Product End of Life Notification

PDN ID:	PDN01018
Notification Date:	1/29/16
Last Buy Date:	7/29/16
Last Shipment Date	1/29/17

Summary: The CMPS5061, CMPS5062, and CMPS5063 Silicon Controlled Rectifiers are being discontinued and are now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

Central Part Number	Replacement		
CMPS5061 BK	CMPS5061 BK	H	
CMPS5061 TR	CMPS5061 TR	Н	
CMPS5062 BK	CMPS5062 BK	Н	
CMPS5062 TR	CMPS5062 TR	H	
CMPS5063 BK	CMPS5064 BK		
CMPS5063 TR	CMPS5064 TR		

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002