



**Micro Commercial Components** 



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

# W005M **THRU W10M**

### **Features**

- Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)
  Halogen free available upon request by adding suffix "-HF"
- Low Profile Package
- Any Mounting Position
- Silver Plated Copper Leads
- Surge Overload Rating Of 50 Amps
- UL Řecognized File # Ĕ165989
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

### Maximum Ratings

- Operating Temperature: -55°C to +125°C
- Storage Temperature: -55°C to +150°C


MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Recurrent	RMS	DC
Number		Peak Reverse	Voltage	Blocking
		Voltage	_	Voltage
W005M	W005M	50V	35V	50V
W01M	W01M	100V	70V	100V
W02M	W02M	200V	140V	200V
W04M	W04M	400V	280V	400V
W06M	W06M	600V	420V	600V
M80W	W80W	800V	560V	800V
W10M	W10M	1000V	700V	1000v

#### Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I <sub>F(AV)</sub>	1.5A	T <sub>J</sub> = 25°C
Peak Forward Surge Current	I <sub>FSM</sub>	50A	8.3ms, half sine
Maximum Forward Voltage Drop Per Element	$V_{F}$	1.0V	$I_{FM} = 1.5A;$ $T_J = 25^{\circ}C^*$
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	10μA 1mA	$T_J = 25^{\circ}C$ $T_J = 100^{\circ}C$

<sup>\*</sup>Pulse test: Pulse width 300 µsec, Duty cycle 1%

# 1.5 Amp Single Phase **Bridge Rectifier** 50 to 1000 Volts




DIMENSIONS						
	INCHES		MM			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α		.358		9.10		
В		.225		5.70		
С	1.000		25.40			
D	1.098		27.90			
Е	.180	.220	4.60	5.60		
F	.028	.032	0.71	0.81		




## W005M thru W10M

Figure 1
Typical Forward Characteristics




Instantaneous Forward Current - Amperesversus Instantaneous Forward Voltage - Volts



Average Forward Rectified Current - Amperes versus Case Temperature -  $^{\circ}\text{C}$ 


### Micro Commercial Components

Figure 2 Typical Reverse Characteristics



Instantaneous Reverse Leakage Current - MicroAmperesversus Percent Of Rated Peak Reverse Voltage - Volts

Figure 4 Peak Forward Surge Current



Peak Forward Surge Current - Amperesversus Number Of Cycles At 60Hz - Cycles



### **Ordering Information**

Device	Packing
(Part Number)-BP	Bulk;10K/Ctn

Note: Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.