

**Part Number :** 2166201043

Product Description: Squba 3.6 Female-to-Squba

3.6 Female Off-the-Shelf (OTS) Cable Assembly,

3.60mm Pitch, Single Row, 600.00mm Length, Tin (Sn)

Plating, 4 Circuits, Black **Series Number:** 216620

**Status**: Active

**Product Category:** Power and Signal Cable

**Assemblies** 



#### **Documents & Resources**

### **Drawings**

2166201043 sd.pdf

**3D Models and Design Files** 

STEP AP242

**SOLIDWORKS** 

Creo

# **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	Not Reviewed per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Dodecamethylcyclohexasiloxane; Decamethylcyclopentasiloxane; Octamethylcyclotetrasiloxane per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant per EU 2015/863

### **Compliance Statements**

• EU RoHS

- REACH SVHC
- Low-Halogen

## **Industry Documents**

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## **Substances of Interest**

PFAS

## **EU RoHS Certificate of Compliance**

# Additional Product Compliance Information

## **Part Details**

### **General**

Status	Active
Category	Power and Signal Cable Assemblies
Series	216620
Description	Squba 3.6 Female-to-Squba 3.6 Female Off-the-Shelf (OTS) Cable Assembly, 3.60mm Pitch, Single Row, 600.00mm Length, Tin (Sn) Plating, 4 Circuits, Black
Application	Power, Signal, Wire-to-Wire
Assembly Configuration	Dual Ended Connectors
Connector to Connector	Squba 3.6-to-Squba 3.6
Product Name	Squba
Туре	Discrete Wire Assembly, Sealed Assembly
UPC	193264746408

#### **Electrical**

Current - Maximum per Contact	14.0A
Voltage - Maximum	600V

## **Physical**

Cable Length	600.00mm
Cable Lefigur	000.00111111

Circuits (Loaded)	4
Circuits (maximum)	4
Color - Resin	Black
Gender	Female-Female
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Matte Tin
Material - Plating Termination	Matte Tin
Material - Resin	Nylon
Net Weight	48.200/g
Number of Rows	1
Overmolded	No
Packaging Type	Bag
Pitch - Mating Interface	3.60mm
Plating min - Mating	2.540µm
Plating min - Termination	2.540µm
Single Ended	No
Termination Interface Style	Crimp or Compression
Wire/Cable Type	UL 11028
Wire Size (AWG)	16

# Mates With / Use With

# Mates with Part(s)

Description	Part Number
Squba 3.6 Sealed Plug Assembly, 3.60mm Pitch, 2 Circuits, Single Row, Glow-Wire Capable, Black, UL1007/UL1061 Compatible	<u>2077780002</u>

This document was generated on Sep 11, 2025