



Color:  white

Technical data	
Marking method	Thermal transfer
Marking	plain
Delivery form	Roll
Delivery form configuration	2,500 markers/reel
Printing device	Smart Printer (thermal transfer printer)

Physical data	
Depth	0.26 mm
Length	23 mm
Marking surface	4 x 23 mm

Mechanical data	
Mounting type	Pushing in
Smear resistance	in conjunction with 258-5005 Ink Ribbon

Material data	
Color	white
Material	Polyester
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	without adhesive
Halogen-free	Yes
Weight	220 g
Fire load	0 MJ



Environmental requirements		
Ambient temperature (storage)		+10 ... +22 °C
Ambient temperature (operation)		-20 ... +80 °C
Relative humidity		40 ... 50 %

Commercial data		
Product Group		2 (Terminal Block Accessories)
PU (SPU)		1 pcs
Packaging type		Box
Country of origin		DE
GTIN		4050821675006
Customs tariff number		39269097900

Product classification		
UNSPSC		55121612
eCl@ss 10.0		27-40-04-01
eCl@ss 9.0		27-40-06-29
ETIM 9.0		EC001530
ETIM 8.0		EC001530
ECCN		NO US CLASSIFICATION

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 211-821

↓

Documentation

Operating Instructions

211-821 Information on printing material

1

28.08.2020

pdf

1248.71 KB

↓

1 Compatible Products
1.1 Optional Accessories
1.1.1 Marking
1.1.1.1 Marking sleeve



**Item No.: 211-922**  
Nozzles; Length: 23 mm; For the use of 211-821; halogenated; Cable outer diameter: 1.5 ... 2.5 mm; transparent



**Item No.: 211-926**  
Nozzles; Length: 23 mm; For the use of 211-821; halogenated; Cable outer diameter: 10.0 ... 14.0 mm; transparent



**Item No.: 211-927**  
Nozzles; Length: 23 mm; For the use of 211-821; halogenated; Cable outer diameter: 14.0 ... 22.0 mm; transparent



**Item No.: 211-923**  
Nozzles; Length: 23 mm; For the use of 211-821; halogenated; Cable outer diameter: 2.0 ... 4.0 mm; transparent



**Item No.: 211-924**  
Nozzles; Length: 23 mm; For the use of 211-821; halogenated; Cable outer diameter: 4.0 ... 7.0 mm; transparent



**Item No.: 211-925**  
Nozzles; Length: 23 mm; For the use of 211-821; halogenated; Cable outer diameter: 6.0 ... 10.0 mm; transparent



**Item No.: 211-823**  
Nozzles; Length: 23 mm; For the use of 211-821; halogen-free; Cable outer diameter: 1.4 ... 5.0 mm; transparent



**Item No.: 211-824**  
Nozzles; Length: 23 mm; For the use of 211-821; halogen-free; Cable outer diameter: 5.0 ... 11.0 mm; transparent



**Item No.: 211-829**  
Nozzles; Length: 23 mm; For the use of 211-821; halogen-free; transparent


Installation Notes
Marking




Remove the printed marker from the reel.



Slide the marker into the marking sleeve receptacle. Replacing the marker is also possible after the conductor has been terminated.



Slide the marker through the marker slot up to the end of the sleeve.



Then remove the rest of the card by twisting it off.