
NPN Epitaxial Silicon Darlington Transistor

KSE800



1. Emitter
2. Collector
3. Base

TO−126−3LD
CASE 340AS

Features


- Monolithic Construction with Built−in Base−Emitter Resistors
- High DC Current Gain: h_{FE} = 750 (Min.) @ I_C = 1.5 and 2.0 A DC
- Complement to KSE700
- This is a Pb−Free Device

ABSOLUTE MAXIMUM RATINGS (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Value	Units
V_{CBO}	Collector−Base Voltage	60	V
V_{CEO}	Collector−Emitter Voltage	60	V
V_{EBO}	Emitter−Base Voltage	5	V
I_C	Collector Current	4	A
I_B	Base Current	0.1	A
P_C	Collector Dissipation (T_C = 25°C)	40	W
T_J	Junction Temperature	150	°C
T_{STG}	Storage Temperature	−55 ~ 150	°C


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

MARKING DIAGRAM



&3 = 3−Digit Date Code
KSE800 = Specific Device Code

EQUIVALENT CIRCUIT



R1 ≅ 10 kΩ
R2 ≅ 0.6 kΩ

ORDERING INFORMATION

Device	Package	Shipping
KSE800STU	TO−126−3LD (Pb−Free)	1920 Units / Tube

© Semiconductor Components Industries, LLC, 2001

Downloaded from Arrow.com.

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Test Condition	Min	Max	Units
BV_{CEO}	Collector−Emitter Breakdown Voltage	I_C = 50 mA, I_B = 0	60		V
I_{CEO}	Collector Cut−off Current	V_{CE} = 60 V, I_B = 0		100	μA
I_{CBO}	Collector Cut−off Current	V_{CB} = Rated BV_{CEO}, I_E = 0 V_{CB} = Rated BV_{CEO}, I_E = 0, T_C = 100°C		100 500	μA
I_{EBO}	Emitter Cut−off Current	V_{BE} = 5 V, I_C = 0		2	mA
h_{FE}	DC Current Gain	V_{CE} = 3 V, I_C = 1.5 A V_{CE} = 3 V, I_C = 4 A	750 100		
V_{CE}(sat)	Collector−Emitter Saturation Voltage	I_C = 1.5 A, I_B = 30 mA I_C = 4 A, I_B = 40 mA		2.5 3	V
V_{BE}(on)	Base−Emitter On Voltage	V_{CE} = 3 V, I_C = 1.5 A V_{CE} = 3 V, I_C = 4 A		2.5 3	V

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Downloaded from Arrow.com.

TYPICAL CHARACTERISTICS




Figure 1. Static Characteristic




Figure 2. DC Current Gain




Figure 3. Collector−Emitter Saturation Voltage Base−Emitter Saturation Voltage




Figure 4. Collector Output Capacitance




Figure 5. Safe Operating Area






Figure 6. Power Derating

Downloaded from Arrow.com.

TO−126−3LD
CASE 340AS
ISSUE O

DATE 30 SEP 2016





PRODUCTION CODE	TERMINAL LENGTH "D"	TERMINAL LENGTH "E"
TSSTU	3.45 - 4.05	6.45 - 7.45
TSTU	2.36 - 2.96	5.36 - 6.36
NONE (STD LENGTH)	12.76 - 13.36	15.76 - 16.76

NOTES:

A. NO INDUSTRY STANDARD APPLIES TO THIS PACKAGE
B. ALL DIMENSIONS ARE IN MILLIMETERS
C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR PROTRUSIONS

△D FOR TERMINAL LENGTH "D", REFER TO TABLE

△E FOR TERMINAL LENGTH "E", REFER TO TABLE

DOCUMENT NUMBER:	**98AON13817G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**TO−126−3LD**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

Downloaded from Arrow.com.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

◊

Downloaded from Arrow.com.