

www.vishay.com

Vishay General Semiconductor

Glass Passivated Junction Plastic Rectifier



DO-41 (DO-204AL)

PRIMARY CHARACTERISTICS								
I _{F(AV)}	1.0 A 50 V, 100 V, 200 V, 400 V, 600 V, 800 V, 1000 V							
V _{RRM}								
I _{FSM} (8.3 ms sine-wave)	30 A							
I _R	5.0 μA							
V _F	1.1 V							
T _J max.	175 °C							
Package	DO-41 (DO-204AL)							
Circuit configuration	Single							

FEATURES

Superectifier structure for high reliability application



· Cavity-free glass-passivated junction

- Low forward voltage drop
- Low leakage current, typical I_R less than 0.1 μA
- · High forward surge capability
- Solder dip 275 °C max. 10 s, per JESD 22-B106
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

TYPICAL APPLICATIONS

For use in general purpose rectification of power supplies, inverters, converters and freewheeling diodes for consumer applications.

MECHANICAL DATA

Case: DO-41 (DO-204AL), molded epoxy over glass body Molding compound meets UL 94 V-0 flammability rating Base P/N-E3 - RoHS-compliant, commercial grade

Terminals: matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

E3 suffix meets JESD 201 class 1A whisker test

Polarity: color band denotes cathode end

MAXIMUM RATINGS (T _A = 25 °C unless otherwise noted)										
PARAMETER		SYMBOL	1N4001GP	1N4002GP	1N4003GP	1N4004GP	1N4005GP	1N4006GP	1N4007GP	UNIT
Maximum repetitive peak reverse voltage		V_{RRM}	50	100	200	400	600	800	1000	٧
Maximum RMS voltage		V _{RMS} ⁽¹⁾	35	70	140	280	420	560	700	V
Maximum DC blocking	voltage	V _{DC} (1)	50	100	200	400	600	800	1000	V
Maximum average forw current 0.375" (9.5 mm) at T _A = 75 °C						1.0				
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load		I _{FSM} ⁽¹⁾	30							А
Non-repetitive peak $t_p = 1 \text{ ms}$			45							
forward surge current square waveform	$t_p = 2 \text{ ms}$	I _{FSM} ⁽¹⁾	35							
$T_A = 25 ^{\circ}\text{C (fig. 3)}$ $t_p = 5 \text{ms}$			30							
Maximum full load reverse current, full cycle average 0.375" (9.5 mm) lead length $T_A = 75\ ^{\circ}\text{C}$		I _{R(AV)} (1)	30							μA
Rating for fusing (t < 8.3 ms)		I ² t ⁽²⁾	3.7							A ² s
Operating junction and storage temperature range			-65 to +175							°C

Notes

(1) JEDEC® registered values

(2) For device using on bridge rectifier application



www.vishay.com

Vishay General Semiconductor

ELECTRICAL CHARACTERISTICS (T _A = 25 °C unless otherwise noted)										
PARAMETER	TEST CONDITIONS	SYMBOL	1N4001GP	1N4002GP	1N4003GP	1N4004GP	1N4005GP	1N4006GP	1N4007GP	UNIT
Maximum instantaneous forward voltage	1.0 A	V _F		1.1						V
Maximum DC reverse current	T _A = 25 °C	ı (1)	5.0							
at rated DC blocking voltage	T _A = 125 °C	I _R ⁽¹⁾	50						μA	
Typical reverse recovery time	$I_F = 0.5 A,$ $I_R = 1.0 A,$ $I_{rr} = 0.25 A$	t _{rr}	2.0					μs		
Typical junction capacitance	4.0 V, 1 MHz	CJ	8.0					pF		

Note

(1) JEDEC® registered values

THERMAL CHARACTERISTICS (T _A = 25 °C unless otherwise noted)									
PARAMETER	SYMBOL	SYMBOL 1N4001GP 1N4002GP 1N4003GP 1N4004GP 1N4005GP 1N4006GP 1N4007GP U							UNIT
Typical thormal registance	R _{0JA} (1)	55							°C/
Typical thermal resistance	R _{0JL} (1)	25						W	

Note

⁽¹⁾ Thermal resistance from junction to ambient at 0.375" (9.5 mm) lead length, PCB mounted

ORDERING INFORMATION (Example)									
PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE					
1N4004GP-E3/54	0.335	54	5500	13" diameter paper tape and reel					
1N4004GP-E3/73	0.335	73	3000	Ammo pack packaging					

RATINGS AND CHARACTERISTICS CURVES ($T_A = 25$ °C unless otherwise noted)




Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-repetitive Peak Forward Surge Current



Vishay General Semiconductor

www.vishay.com




Fig. 3 - Non-Repetitive Peak Forward Surge Current




Fig. 4 - Typical Instantaneous Forward Characteristics




Fig. 5 - Typical Reverse Characteristics




Fig. 6 - Typical Junction Capacitance





Fig. 7 - Typical Transient Thermal Impedance



www.vishay.com Vishay General Semiconductor

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)



Note

• Lead diameter is $\frac{0.026 (0.66)}{0.023 (0.58)}$ for suffix "E" part numbers





Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

© 2024 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED