# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# Rack PDU, Switched, 1U, 20A, 120V, (8)5-20



AP7901B

### **Overview**

| Lead time Usually in Stock |  |
|----------------------------|--|
|----------------------------|--|

### Main

| Colour                    | Black   |
|---------------------------|---|
| product or component type | PDU   |
| PDU type                  | Switched  |
| Cord length               | 3.7 m   |
| Number of cables          | 1   |
| provided equipment        | Cord retention bracket(s) Horizontal mounting brackets User manual Installation guide |

# Complementary

| J                        |               |
|--------------------------|---------------|
| Input Voltage            | 100 V         |
|                          | 120 V         |
| Height                   | 4.4 cm        |
| Width                    | 44.5 cm       |
| Output Voltage           | 120 V         |
| Depth                    | 10.8 cm       |
| net weight               | 2.27 kg       |
| mounting location        | Front         |
|                          | Rear          |
| Mounting preference      | No preference |
| Input Plug Type          | NEMA L5-20P   |
| mounting mode            | Rack-mounted  |
| Rack units               | 1U            |
| Mounting position        | Horizontal    |
| [In] rated current       | 16 A          |
| Permissible voltage      | 100120 V      |
| Input current limits     | 20 A          |
| Load capacity            | 1900 VA       |
| Network frequency        | 50/60 Hz      |
| Outlet type and quantity | 8 NEMA 5-20R  |

Downloaded from Arrow.com.

# **Environment**

| Product certifications      | cUL listed                               |
|-----------------------------|--|
|                             | CSA                                      |
|                             | Industry Canada                          |
|                             | UL listed                                |
|                             | OL listed                                |
| Standards                   | FCC part 15 class A                      |
|                             | ICES-003                                 |
|                             | 10-10-10-10-10-10-10-10-10-10-10-10-10-1 |
|                             | UL 60950                                 |
| Ambient air temperature for | 045 °C                                   |
| operation                   |  |
| Relative humidity           | 095 %                                    |
|                             |  |
| Operating altitude          | 010000 ft                                |
|                             |  |
| Ambient air temperature for | -2565 °C                                 |
| storage                     |  |
| Storage Relative Humidity   | 095 %                                    |
|                             |  |
| Storage altitude            | 0.00000000015240.000000000 m             |

# **Packing Units**

| Unit Type of Package 1       | PCE     |
|------------------------------|---------|
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 7 cm    |
| Package 1 Width              | 34.3 cm |
| Package 1 Length             | 47 cm   |
| Package 1 Weight             | 3.45 kg |

# **Contractual warranty**

Warranty 2 years repair or replace

### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

| Resource    | performance      |
|-------------|------------------|
| i toooai oo | poi 101 111a1100 |

|  | Energy Efficient Product |
|--|--------------------------|
|--|--------------------------|



## Well-being performance

| Lead Free |  |
|-----------|--|
|           |  |





### **Certifications & Standards**

| Reach Regulation         | REACh Declaration             |
|--------------------------|-------------------------------|
| Eu Rohs Directive        | Compliant with Exemptions     |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile      | End of Life Information       |