



## SinglFuse™ SF-3812TM-T Series Features

- Replacement for Bourns® Telefuse™ models B0500T, B1250T and B2000T
- For use in telecommunication circuit applications requiring low current protection with high surge tolerance
- Overcurrent protection to Telcordia GR-1089-CORE Issue 7 & UL 60950
- EIA 3812 (10030 metric) footprint
- UL 248-14 compliant
- Surface mount packaging for automated assembly
- RoHS compliant\* and halogen free\*\*

## SF-3812TM-T Series – SinglFuse™ Telefuse™ Telecom Protectors

### Clearing Time Characteristics for Series

| % of Current Rating | Clearing Time at 25 °C |             |
|---------------------|------------------------|-------------|
|                     | Min.                   | Max.        |
| 100 %               | 4 hours                | —           |
| 250 %               | 1 second               | 120 seconds |

### Additional Information

Click these links for more information:



### Electrical Characteristics

| Model           | Rated Current (A) | Resistance (Ω) Typ.*** | Rated Voltage | Interrupting Rating               | Typical I <sup>2</sup> t (A <sup>2</sup> s) **** | Max. Power Dissipation (W) | Certifications               |
|-----------------|-------------------|------------------------|---------------|-----------------------------------|--|----------------------------|------------------------------|
|                 |                   |                        |               |                                   |  |                            | cUL: <a href="#">E198545</a> |
| SF-3812TM050T-2 | 0.50              | 0.48                   | 600 VAC       | 60 A @ 600 VAC                    | 1.4  | 0.4                        | ✓                            |
| SF-3812TM125T-2 | 1.25              | 0.1                    |               | 60 A @ 250 VAC                    | 22   | 0.6                        | ✓                            |
| SF-3812TM200T-2 | 2.00              | 0.055                  |               | 50 A @ 250 VDC<br>100 A @ 125 VDC | 24   | 0.8                        | ✓                            |

\*\*\* Resistance value measured with ≤10 % rated current at 25 °C ambient. Tolerance ± 30 %.

\*\*\*\* Melting I<sup>2</sup>t calculated at 10 times rated current.

### Environmental Characteristics

|                                 |                                 |
|---------------------------------|---------------------------------|
| Operating Temperature.....      | -55 °C to +125 °C               |
| Storage Conditions              |                                 |
| Temperature .....               | +15 °C to +30 °C                |
| Humidity.....                   | 20 % to 70 %                    |
| Shelf Life.....                 | 2 years from manufacturing date |
| Moisture Sensitivity Level..... | 1                               |
| ESD Classification (HBM).....   | Class 6                         |



**WARNING Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

\* RoHS Directive 2015/863, Mar 31, 2015 and Annex.

\*\* Bourns considers a product to be "halogen free" if (a) the Bromine (Br) content is 900 ppm or less; (b) the Chlorine (Cl) content is 900 ppm or less; and (c) the total Bromine (Br) and Chlorine (Cl) content is 1500 ppm or less.


"SinglFuse" is a trademark of Bourns, Inc.

Specifications are subject to change without notice.


The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.

Users should verify actual device performance in their specific applications.

Average Pre-Arcing Time vs. Current Curves



Average I²t vs. t Curves



Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

# SF-3812TM-T Series – SinglFuse™ Telefuse™ Telecom Protectors



## Typical Part Marking

Represents total content. Layout may vary.



| Rated Current | Part Marking |
|---------------|--------------|
| 0.5 A         | 0.5          |
| 1.25 A        | 1.25         |
| 2.0 A         | 2.0          |

## How to Order


**SF - 3812 TM 050 T - 2**

SinglFuse™ \_\_\_\_\_  
 Product Designator \_\_\_\_\_  
 SMD Footprint \_\_\_\_\_  
 3812 = EIA 3812  
 (10030 metric) \_\_\_\_\_  
 Fuse Blow Type \_\_\_\_\_  
 TM = Time Lag, Telecom \_\_\_\_\_  
 Rated Current \_\_\_\_\_  
 050 ~ 200 (0.50 A ~ 2.00 A) \_\_\_\_\_  
 Structure Type \_\_\_\_\_  
 T = Ceramic Tube \_\_\_\_\_  
 Packaging Type \_\_\_\_\_  
 - 2 = Tape & Reel \_\_\_\_\_

## Packaging



|                |                       |
|----------------|-----------------------|
| Reel Dimension | 13-inch Tape and Reel |
| Specification  | EIA 481-2             |
| Quantity       | 2,500 pieces          |
| Packaging Code | -2                    |

## Recommended Pad Layout




DIMENSIONS:  $\frac{\text{MM}}{\text{(INCHES)}}$

## Product Dimensions



DIMENSIONS:  $\frac{\text{MM}}{\text{(INCHES)}}$

## Current Rating Thermal Derating Curve




Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

**Solder Reflow Recommendations**




| Profile Feature   | Pb-Free Assembly                   |
|---|------------------------------------|
| Preheat / Soak:<br>Temperature Min. ( $T_{smin}$ )<br>Temperature Max. ( $T_{smax}$ )<br>Time ( $t_s$ ) from ( $T_{smin}$ to $T_{smax}$ ) | 150 °C<br>200 °C<br>60–180 seconds |
| Ramp Up Rate ( $T_L$ to $T_p$ )   | 3 °C / second max.                 |
| Ramp Up Rate ( $T_{smax}$ to $T_L$ )  | 5 °C / second max.                 |
| Liquidous Temperature ( $T_L$ )<br>Time ( $t_L$ ) maintained above $T_L$  | 217 °C<br>60–90 seconds            |
| Peak Package Body Temperature ( $T_p$ )   | 260 °C +0/-5 °C                    |
| Time within 5 °C of actual peak temperature ( $T_p$ )   | 10–30 seconds*                     |
| Ramp Down Rate ( $T_p$ to $T_L$ )   | 6 °C / second max.                 |
| Time 25 °C to Peak Temperature  | 8 minutes max.                     |
| Do not exceed   | 260 °C                             |

\* Tolerance for peak profile temperature ( $T_p$ ) is defined as a supplier minimum and a user maximum.

**Solder Wave Recommendations**

Peak Temperature (Dwell Time)



| Profile Feature  | Pb-Free Assembly        |
|--|-------------------------|
| Preheat:<br>Temperature Max. ( $T_{smax}$ )<br>Time (Min. to Max.) | 150 °C<br>60–90 seconds |
| Solder Pot Temperature   | 260 °C max.             |
| Solder Dwell Time  | 2–3 seconds             |

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

## Lightning Surge Specifications (Fuse Not Allowed to Open)

| Surge Specification | Max. Rise / Min. Decay ( $\mu$ sec.) | Min. Peak Current (A) | Min. Peak Voltage (V) | Repetitions Each Polarity | Recommended Fuse     |
|---------------------|--------------------------------------|-----------------------|-----------------------|---------------------------|----------------------|
| Telcordia GR-1089   | 10 / 1000                            | 100                   | 600                   | 25                        | 1.25 A / 2 A         |
|                     |                                      | 100                   | 1000                  | 25                        | 1.25 A / 2 A         |
|                     |                                      | 100*                  | 2000                  | 5                         | 1.25 A / 2 A         |
|                     | 10 / 700                             | 160                   | 4000                  | 5                         | 1.25 A / 2 A         |
|                     | 10 / 360                             | 100                   | 1000                  | 25                        | 1.25 A / 2 A         |
|                     |                                      | 25                    | 1000                  | 5                         | 0.5 A / 1.25 A / 2 A |
|                     | 10 / 250                             | 200*                  | 4000                  | 5                         | 1.25 A / 2 A         |
|                     | 8 / 20                               | 750*                  | 6000                  | 1                         | 1.25 A / 2 A         |
|                     |                                      | 600*                  | 6000                  | 5                         | 1.25 A / 2 A         |
|                     |                                      | 300                   | 5000                  | 5                         | 1.25 A / 2 A         |
|                     |                                      | 800*                  | 2000                  | 5                         | 1.25 A / 2 A         |
|                     |                                      | 750                   | 1500                  | 5                         | 1.25 A / 2 A         |
|                     |                                      | 400                   | 800                   | 5                         | 1.25 A / 2 A         |
|                     |                                      | 300                   | 600                   | 5                         | 1.25 A / 2 A         |
|                     | 2 / 10                               | 500                   | 5000                  | 1                         | 1.25 A / 2 A         |
|                     |                                      | 500                   | 2500                  | 10                        | 1.25 A / 2 A         |
|                     |                                      | 300                   | 1500                  | 10                        | 1.25 A / 2 A         |
|                     |                                      | 200                   | 1000                  | 5                         | 1.25 A / 2 A         |
|                     |                                      | 100                   | 800                   | 5                         | 1.25 A / 2 A         |

\* Additional impedance devices utilized for the test.

| Surge Specification     | Surge          | Waveform ( $\mu$ sec.) | Current (A) | Voltage (V) | Repetitions (Each) | Recommended Fuse |
|-------------------------|----------------|------------------------|-------------|-------------|--------------------|------------------|
| FCC Part 68 (TIA-968-A) | Metallic A     | 10 x 560               | 100         | 800         | 1                  | 1.25 A / 2 A     |
|                         | Longitudinal A | 10 x 160               | 200         | 1500        | 1                  | 1.25 A / 2 A     |

| Surge Specification       | Surge          | Waveform ( $\mu$ sec.) | Current (A) | Voltage (V) | Repetitions (Each) | Recommended Fuse     |
|---------------------------|----------------|------------------------|-------------|-------------|--------------------|----------------------|
| UL / EN 60950 (ITU-T K20) | Non-handheld   | 10 x 700               | 37.5        | 1500        | 5                  | 0.5 A / 1.25 A / 2 A |
|                           | Handheld Units |                        | 62.5        | 2500        | 5                  | 0.5 A / 1.25 A / 2 A |

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

**AC Power Fault Tests (Fuse Not Allowed to Open)**

| GR-1089<br>1st Level Test | Voltage<br>(Vrms) | Short Circuit<br>Current (A) | Hits | Duration | Recommended Fuse     |
|---------------------------|-------------------|------------------------------|------|----------|----------------------|
| 1                         | 50                | 0.33                         | 1    | 15 min.  | 0.5 A / 1.25 A / 2 A |
| 2                         | 100               | 0.17                         | 1    | 15 min.  | 0.5 A / 1.25 A / 2 A |
| 3                         | 600               | 0.5                          | 1    | 30 sec.  | 0.5 A / 1.25 A / 2 A |
| 4                         | 1000              | 1                            | 60   | 1 sec.   | 0.5 A / 1.25 A / 2 A |
| 5                         | 200               | 0.47                         | 60   | 1 sec.   | 0.5 A / 1.25 A / 2 A |
| 6                         | 425               | 0.71                         | 5    | 2 sec.   | 0.5 A / 1.25 A / 2 A |
| 7                         | 440               | 2.2                          | 5    | 2 sec.   | 1.25 A / 2 A         |
| 8                         | 600               | 3                            | 1    | 1.1 sec. | 1.25 A / 2 A         |
| 9                         | 1000              | 5                            | 1    | 0.4 sec. | 1.25 A / 2 A         |

Note: These tests can be performed at a higher voltage, but the current must be as specified.

**AC Current Limiting Protector Tests / Fusing Coordination Tests**

| Voltage (V <sub>AC</sub> ) | Current (A) | Duration      | Maximum Time For Fuse to Open (seconds) |               |               |
|----------------------------|-------------|---------------|---|---------------|---------------|
|                            |             |               | 0.50 A                                  | 1.25 A        | 2.00 A        |
| 600                        | 2.20        | up to 15 min. | 1.0                                     | will not open | will not open |
|                            | 2.60        |               | 0.8                                     | 900           | will not open |
|                            | 3.00        |               | 0.5                                     | 20            | will not open |
|                            | 3.75        |               | 0.3                                     | 10            | 20            |
|                            | 5.00        |               | 0.2                                     | 4             | 10            |
|                            | 7.00        |               | 0.1                                     | 2             | 4             |
|                            | 10.00       |               | 0.05                                    | 1             | 1.2           |
|                            | 12.50       |               | 0.03                                    | 0.40          | 0.6           |
|                            | 20.00       |               | 0.01                                    | 0.14          | 0.2           |
|                            | 25.00       |               | 0.008                                   | 0.08          | 0.14          |
|                            | 30.00       |               | 0.006                                   | 0.04          | 0.10          |

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

## Reliability Testing

| No. | Test                         | Test Condition   | Requirement  | Test Reference                                  |
|-----|------------------------------|--|--|---|
| 1   | Solderability                | Temperature setup: 235 ±5 °C<br>Time setup: 10 ±1 sec.   | After test terminal electrode wetting area must be greater than 95 % | IEC 60068-2-58                                  |
| 2   | Resistance to soldering heat | Temperature setup: 260 +0/-5 °C<br>Time setup: 10 sec. max.  | DCR change ≤ ±15 %   | IEC 60068-2-58                                  |
| 3   | Thermal shock                | Temperature setup:<br>25 °C ~ -65 °C ~ 25 °C ~ 125 °C<br>Time setup: -65 °C (30 min)<br>~ 25 °C (5 min) ~ 125 °C (30 min)<br>~ 25 °C (5 min), 5 cycles | DCR change ≤ ±15 %<br>No mechanical damage                           | MIL-STD-202G<br>Method 107G<br>Test Condition B |
| 4   | Humidity unload              | Heat (85 ±0.5 °C)<br>High Humidity (85 ±1 % RH)<br>240 hours   | DCR change ≤ ±15 %<br>No mechanical damage                           | MIL-STD-202G<br>Method 103B<br>Test Condition A |
| 5   | Salt spray                   | Salt spray concentration: 5 ±1 %<br>Test liquid temperature: 35 ±0.5 °C<br>96 hours  | DCR change ≤ ±15 %<br>No mechanical damage                           | MIL-STD-202G<br>Method 101E<br>Test Condition A |
| 6   | Bending                      | The board shall be bent by 1 mm<br>at a rate of 1 mm/sec.  | DCR change ≤ ±15 %   | IEC 60127-4                                     |
| 7   | Vibration                    | Frequency setup: 10 ~ 55 ~ 10 Hz<br>Time setup: 1 Minute/cycle<br>(X-Y-Z, 120 cycles, 6 hours)   | DCR change ≤ ±15 %<br>No mechanical damage                           | MIL-STD-202G<br>Method 201A                     |

**BOURNS®**

Asia-Pacific: Tel: +886-2 2562-4117 • Email: asiacus@bourns.com

EMEA: Tel: +36 88 885 877 • Email: eurocus@bourns.com

The Americas: Tel: +1-951 781-5500 • Email: americus@bourns.com

[www.bourns.com](http://www.bourns.com)

REV. 04/21

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain "typical" applications are based on Bourns' knowledge of typical requirements in generic applications. Bourns assumes that "typical" applications include failsafe/backup features to address critical risks to users and are designed to allow rework of Bourns® product to avoid scrap of a device solely due to malfunctioning Bourns® product. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Thus, users should always verify the actual performance of the Bourns® product in their specific devices and applications and make their own independent judgments regarding the suitability of Bourns® product and the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real-world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification even if such industry standard or qualification is a "state of art". Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage, such as without limitation nuclear, life-critical medical and certain automotive and aviation applications. Except as set forth in the bullet points below or unless expressly and specifically approved in writing on a case-by-case basis by an authorized Bourns' representative, use of any Bourns® products in such unauthorized high-risk applications is at the user's sole risk.

- Bourns considers implantable/invasive devices and devices/procedures designed as life-supporting or life-sustaining by the U.S. Food and Drug Administration or equivalent organizations outside of the United States as "life-critical" medical applications. Bourns expressly identifies those Bourns® standard products that are suitable for use in typical medical applications that are not life-critical in its publication entitled "Bourns Medical Grade Component Guide."
- Bourns expressly identifies those Bourns® standard products that are suitable for use in typical automotive applications associated with any Automate Safety Integrity Level (ASIL) in its publication entitled "Bourns Automotive Grade Component Guide." Bourns' designation of Bourns® product as compliant with the AEC-Q standard does not by itself mean that Bourns has approved such product for use in an automotive application.
- Bourns expressly identifies Bourns® standard products that are suitable for use in the typical aviation applications/systems requiring System Design Assurance Level (RTCA DO-254 DAL) of C, D or E in its publication entitled "Bourns Civilian Aerospace/Aviation Grade Component Guide." Bourns does not test its products for compliance with United States Federal Aviation Administration standards or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aviation applications. Use of Bourns® standard components in aviation applications associated with RTCA DO-254 DAL A or B without proper approval noted above shall be at the user's sole risk.
- Bourns will review and authorize on a case-by-case basis the use of Bourns® standard products which are at least AEC-Q compliant in space-related civil applications (rockets, satellites) with a negotiated cross-waiver and indemnity agreement.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Use of Bourns® products or Bourns' technology in military/defense applications must be reviewed with Bourns for compliance with applicable export control laws and embargoes. Users shall not sell, transfer, export or re-export (which includes transfers within a country) any Bourns® products or technology or technical data for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology or technical data in any facility which engages in activities relating to such devices. Further, Bourns® products and Bourns' technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products and technology may not, without prior authorization from Bourns and/or the Government of a country where such product/technology is designed and/or manufactured, be resold, transferred, or re-exported (including within the same country) to any party not eligible to receive commodities, software, and technical data originating in such country.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties (those not based on parameters specified in Bourns' data sheets and/or specifications), including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: <https://www.bourns.com/legal/disclaimers-terms-and-policies>

PDF: <https://www.bourns.com/docs/Legal/disclaimer.pdf>