

REV.		ECN NO.		DATE		SIGN		DESCRIPTION	
B		LE3-710063		2006/12/15		DongYaLi		Move DOR0038SI70 To ZSE00100548	
C		LEN-970107		2009/07/10		Vicky		Remove Pin Dim.	
D		LEN1350209		2013/05/14		Yulong		Change the Dimension	

With Liquid Glue
點防水膠

Panel Thickness
面板厚度
X(MAX)

Screw L=5.0 For Panel Thickness Under 1.2mm
適用板厚為 1.2mm 以下

Screw L=6.0 For Panel Thickness Between 1.2~2.0mm
適用板厚為 1.2~2.0mm

Recommended Panel Cut-Out
建議挖孔尺寸

ALTW
CONFIDENTIAL
2013-05-14
R&D DEPT.

ALTW
DCC. DEPT.
CONFIDENTIAL
2013.05.23
ISSUED

Note:

- * $\varnothing$ Important Dimension.
- * Waterproof Rate: IP68
- IP68: 1M of depth of water 24 hours
(防水等級: IP68)
(1米水深24小時)
- * Do Mating Test After Glued
點膠後, 須作對插測試
- * Housing: Black, Nylon+GF.
- * Connector: Black, PBT.
- * Female Pin: Copper Alloy, Gold Plated.
- * Ring: Light Blue, Silicone.
- * Screw: Copper Alloy, Nickel Plated, #4-40 UNC.
- * Applicable Wire Range: 22AWG-26AWG.
- 適用電線範圍: 22AWG-26AWG

UNIT: mm			TITLE D-SUB Conn. Panel Screw DB9P F Conn. F Pin		SCALE 1:1		SIZE A4	SHEET 1	OF 1
TOLERANCE .X .XX .XXX ANGLES	±0.25 ±0.1 ±0.05 ±1°		REV. D	WC-REV. A.3	$\varnothing$: Inspection item				

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO.	SDB-09PFFS-SL8001	DRAWN BY	SamChang	DATE	2013-05-14
DWG NO.	SDB-09PFFS-SL8001	CHECKED BY	Victor	DATE	2013-05-14
CUSTOMER	ALTW	APPROVED BY	Maslow	DATE	2013-05-14

FMW10702-01-02A1