



Luxeon III Star compatible - 3Wl super light RGB LED

SKU 104990074



ADD TO CART

Description

Features

- High flux per LED
- Very long operating life(up to 100k hours)
- Various colors
- Good color uniformity
- More energy efficient than incandescent and most halogen lamps
- Low Voltage DC operated
- Instant light (less than 100ns)
- No UV
- Superior ESD protection

Typical Applications

- Reading lights (car, bus, aircraft)
- Portable (flashlight, bicycle)
- Uplighters/Downlighters
- Decorative/Entertainment
- Bollards/Security/Garden
- Cove/Undershelf/Task
- Indoor/Outdoor Commercial and Residential Architectural
- Automotive Ext (Stop-Tail-Turn, CHMSL, Mirror Side Repeat)
- LCD backlights

Document

Downloaded from Arrow.com

Technical Details

Dimensions 50mm x 70mm x 7mm

Weight G.W 3g

Battery Exclude

ECCN/HTS

ECCN Not Available

HSCODE 9405409000

Certification

RoHS Compliant

Questions and Answers

Have a question about this? Ask people who

0 where is the datasheet?

thaddeus.robertson on Jul 25,2018

Reply

upvote (0)

Sorry, we will fix this link as soon as possible.Regards !

Seeed Techsupport Team on Jul 27,2018 10:08 AM Reply

upvote (0)

Luxeon III Star compatible - 3Wl super light RGB LED

SKU 104990074



IN STOCK

4 Available

1

ADD TO CART

Description

Technical Details

Questions and Answers

<>

×

✕
Notify me when it's back in stock

SUBMIT

POPULAR SEARCHES

PCB Manufacturing	PCB Assembly	PCB Layout	3D Printing	PCB Stencil	Lora	ReSpeaker	Grove	Lidar	GPS	Can-Bus	Arduino	Arduino Shield	Beaglebone
Raspberry Pi	FPGA	LinkIt ONE	Crazyflie 2.0	Raspberry Pi 3 Model B	RF Explorer	DSO Nano v3	HiKey	rplidar	raspberry pi relay	RPLIDAR A2			

Company

About Seeed
Distributors
Careers
Contacts

Help Center

How to Get Help
FAQ
Technical Support
Shipping & Order
Warranty & Returns
Payment Information

Community

Project Hub
Forum
Blog
Wiki

Stay Tuned

Subscribe to our newsletter.

 

© 2008-2018 Seeed Technology Co.,Ltd. All rights reserved. Site Map

Privacy Policy




Select Language

 Contact Support