

GENERAL DESCRIPTION

The HI-8597 is a 3.3V single supply ARINC 429 line driver with built-in lightning protection. The internal lightning protection circuitry allows compliance with RTCA/DO-160G, Section 22 Level 3 Pin Injection Test Waveform Set A (3 & 4), Set B (3 & 5A) and Set Z (3 & 5B) without the use of any external components, an industry first. Pin surge levels for Level 3 are summarized as follows:

| Waveform 3 | Waveform 4 | Waveform 5A | Waveform 5B |
|---------------------|---------------------|----------------------|----------------------|
| Voc/Isc 600V/24A | Voc/Isc 300V/60A | Voc/Isc 300V/300A | Voc/Isc 300V/300A |

An internal 37.5 Ohm resistor on each output enables direct connection to the ARINC 429 bus.

In addition, the device includes a dual polarity voltage doubler, allowing it to operate from a single +3.3V supply using only four external capacitors.

Other features include high-impedance outputs (tri-state) when both data inputs are taken high, allowing multiple line drivers to be connected to a common bus.

Bus pins feature built-in 8kV ESD input protection (HBM), with 6kV capability on all other pins. All logic inputs are 5V or 3.3V compatible.

The HI-8597 line driver is intended for use where logic signals must be converted to ARINC 429 levels such as when using an FPGA or the HI-3586 ARINC 429 protocol IC. The single supply operation and internal lightning protection circuitry enable huge board space saving, making HI-8597 the most compact, cost effective ARINC 429 line driver on the market today.

The part is available in Industrial -40°C to +85°C, or Extended, -55°C to +125°C temperature ranges. Optional burn-in is available on the extended temperature range.

FEATURES

- Internal lightning protection circuitry allows compliance with RTCA/DO-160G, Section 22 Level 3 Pin Injection Test Waveform Set A (3 & 4), Set B (3 & 5A) and Set Z (3 & 5B).
- Operates from a single +3.3V supply
- Superb short circuit capability on ARINC 429 outputs ($\pm 50V$ for 1 second)
- All ARINC 429 voltage levels generated on-chip
- Digitally selectable rise and fall times
- Tri-state Outputs
- 37.5 Ohm output resistance allows direct connection to ARINC 429 bus
- Industrial and Extended temperature ranges
- Burn-in available

PIN CONFIGURATION (TOP VIEW)




Table 1. Function Table

| TX1IN | TX0IN | SLP | TXAOUT | TXBOUT | SLOPE |
|-------|-------|-----|--------|--------|-------|
| 0 | 0 | X | 0V | 0V | N/A |
| 0 | 1 | 0 | -5V | 5V | 10µs |
| 0 | 1 | 1 | -5V | 5V | 1.5µs |
| 1 | 0 | 0 | 5V | -5V | 10µs |
| 1 | 0 | 1 | 5V | -5V | 1.5µs |
| 1 | 1 | X | Hi-Z | Hi-Z | N/A |

BLOCK DIAGRAM




Figure 1. HI-8597 Block Diagram

PIN DESCRIPTIONS

Table 2. Pin Descriptions

| Pin No. | Pin Name | Function | Description |
|---------|------------|----------|---|
| 1 | NC | None | No connect. |
| 2 | GNDA | POWER | Ground connection of internal lightning protection circuitry for ARINC high output. MUST be tied to chip ground pin, GND. |
| 3 | TXAOUT | OUTPUT | ARINC high output with 37.5 Ohms series resistance |
| 4 | TXBOUT | OUTPUT | ARINC low output with 37.5 Ohms series resistance |
| 5 | GNDB | POWER | Ground connection of internal lightning protection circuitry for ARINC low output. MUST be tied to chip ground pin, GND. |
| 6 | SLP | INPUT | Output slew rate control. High selects ARINC 429 high-speed. Low selects ARINC 429 low-speed. |
| 7 | TX0IN | INPUT | Data input zero |
| 8 | TX1IN | INPUT | Data input one |
| 9 | V_{DD2+} | OUTPUT | Voltage doubler positive output (~6.25V for 3.3V supply) |
| 10 | CP+ | ANALOG | V_{DD2+} flyback capacitor, C_{FLY} ; positive terminal |
| 11 | CP- | ANALOG | V_{DD2+} flyback capacitor, C_{FLY} ; negative terminal |
| 12 | V_{DD} | POWER | +3.3V power supply |
| 13 | GND | POWER | Ground supply |
| 14 | CN- | ANALOG | V_{DD2-} flyback capacitor, C_{FLY} ; negative terminal |
| 15 | CN+ | ANALOG | V_{DD2-} flyback capacitor, C_{FLY} ; positive terminal |
| 16 | V_{DD2-} | OUTPUT | Voltage doubler negative output (~ -6.1V for 3.3V supply) |

FUNCTIONAL DESCRIPTION

Figure 1 shows a block diagram of the line driver. The HI-8597 is internally lightning protected in compliance with RTCA/DO-160G, Section 22 Level 3 Pin Injection Test Waveform Set A (3 & 4), Set B (3 & 5A) and Set Z (3 & 5B). The waveforms are shown in Figure 5 through Figure 7. The device requires only a single +3.3V power supply. An integrated inverting / non-inverting voltage doubler generates the rail voltages ($\pm 6.6V$) which are then used to produce the $\pm 5V$ ARINC-429 output levels.

The internal dual polarity charge pump circuit requires four external capacitors, two for each polarity generated by the doubler. $CP+$ and $CP-$ connect the external charge transfer or "fly" capacitor, C_{FLY} , to the positive portion of the doubler, resulting in twice V_{DD} at the V_{DD2+} pin. An output "hold" capacitor, C_{OUT} , is placed between V_{DD2+} and GND. C_{OUT} should be ten times the size of C_{FLY} . The inverting or negative portion of the converter works in a similar fashion, with C_{FLY} and C_{OUT} placed between $CN+$ / $CN-$ and V_{DD2-} / GND respectively.

Currents for slope control are set by on-chip resistors.

The TX0IN and TX1IN inputs receive logic signals from a control transmitter chip such as the HI-3584 or HI-3586. TXAOUT and TXBOUT hold each side of the ARINC bus at Ground until one of the inputs becomes a One. If for example TX1IN goes high, a charging path is enabled to 5V on an "A" side internal capacitor while the "B" side is enabled to -5V. The charging current is selected by the

SLP pin. If the SLP pin is high, the capacitor is nominally charged from 10% to 90% in 1.5 μ s. If SLP is low, the rise and fall times are 10 μ s.

A unity gain buffer receives the internally generated slopes and differentially drives the ARINC line. Current is limited by the series output resistors at each pin. There are no fuses at the outputs of the HI-8597.

The HI-8597 has 37.5 ohms in series with each TXOUT output, allowing direct connection to the ARINC 429 bus. The outputs are automatically lightning protected in compliance with RTCA/DO-160G, Section 22 Level 3 Pin Injection Test Waveform Set A (3 & 4), Set B (3 & 5A) and Set Z (3 & 5B) without any external components.

Tri-stateable outputs allow multiple line drivers to be connected to the same ARINC 429 bus. Setting TX1IN and TX0IN both to a logic "1" puts the outputs in the high-impedance state.

PACKAGE HEAT SINK

The HI-8597 package includes a metal heat sink located on the bottom surface of the device. The heat sink is electrically isolated and may be optionally soldered to any convenient power or ground plane for optimum thermal dissipation.

ABSOLUTE MAXIMUM RATINGS

| Supply Voltages | |
|-------------------------------------|-----------------------|
| V_{DD} | +5V |
| Junction Temperature (T_{JMAX}) | |
| | 175°C |
| Solder Temperature (reflow) | 260°C |
| Storage Temperature | -65°C to +150°C |

| RTCA/DO-160G, Section 22 pin injection | |
|--|-----------------|
| Waveform | V_{oc}/I_{sc} |
| 3 | 800V/32A |
| 4 | 375V/75A |
| 5A | 375V/375A |
| 5B | 375V/375A |

RECOMMENDED OPERATING CONDITIONS

| Supply Voltages | |
|-------------------|---|
| V_{DD} | +3.0V to +3.6V |
| Temperature Range | |
| | Industrial Screening -40°C to +85°C |
| | Hi-Temp Screening -55°C to +125°C |

NOTE: Stresses above absolute maximum ratings or outside recommended operating conditions may cause permanent damage to the device. These are stress ratings only. Operation at the limits is not recommended.

ELECTRICAL CHARACTERISTICS

Table 3. DC Electrical Characteristics

 $V_{DD} = +3.3V$, T_A = Operating Temperature Range (unless otherwise stated)

| Parameters | Symbol | Test Conditions | Min | Typ | Max | Units |
|--|-------------|--|--------------|------|--------------|---------|
| Input Voltage (TX1IN, TX0IN, SLP) | V_{IH} | | 0.7 V_{DD} | - | - | V |
| | V_{IL} | | | | 0.3 V_{DD} | V |
| Input Current (TX1IN, TX0IN, SLP) | I_{IH} | (73k Ω Internal Pulldown) $V_{IN} = 3.3V$ | - | 45 | - | μA |
| | I_{IL} | | | | -0.1 | μA |
| ARINC Output Voltage (Differential) | V_{DIFF1} | no load; TXAOUT - TXBOUT | 9 | 10 | 11 | V |
| | V_{DIFF0} | no load; TXAOUT - TXBOUT | -11 | -10 | -9 | V |
| | V_{DIFFN} | no load; TXAOUT - TXBOUT | -0.5 | 0 | 0.5 | V |
| ARINC Output Voltage (Ref. to GND) | V_{DOUT} | no load & magnitude at pin | 4.5 | 5.0 | 5.5 | V |
| | V_{NOUT} | no load | -0.25 | 0 | 0.25 | V |
| Operating Supply Current | I_{DDNL} | SLP = V_{DD} TX1IN & TX0IN = 0V | - | 28 | 40 | mA |
| | | 100kHz, 400 Ω load | | | - | |
| | I_{DDL} | See Note 1 | - | 65 | - | mA |
| Power Dissipation in device ² | P_{DDNL} | SLP = V_{DD} TX1IN & TX0IN = 0V | - | 93 | 132 | mW |
| | | 100kHz, 400 Ω load | | | - | |
| | P_{DDLT} | See Note 1 | - | 215 | - | mW |
| ARINC Outputs Shorted (TXOUT outputs) | P_{DDST} | See Note 1 | - | 545 | - | mW |
| | | | | | - | |
| | I_{OUT} | | 35 | 37.5 | 40 | Ohms |
| ARINC Output Tri-State Current | I_{OZ} | TX0IN = TX1IN = V_{DD} , $T_A = 25^\circ C$ -5.5V < V_{OUT} < +5.5V | -200 | | 200 | μA |
| ARINC Output Tri-State Voltage | V_{OZ} | TX0IN = TX1IN = V_{DD} , $T_A = 25^\circ C$ -150 μA < I_{OUT} < +150 μA | -5.5 | - | +5.5 | V |

Note 1: TXAOUT and/or TXBOUT shorted to each other or ground.

Note 2: Estimate junction temperature using Theta JB or Theta JA values available on Holt's website, www.holtic.com. $T_J \leq T_{JMAX}$.

Table 4. Converter Characteristics

$V_{DD} = +3.3V$, T_A = Operating Temperature Range (unless otherwise stated)

| Parameters | Symbol | Test Conditions | Min | Typ | Max | Units |
|---|-----------------|---|-----|-----|------|-------|
| Start-up transient (V_+ , V_-) | t_{START} | | - | - | 10 | ms |
| Operating Switching Frequency | f_{sw} | | - | 650 | - | kHz |
| Worst case maximum voltage doubler output | $V_{DD2+(max)}$ | $V_{DD} = 3.6V$, $T = -55^{\circ}C$. Open load. | | | 6.93 | V |

DC/DC convertor capacitor recommendations.

For optimum performance use typical (not min.) values. For EMC compliance, see AN-135.

| | | | | | | |
|--|-----------------------------|--|-----|-----|----------|----------------------|
| Ratio of bulk storage to fly-back capacitors | C_{OUT} / C_{FLY} | | 2.2 | 10 | | |
| Fly-back capacitor (Recommend ceramic, preferably multilayer, dielectric XR7 caps, 10V min.). | C_{FLY} $C_{FLY(ESR)}$ | $C_{OUT} / C_{FLY} \geq 10$ [0.5, 1.0]Mhz | 1.0 | 4.7 | - 500 | μF $m\Omega$ |
| Bulk storage capacitor (Recommend ceramic, preferably multilayer, dielectric XR7 caps, 10V min.). | C_{OUT} $C_{OUT(ESR)}$ | $C_{OUT} / C_{FLY} \geq 10$ [0.5, 1.0]Mhz | 2.2 | 47 | - 300 | μF $m\Omega$ |
| By-pass capacitor (Recommend ceramic cap, 10V min.). | C_{SUPPLY} | $C_{SUPPLY} \geq C_{OUT}$ (connect from V_{DD} to GND) | | | | |

Table 5. AC Electrical Characteristics

$V_{DD} = +3.3V$, T_A = Operating Temperature Range (unless otherwise stated)

| Parameters | Symbol | Test Conditions | Min | Typ | Max | Units |
|--|-----------|------------------------------|-----|------|------|---------|
| Line Driver Propogation Delay Output high to low Output low to high | t_{phx} | defined in Figure 2, no load | - | 500 | - | ns |
| | t_{phx} | | - | 500 | - | ns |
| Line Driver Transition Times High Speed Output high to low Output low to high | t_{fx} | SLP pin = Logic "1" | 1.0 | 1.5 | 2.0 | μs |
| | t_{rx} | | 1.0 | 1.5 | 2.0 | μs |
| Low Speed Output high to low Output low to high | t_{fx} | SLP pin = Logic "0" | 5.0 | 10.0 | 15.0 | μs |
| | t_{rx} | | 5.0 | 10.0 | 15.0 | μs |
| Input Capacitance (Logic) ¹ | C_{IN} | | - | - | 10 | pF |
| Output Capacitance (Tri-state) ¹ | C_{OUT} | $TX0IN = TX1IN = V_{DD}$ | - | - | 10 | pF |

Notes: 1. Guaranteed but not tested




Figure 2. Line Driver Timing




Figure 3. Tri-State Leakage Current vs Bus Voltage at Temperature.




Figure 4. Tri-State Leakage Current vs Bus Voltage at Room Temperature.

LIGHTNING INDUCED TRANSIENT VOLTAGE WAVEFORMS

Waveform 3.




Figure 5. DO-160G Lightning Induced Transient Voltage Waveform 3.
Voc = 600V, Isc = 24A, Frequency = 1MHz \pm 20%.

Waveform 4.




Figure 6. DO-160G Lightning Induced Transient Voltage Waveform 4.
Voc = 300V, Isc = 60A.

Waveform 5.




Figure 7. DO-160G Lightning Induced Transient Voltage Waveforms 5A and 5B.
 $V_{oc} = 300V$, $I_{sc} = 300A$.

ORDERING INFORMATION

HI - 8597PS x F (Plastic)

| PART NUMBER | LEAD FINISH | | |
|-------------|--|------|---------|
| F | 100% Matte Tin (Pb-free, RoHS compliant) | | |
| PART NUMBER | TEMPERATURE RANGE | FLOW | BURN IN |
| I | -40°C to +85°C | I | No |
| T | -55°C to +125°C | T | No |
| M | -55°C to +125°C | M | Yes |
| PART NUMBER | PACKAGE DESCRIPTION | | |
| 8597PS | 16 PIN PLASTIC SMALL OUTLINE - WB SOIC (16HWE) | | |

REVISION HISTORY


| Revision | Date | Description of Change |
|------------------|------------|---|
| DS8597, Rev. New | 11/9/12 | Initial Release |
| Rev. A | 12/11/12 | Clarify operating supply current for shorted ARINC outputs. |
| Rev. B | 01/21/13 | Change "VSS" pin label to "GND" and "-" to "NC" for clarification. Add pin numbers to Pin Description table. Rephrase "guarantees" compliance with DO-160G Level 3 to "allows" compliance with DO-160G Level 3. Update tri-state leakage parameter to 200µA. Add Absolute Maximum Ratings for lightning waveforms. |
| Rev. C | 03/14/13 | Remove erroneous references to AMPA and AMPB outputs in footnote on page 5. |
| Rev. D | 05/08/13 | Corrected state of SLP pin and erroneous reference to pin 1 in Test Conditions for Line Driver Transition Times (see AC Characteristics Table). |
| Rev. E | 06/13/13 | Update operating supply current. |
| Rev. F | 07/19/13 | Update operating supply current from 85mA to 100mA max. |
| Rev. G | 10/02/14 | Correct converter caps ESR values to be maximum instead of minimum. Update 16HWE package drawing. |
| Rev. H | 12/09/14 | Update Operating Supply Current and ARINC Output Impedance in "Table 3. DC Electrical Characteristics". |
| Rev. I | 01/21/15 | Delete Max. Power Dissipation in Absolute Maximum Ratings table. Add Max. Junction Temperature to table. Add Device Power Dissipation to DC Electrical Characteristics in Table 3. Recommend ceramic converter caps only (no tantalum) in "Converter Characteristics". |
| Rev. J | 07/22/15 | Clarify Load condition for Power Dissipation in DC Electrical Characteristics in Table 3. |
| Rev. K | 02/21/17 | Clarify ordering information. Only lead-free option offered in 16-pin WB SOIC. |
| Rev. L | 11/18/2021 | Add note on soldering of package heat sink. |
| Rev. M | 11/29/2021 | Add note to package drawing on soldering of package heat sink. |
| Rev. N | 07/08/2022 | Clarify test conditions for I_{IH} and I_{IL} parameters. |
| Rev. P | 11/30/2023 | Correct typo in Input Current pulldown resistor value on TX1IN, TX0IN and SLP pins. |

PACKAGE DIMENSIONS

16-PIN PLASTIC SMALL OUTLINE (ESOIC) - WB
(Wide Body, Thermally Enhanced)

millimeters (inches)

Package Type: 16HWE



BSC = "Basic Spacing between Centers" is theoretical true position dimension and has no tolerance. (JEDEC Standard 95)