




PRODUCT NUMBER: 896-43-004-00-000000

www.mill-max.com  
DATA SHEET



## 896-43-004-00-000000- SPECIFICATIONS

| General Info        |                   |
|---------------------|-------------------|
| Description:        | Type A<br>USB 2.0 |
| Type:               | USB               |
| Category:           | Connector         |
| Mounting Style:     | Surface Mount     |
| # Pins:             | 4                 |
| Packaging:          | Packaged in Trays |
| Qty Tube:           | 150               |
| RoHS <sup>1</sup> : | Yes               |
| Product Lifecycle:  | Active            |

| Materials |  |
|-----------|--|
| Shell     | 200 $\mu$ " Tin (matte finish) over    |
| Plating:  | 100 $\mu$ " Nickel                     |
| Inner     | 30 $\mu$ " Gold over 50 $\mu$ " Nickel |
| Plating:  |  |

| Technical Specs    |                |
|--------------------|----------------|
| Temperature Range: | -40/+85° C     |
| Rows:              | Single Row (1) |

## NOTES:

1. Mill-Max products labeled with the RoHS symbol are compliant with all three ROHS Directives. All of our products previously described as RoHS (2002/95/EC) and RoHS-2 (2011/65/EC) are also compliant with RoHS-3 (2015/863/EU).

## ADDITIONAL NOTES AND SPECIFICATIONS

In the interest of improved design, quality and performance , Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

## RELATED LINKS AND DOCUMENTS

Environmental Compliance: ( <https://www.mill-max.com/rohs> )