

Intelligent Power Module (IPM)

600 V, 30 A

STK581U3C2D-E

Overview

This “Inverter IPM” is highly integrated device containing all High Voltage (HV) control from HV–DC to 3–phase outputs in a single SIP module (Single–In line Package). Output stage uses IGBT/FRD technology and implements Under Voltage Protection (UVP) and Over Current Protection (OCP) with a Fault Detection output flag. Internal Boost diodes are provided for high side gate boost drive.

Features

- Single Control Power Supply due to Internal Bootstrap Circuit for High Side Pre–driver Circuit
- All Control Input and Status Output are at Low Voltage Levels directly compatible with Microcontrollers
- Built–in Cross Conduction Prevention
- Externally accessible Embedded Thermistor for Substrate Temperature Measurement
- The Level of the Over–current Protection Current is adjustable with the External Resistor, “RSD”
- These Devices are Pb–Free and are RoHS Compliant

Certification

- UL1557 (File number : E339285)



ON Semiconductor®

www.onsemi.com

SIP22 70x31.1
CASE 127BU

MARKING DIAGRAM



STK581U3C2D = Specific Device Code
A = Year
B = Month
C = Production Site
DD = Factory Lot code
Device marking is on package underside

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 13 of this data sheet.

STK581U3C2D-E

Specifications

ABSOLUTE MAXIMUM RATINGS (at T_c = 25°C)

Parameter	Symbol	Conditions	Ratings	Unit
Supply voltage	V _{CC}	P to N, surge < 500 V (Note 1)	450	V
Collector-emitter voltage	V _{CE}	P to U,V,W or U,V,W to N	600	V
Output current	I _o	P, N, U,V,W terminal current	±30	A
		P, N, U,V,W terminal current at T _c = 100°C	±15	A
Output peak current	I _{op}	P, N, U,V,W terminal current for a Pulse width of 1 ms	±45	A
Pre-driver voltage	VD1,2,3,4	VB1 to U, VB2 to V, VB3 to W, V _{DD} to V _{SS} (Note 2)	20	V
Input signal voltage	V _{IN}	HIN1, 2, 3, LIN1, 2, 3	-0.3 to V _{DD}	V
FAULT terminal voltage	V _{FAULT}	FAULT terminal	-0.3 to V _{DD}	V
Maximum power dissipation	P _d	IGBT per channel	49	W
Junction temperature	T _j	IGBT, FRD	150	°C
Storage temperature	T _{stg}		-40 to +125	°C
Operating case temperature	T _c	IPM case temperature	-40 to +100	°C
Tightening torque		Case mounting screws (Note 3)	1.17	Nm
Withstand voltage	V _{is}	50 Hz sine wave AC 1 minute (Note 4)	2000	VRMS

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

NOTE: Reference voltage is "V_{SS}" terminal voltage unless otherwise specified.

1. Surge voltage developed by the switching operation due to the wiring inductance between "P" and "N" terminal.
2. Terminal voltage : VD1 = VB1 to U, VD2 = VB2 to V, VD3 = VB3 to W, VD4 = V_{DD} to V_{SS}
3. Flatness of the heat-sink should be 0.15 mm and below.
4. Test conditions : AC 2500 V, 1 s.

ELECTRICAL CHARACTERISTICS (at T_c = 25°C, VD1, VD2, VD3, VD4 = 15 V, V_{CC} = 300 V, L = 3.5 mH)

Parameter	Symbol	Conditions		Test Circuit	Min	Typ	Max	Unit
Power Output Section								
Collector-emitter cut-off current	I _{CE}	V _{CE} = 600 V		Fig.1	–	–	0.1	mA
Bootstrap diode reverse current	IR(BD)	VR(BD)			–	–	0.1	mA
Collector to emitter saturation voltage	V _{CE(SAT)}	I _c = 30 A T _j = 25°C	Upper side	Fig.2	–	1.8	2.7	V
			Lower side (Note 5)		–	2.1	3.0	
		I _c = 15 A T _j = 100°C	Upper side		–	1.5	–	
			Lower side (Note 5)		–	1.7	–	
Diode forward voltage	V _F	I _F = 30 A T _j = 25°C	Upper side	Fig.3	–	2.0	2.9	V
			Lower side (Note 5)		–	2.3	3.2	
		I _F = 15 A T _j = 100°C	Upper side		–	1.5	–	
			Lower side (Note 5)		–	1.7	–	
Junction to case thermal resistance	θ _{j-c} (T)	IGBT			–	–	2.5	°C/W
	θ _{j-c} (D)	FRD			–	–	3	
Control (Pre-driver) Section								
Pre-driver power dissipation	ID	VD1, 2, 3 = 15 V		Fig.4	–	0.08	0.4	mA
		VD4 = 15 V			–	1.6	4	

STK581U3C2D-E

ELECTRICAL CHARACTERISTICS (at Tc = 25°C, VD1, VD2, VD3, VD4 = 15 V, VCC = 300 V, L = 3.5 mH) (continued)

Parameter	Symbol	Conditions	Test Circuit	Min	Typ	Max	Unit
Control (Pre-driver) Section							
High level Input voltage	V _{in H}	HIN1, HIN2, HIN3, LIN1, LIN2, LIN3 to V _{SS}		2.5	–	–	V
Low level Input voltage	V _{in L}			–	–	0.8	V
Input threshold voltage hysteresis (Note 5)	V _{inH(hys)}			0.5	0.8	–	V
Logic 1 input leakage current	I _{IN+}	V _{IN} = +3.3 V		–	100	143	μA
Logic 0 input leakage current	I _{IN–}	V _{IN} = 0 V		–	–	2	μA
FAULT terminal input electric current	I _{oSD}	FAULT : ON / V _{FAULT} = 0.1 V		–	2	–	mA
FAULT clear time	FLTCLR	Fault output latch time.		18	–	80	ms
V _{CC} and V _S undervoltage positive going threshold	V _{CCUV+} V _{SUV+}			10.5	11.1	11.7	V
V _{CC} and V _S undervoltage negative going threshold	V _{CCUV–} V _{SUV–}			10.3	10.9	11.5	V
V _{CC} and V _S undervoltage hysteresis	V _{CCUVH} V _{SUVH–}			0.14	0.2	–	V
Over current protection level	ISD	PW = 100 μs, RSD = 0 Ω	Fig.5	38.5	–	48.2	A
Output level for current monitor	ISO	I _o = 30 A		0.32	0.34	0.36	V

Switching Characterisitcs

Switching time	t _{ON}	I _o = 30 A	Fig.6	0.3	0.6	1.3	μs
	t _{OFF}			–	0.9	1.6	
Turn-on switching loss	E _{on}	I _o = 30 A		–	800	–	μJ
Turn-off switching loss	E _{off}			–	550	–	μJ
Total switching loss	E _{tot}			–	1350	–	μJ
Turn-on switching loss	E _{on}	I _o = 15 A, Tc = 100°C		–	530	–	μJ
Turn-off switching loss	E _{off}			–	450	–	μJ
Total switching loss	E _{tot}			–	980	–	μJ
Diode reverse recovery energy	E _{rec}	I _F = 15 A, P = 400 V, Tc = 100°C		–	24	–	μJ
Diode reverse recovery time	t _{rr}			–	58	–	ns
Reverse bias safe operating area	RBSOA	I _o = 45 A, V _{CE} = 450 V		Full square			
Short circuit safe operating area	SCSOA	V _{CE} = 400 V, Tc = 100°C		4	–	–	μs
Allowable offset voltage slew rate	dv/dt	Between U, V, W to N		–50	–	50	V/ns

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

NOTE: Reference voltage is "V_{SS}" terminal voltage unless otherwise specified.

5. The lower side's V_{CE}(SAT) and V_F include a loss by the shunt resistance

Notes:

- When the internal protection circuit operates, a Fault signal is turned ON (When the Fault terminal is low level, Fault signal is ON state : output form is open DRAIN) but the Fault signal does not latch. After protection operation ends, it returns automatically within about 18 ms to 80 ms and resumes operation beginning condition. So, after Fault signal detection, set all input signals to OFF (Low) at once. However, the operation of pre-drive power supply low voltage protection

(UVLO : with hysteresis about 0.2 V) is as follows.

Upper side:

The gate is turned off and will return to regular operation when recovering to the normal voltage, but the latch will continue till the input signal will turn 'low'.

Lower side:

The gate is turned off and will automatically reset when recovering to normal voltage. It does not depend on input signal voltage.

STK581U3C2D-E

2. When assembling the IPM on the heat sink with M3 type screw, tightening torque range is 0.79 Nm to 1.17 Nm.

3. The pre-drive low voltage protection is the feature to protect devices when the pre-driver supply voltage falls due to an operating malfunction.

RECOMMENDED OPERATING CONDITIONS (at T_c = 25°C)

Item	Symbol	Conditions	Min	Typ	Max	Unit
Supply voltage	V _{CC}	P to N	0	280	450	V
Pre-driver supply voltage	VD1, 2, 3	VB1 to U, VB2 to V, VB3 to W	12.5	15	17.5	V
	VD4	V _{DD} to V _{SS} (Note 6)	13.5	15	16.5	
ON-state input voltage	V _{IN(ON)}	HIN1, HIN2, HIN3, LIN1, LIN2, LIN3	3.0	–	5.0	V
OFF-state input voltage	V _{IN(OFF)}		0	–	0.0	
PWM frequency	f _{PWM}		1	–	20	kHz
Dead time	DT	Turn-off to turn-on	2	–	–	μs
Allowable input pulse width	PWIN	ON and OFF	1	–	–	μs
Package mounting torque		'M4' type screw	0.79	–	1.17	Nm

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

6. Pre-drive power supply (VD4 = 15 ±1.5 V) must have the capacity of I_o = 20 mA (DC), 0.5 A (Peak).

MODULE PIN-OUT DESCRIPTION

Pin	Name	Description
1	VB1	High Side Floating Supply Voltage 1
2	U, VS1	Output 1 – High Side Floating Supply Offset Voltage
3	–	Without Pin
4	VB2	High Side Floating Supply voltage 2
5	V, VS2	Output 2 – High Side Floating Supply Offset Voltage
6	–	Without Pin
7	VB3	High Side Floating Supply voltage 1
8	W, VS3	Output 1 – High Side Floating Supply Offset Voltage
9	–	Without Pin
10	P	Positive Bus Input Voltage
11	–	Without Pin
12	N	Positive Bus Input Voltage
13	HIN1	Logic Input High Side Gate Driver – Phase U
14	HIN2	Logic Input High Side Gate Driver – Phase V
15	HIN3	Logic Input High Side Gate Driver – Phase W
16	LIN1	Logic Input Low Side Gate Driver – Phase U
17	LIN2	Logic Input Low Side Gate Driver – Phase V
18	LIN3	Logic Input Low Side Gate Driver – Phase W
19	FAULT	FAULT Output
20	ISO	Current monitor output
21	VDD	+15V Main Supply
22	VSS	Negative Main Supply

STK581U3C2D-E

Equivalent Block Diagram




Figure 1. Block Diagram

Test Circuits

(The tested phase : U+ shows the upper side of the U phase and U- shows the lower side of the U phase.)

• ICE / IR(BD)

	U+	V+	W+	U-	V-	W-
M	10	10	10	2	5	8
N	2	5	8	12	12	12

	U(DB)	V(DB)	W(DB)
M	1	4	7
N	22	22	22




Figure 2. Test Circuit for ICE

• $V_{CE}(SAT)$ (Test by pulse)

	U+	V+	W+	U-	V-	W-
M	10	10	10	2	6	8
N	2	5	8	12	12	12
m	13	14	15	16	17	18




Figure 3. Test Circuit for $V_{CE}(sat)$

• V_F (Test by pulse)

	U+	V+	W+	U-	V-	W-
M	10	10	10	2	5	8
N	2	5	8	12	12	12




Figure 4. Test Circuit for V_F

• ID

	VD1	VD2	VD3	VD4
M	1	4	7	21
N	2	5	8	22




Figure 5. Test Circuit for ID

- ISD





Figure 6. Test Circuit for ISD

- Switching time
(The circuit is a representative example of the lower side U phase.)






Figure 7. Switching Time Test Circuit

STK581U3C2D-E

Logic Timing Chart



Notes:

- *1: Diagram shows the prevention of shoot-through via control logic. More dead time to account for switching delay needs to be added externally.
- *2: When V_{DD} decreases all gate output signals will go low and cut off all of 6 IGBT outputs. When V_{DD} rises the operation will resume immediately.
- *3: When the upper side gate voltage at VB1, VB2 and VB3 drops only, the corresponding upper side output is turned off. The outputs return to normal operation immediately after the upper side gate voltage rises.
- *4: In case of over current detection, all IGBT's are turned off and the FAULT output is asserted. Normal operation resumes in 18 to 80 ms after the over current condition is removed.

Figure 8. Logic Timing Chart

STK581U3C2D-E

Logic Level Table




Figure 9.

LOGIC LEVEL TABLE

INPUT			OUTPUT			
HIN	LIN	OCP	Ho	Lo	U, V, W	FAULT
H	L	OFF	H	L	P	OFF
L	H	OFF	L	H	N	OFF
L	L	OFF	L	L	High Impedance	OFF
H	H	OFF	L	L	High Impedance	OFF
X	X	ON	L	L	High Impedance	ON

Sample Application Circuit




Figure 10. Sample Application Circuit

Usage Precautions

1. This IPM includes bootstrap diode and resistors. Therefore, by adding a capacitor “CB”, a high side drive voltage is generated; each phase requires an individual bootstrap capacitor. The recommended value of CB is in the range of 1 to 47 μF , however this value needs to be verified prior to production. If selecting the capacitance more than 47 μF ($\pm 20\%$), connect a resistor (about 20 Ω) in series between each 3-phase upper side power supply terminals (VB1, 2, 3) and each bootstrap capacitor.

When not using the bootstrap circuit, each upper side pre-drive power supply requires an external independent power supply.

2. It is essential that wiring length between terminals in the snubber circuit be kept as short as possible to reduce the effect of surge voltages. Recommended value of “CS” is in the range of 0.1 to 10 μF .
3. “ISO” (pin20) is terminal for current monitor. When the pull-down resistor is used, please select it more than 5.6 k Ω

4. “FAULT” (pin19) is open DRAIN output terminal (Active Low). Pull up resistor is recommended more than 5.6 k Ω .
5. Inside the IPM, a thermistor used as the temperature monitor for internal substrate is connected between V_{SS} terminal and TH terminal, therefore, an external pull up resistor connected between the TH terminal and an external power supply should be used. The temperature monitor example application is as follows, please refer the Fig.11, and Fig.12 below.
6. Pull down resistor of 33 k Ω is provided internally at the signal input terminals. An external resistor of 2.2 k to 3.3 k Ω should be added to reduce the influence of external wiring noise.
7. The over-current protection feature is not intended to protect in exceptional fault condition. An external fuse is recommended for safety.
8. When input pulse width is less than 1.0 μs , an output may not react to the pulse. (Both ON signal and OFF signal)

This data shows the example of the application circuit, does not guarantee a design as the mass production set.

THERMISTOR CHARACTERISTICS

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Resistance	R ₂₅	T _c = 25°C	99	100	101	kΩ
	R ₁₀₀	T _c = 100°C	5.12	5.38	5.66	kΩ
B-Constant (25 to 50°C)	B		4165	4250	4335	K
Temperature Range			-40	-	+125	°C




Figure 11. Thermistor Resistance versus Case Temperature




Figure 12. Thermistor Voltage versus Case Temperature

STK581U3C2D-E

PWM Switching Frequency Characteristics

Maximum sinusoidal phase current as function of switching frequency ($V_{BUS} = 300\text{ V}$, $T_c = 100^\circ\text{C}$)




Figure 13. PWM Switching Frequency Characteristics

Switching Waveforms

IGBT Turn-on. Typical turn-on waveform @ $T_c = 100^\circ\text{C}$, $V_{BUS} = 400\text{ V}$




Figure 14.

IGBT Turn-off. Typical turn-off waveform @ $T_c = 100^\circ\text{C}$, $V_{BUS} = 400\text{ V}$




Figure 15.

STK581U3C2D-E

CB Capacitor Value Calculation for Bootstrap Circuit

CALCULATE CONDITIONS TABLE

Item	Symbol	Value	Unit
Upper side power supply.	VBS	15	V
Total gate charge of output power IGBT at 15 V.	Qg	266	nC
Upper side power supply low voltage protection.	UVLO	12	V
Upper side power dissipation.	IDmax	400	μA
ON time required for CB voltage to fall from 15 V to UVLO	Tonmax	–	s

Capacitance Calculation Formula

CB must not be discharged below to the upper limit of the UVLO – the maximum allowable on-time (Tonmax) of the upper side is calculated as follows:

$$VBS * CB - Qg - IDmax * Tonmax = UVLO * CB$$

$$CB = (Qg + IDmax * Tonmax) / (VBS - UVLO)$$

The relationship between Tonmax and CB becomes as follows. CB is recommended to be approximately 3 times the value calculated above. The recommended value of CB is in the range of 1 to 47 μF, however, the value needs to be verified prior to production.




Figure 16. Tonmax–CB Characteristics


ORDERING INFORMATION

Device	Marking	Package	Shipping
STK581U3C2D-E	STK581U3C2D	SIP22 70x31.1 (Pb-Free)	7 Units / Tube

SIP22 70x31.1
CASE 127BU
ISSUE 0

DATE 30 APR 2012

Missing P in : 3,6,9,11



DOCUMENT NUMBER:	98AON79787E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	SIP22 70X31.1	PAGE 1 OF 1

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Email Requests to: orderlit@onsemi.com

ON Semiconductor Website: www.onsemi.com

TECHNICAL SUPPORT

North American Technical Support:

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative

