




## Features :

- Interchangeable AC plugs (plug kit sold separately)
- Universal AC input / Full range
- No load power consumption < 0.075W
- **Energy efficiency Level VI**
- Comply with EISA 2007/DoE and EU ErP
- Class II power (without earth pin)
- Protections: Short circuit / Overload / Over voltage
- Pass LPS
- Fully enclosed plastic case
- LED indicator for power on
- 2 years warranty



Interchangeable AC plug specifically for GE series


| TYPE      |  |  |  |  |  |
|-----------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|           | Australian type                                                                   | U.K type                                                                          | European type                                                                     | US type                                                                             | Mix four type                                                                       |
| ORDER NO. | AC plug-AU                                                                        | AC plug-UK                                                                        | AC plug-EU                                                                        | AC plug-US                                                                          | AC plug-MIX                                                                         |

## SPECIFICATION

| POWER SUPPLY MAIN BODY ORDER NO.      |                                             | GE24I05-P1J                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | GE24I07-P1J | GE24I09-P1J | GE24I12-P1J | GE24I15-P1J | GE24I18-P1J | GE24I24-P1J | GE24I48-P1J |
|---------------------------------------|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| OUTPUT                                | SAFETY MODEL NO.                            | GE24I05                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | GE24I07     | GE24I09     | GE24I12     | GE24I15     | GE24I18     | GE24I24     | GE24I48     |
|                                       | DC VOLTAGE <small>Note.2</small>            | 5V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 7.5V        | 9V          | 12V         | 15V         | 18V         | 24V         | 48V         |
|                                       | RATED CURRENT                               | 3.0A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 2.0A        | 2.22A       | 2.0A        | 1.6A        | 1.33A       | 1.0A        | 0.5A        |
|                                       | CURRENT RANGE                               | 0 ~ 3.0A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0 ~ 2.0A    | 0 ~ 2.22A   | 0 ~ 2.0A    | 0 ~ 1.6A    | 0 ~ 1.33A   | 0 ~ 1.0A    | 0 ~ 0.5A    |
|                                       | RATED POWER (max.)                          | 15W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 15W         | 20W         | 24W         | 24W         | 24W         | 24W         | 24W         |
|                                       | RIPPLE & NOISE (max.) <small>Note.3</small> | 50mVp-p                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 75mVp-p     | 100mVp-p    | 120mVp-p    | 150mVp-p    | 180mVp-p    | 240mVp-p    | 300mVp-p    |
|                                       | VOLTAGE TOLERANCE <small>Note.4</small>     | ±5.0%                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | ±5.0%       | ±5.0%       | ±3.0%       | ±3.0%       | ±3.0%       | ±3.0%       | ±3.0%       |
|                                       | LINE REGULATION <small>Note.5</small>       | ±1.0%                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | ±1.0%       | ±1.0%       | ±1.0%       | ±1.0%       | ±1.0%       | ±1.0%       | ±1.0%       |
|                                       | LOAD REGULATION <small>Note.6</small>       | ±5.0%                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | ±5.0%       | ±5.0%       | ±3.0%       | ±3.0%       | ±3.0%       | ±3.0%       | ±3.0%       |
| INPUT                                 | SETUP, RISE, HOLD UP TIME                   | 4000ms, 100ms, 30ms / 230VAC      4000ms, 100ms, 10ms / 115VAC at full load                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |             |             |             |             |             |             |             |
|                                       | VOLTAGE RANGE <small>Note.7</small>         | 90 ~ 264VAC      135 ~ 370VDC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |             |             |             |             |             |             |             |
|                                       | FREQUENCY RANGE                             | 47 ~ 63Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |             |             |             |             |             |             |             |
|                                       | EFFICIENCY (Typ.)                           | 81%                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 83%         | 85.5%       | 86%         | 86%         | 87%         | 87.5%       | 89%         |
|                                       | AC CURRENT                                  | 0.7A / 100VAC      0.4A / 230VAC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |             |             |             |             |             |             |             |
|                                       | INRUSH CURRENT (max.)                       | COLD START 40A / 100VAC      80A / 230VAC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |             |             |             |             |             |             |             |
| PROTECTION                            | OVERLOAD                                    | 110% ~ 200% rated output power<br>Protection type : Hiccup mode, recovers automatically after fault condition is removed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |             |             |             |             |             |             |             |
|                                       | OVER VOLTAGE                                | 115% ~ 135% rated output voltage<br>Protection type : Clamp by zener diode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |             |             |             |             |             |             |             |
|                                       | WORKING TEMP.                               | -10 ~ +50°C (Refer to "Derating Curve")                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |             |             |             |             |             |             |             |
| ENVIRONMENT                           | WORKING HUMIDITY                            | 20% ~ 90% RH non-condensing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |             |             |             |             |             |             |             |
|                                       | STORAGE TEMP., HUMIDITY                     | -20 ~ +85°C, 10 ~ 95% RH                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |             |             |             |             |             |             |             |
|                                       | TEMP. COEFFICIENT                           | ±0.03% / °C (0 ~ 30°C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |             |             |             |             |             |             |             |
|                                       | VIBRATION                                   | 10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |             |             |             |             |             |             |             |
| SAFETY & EMC <small>(Note. 8)</small> | SAFETY STANDARDS                            | UL60950-1, CSA C22.2, TUV EN60950-1, AS/NZS 60950.1, CCC GB4943 approved                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |             |             |             |             |             |             |             |
|                                       | WITHSTAND VOLTAGE                           | I/P-O/P:4242VDC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |             |             |             |             |             |             |             |
|                                       | ISOLATION RESISTANCE                        | I/P-O/P:100M Ohms / 500VDC / 25°C / 70% RH                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |             |             |             |             |             |             |             |
|                                       | EMC EMISSION                                | Compliance to EN55032, EN61000-3-2,3, FCC part15, GB9254 class B, GB17625.1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |             |             |             |             |             |             |             |
| OTHERS                                | EMC IMMUNITY                                | Compliance to EN61000-4-2,3,4,5,6,8,11, light industry level, criteria A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |             |             |             |             |             |             |             |
|                                       | LIFE                                        | 2 years : 100% load 30°C, 8 hours / day                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |             |             |             |             |             |             |             |
|                                       | MTBF                                        | 100Khrs min.      MIL-HDBK-217F (25°C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |             |             |             |             |             |             |             |
|                                       | DIMENSION                                   | 81*43*40.5mm (L*W*H)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |             |             |             |             |             |             |             |
| DC OUTPUT CONNECTOR                   | PACKING                                     | 134g ; 50pcs / 8.4kg / CARTON                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |             |             |             |             |             |             |             |
|                                       | PLUG                                        | See page 2 ; Other type available by customer requested                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |             |             |             |             |             |             |             |
| NOTE                                  | CABLE                                       | See page 2 ; Other type available by customer requested                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |             |             |             |             |             |             |             |
|                                       |                                             | 1.All parameters are specified at 230VAC input, rated load, 25°C 70% RH ambient.<br>2.DC voltage: The output voltage set at point measure by plug terminal & 50% load.<br>3.Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.<br>4.Tolerance: includes set up tolerance, line regulation, load regulation.<br>5.Line regulation is measured from low line to high line at rated load.<br>6.Load regulation is measured from 10% to 100% rated load<br>7.Derating may be needed under low input voltage. Please check the derating curve for more details.<br>8.The power supply is considered as an independent unit, but the final equipment still need to re-confirm that the whole system complies with the EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies."<br>(as available on <a href="http://www.meanwell.com">http://www.meanwell.com</a> )<br>9.Main body unit and AC inlet plug should be ordered separately ; it needs to be used along with any of the AC inlet plug. |             |             |             |             |             |             |             |

## Mechanical Specification

Unit:mm




## Plug Assignment

Standard plug: P1J

| P1J    |        |
|--------|--------|
| P/N    | OUTPUT |
| CENTER | +      |

## Derating Curve



## Static Characteristics

