PBLS6021D

60 V, 1.5 A PNP BISS loadswitch

28 May 2026 **Product data sheet**

1. General description

PNP low V_{CEsat} transistor and NPN Resistor- Equipped Transistor (RET) in a SOT457 (SC-74) small Surface-Mounted Device (SMD) plastic package.

2. Features and benefits

- Low V_{CEsat} and resistor-equipped transistor in one package
- Low threshold voltage (<1 V) compared to MOSFET
- Space-saving solution
- Reduction of component count

3. Applications

- Supply line switches
- Battery charger switches
- High-side switches for LEDs, drivers and backlights
- Portable equipment

4. Quick reference data

Table 1. Quick reference data

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
TR1; PNP low V_{CEsat} transistor							
V_{CEO}	collector-emitter voltage	open base		-	-	-60	V
I_C	collector current			-	-	-1.5	A
I_{CM}	peak collector current	single pulse; $t_p \leq$ 1 ms		-	-	-3	A
R_{CEsat}	collector-emitter saturation resistance	I_C = -1.5 A; I_B = -100 mA; $t_p \leq$ 300 µs; $\delta_{factor} \leq$ 0.02; T_{amb} = 25 °C		-	110	175	mΩ
TR2; NPN resistor-equipped transistor							
V_{CEO}	collector-emitter voltage	open base		-	-	50	V
I_O	output current			-	-	100	mA
R1	bias resistor 1 (input)	T_{amb} = 25 °C		1.54	2.2	2.86	kΩ
R2/R1	bias resistor ratio			0.8	1	1.2	

Downloaded from Arrow.com.

5. Pinning information

Table 2. Pinning information

Pin	Symbol	Description	Simplified outline	Graphic symbol
1	B1	base TR1	 TSOP6 (SOT457)	
2	I2	input (base) TR2		
3	O2	output (collector) TR2		
4	GND2	GND (emitter) TR2		
5	C1	collector TR1		
6	E1	emitter TR1		

6. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
PBLS6021D	TSOP6	plastic, surface-mounted package (SC-74; TSOP6); 6 leads	SOT457

7. Marking

Table 4. Marking codes

Type number	Marking code
PBLS6021D	KE

8. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions		Min	Max	Unit
TR1; PNP low V_{CEsat} transistor						
V_{CBO}	collector-base voltage	open emitter		-	-60	V
V_{CEO}	collector-emitter voltage	open base		-	-60	V
V_{EBO}	emitter-base voltage	open collector		-	-5	V
I_C	collector current			-	-1.5	A
I_{CM}	peak collector current	single pulse; $t_p \leq$ 1 ms		-	-3	A
I_B	base current			-	-300	mA
I_{BM}	peak base current	single pulse; $t_p \leq$ 1 ms		-	-1	A
P_{tot}	total power dissipation	$T_{amb} \leq$ 25 °C	[1]	-	370	mW
			[2]	-	480	mW
			[3]	-	630	mW
TR2; NPN resistor-equipped transistor						
V_{CBO}	collector-base voltage	open emitter		-	50	V
V_{CEO}	collector-emitter voltage	open base		-	50	V

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.

Symbol	Parameter	Conditions		Min	Max	Unit
V_{EBO}	emitter-base voltage	open collector		-	10	V
V_I	input voltage			-10	12	V
I_O	output current			-	100	mA
I_{CM}	peak collector current	single pulse; $t_p \leq$ 1 ms		-	100	mA
P_{tot}	total power dissipation	$T_{amb} \leq$ 25 °C	[1] [2] [3]	-	200	mW
Per device						
P_{tot}	total power dissipation	$T_{amb} \leq$ 25 °C	[1]	-	480	mW
			[2]	-	590	mW
			[3]	-	760	mW
T_j	junction temperature			-	150	°C
T_{amb}	ambient temperature			-55	150	°C
T_{stg}	storage temperature			-65	150	°C

[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint.
[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 1 cm^2.
[3] Device mounted on a ceramic PCB, Al_2O_3, standard footprint.



(1) Ceramic PCB, A_2O_3, standard footprint
(2) FR4 PCB, mounting pad for collector 1 cm^2
(3) FR4 PCB, standard footprint

Fig. 1. Power derating curve

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.

9. Thermal characteristics

Table 6. Thermal characteristics

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
$R_{th(j-sp)}$	thermal resistance from junction to solder point			-	-	100	K/W
Per device							
$R_{th(j-a)}$	thermal resistance from junction to ambient	in free air	[1]	-	-	260	K/W
			[2]	-	-	211	K/W
			[3]	-	-	165	K/W

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.
[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 1 cm^2.
[3] Device mounted on a ceramic PCB, Al_2O_3, standard footprint.



FR4 PCB, standard footprint

Fig. 2. TR1 (PNP): Transient thermal impedance from junction to ambient as a function of pulse duration; typical values



FR4 PCB, mounting pad for collector 1 cm^2

Fig. 3. TR1 (PNP): Transient thermal impedance from junction to ambient as a function of pulse duration; typical values

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.



Ceramic PCB, Al_2O_3, standard footprint

Fig. 4. TR1 (PNP): Transient thermal impedance from junction to ambient as a function of pulse duration; typical values

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.

10. Characteristics

Table 7. Characteristics

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
TR1; PNP low V_{CEsat} transistor							
I_{CBO}	collector-base cut-off current	V_{CB} = -60 V; I_E = 0 A; T_{amb} = 25 °C		-	-	-100	nA
		V_{CB} = -60 V; I_E = 0 A; T_j = 150 °C		-	-	-50	µA
I_{CES}	collector-emitter cut-off current	V_{CE} = -48 V; V_{BE} = 0 V; T_{amb} = 25 °C		-	-	-100	nA
I_{EBO}	emitter-base cut-off current	V_{EB} = -5 V; I_C = 0 A; T_{amb} = 25 °C		-	-	-100	nA
h_{FE}	DC current gain	V_{CE} = -2 V; I_C = -100 mA; T_{amb} = 25 °C		180	285	-	
		V_{CE} = -2 V; I_C = -500 mA; pulsed; t_p ≤ 300 µs; δ ≤ 0.02; T_{amb} = 25 °C		150	255	-	
		V_{CE} = -2 V; I_C = -1 A; pulsed; t_p ≤ 300 µs; δ ≤ 0.02; T_{amb} = 25 °C		140	210	-	
		V_{CE} = -2 V; I_C = -1.5 A; pulsed; t_p ≤ 300 µs; δ ≤ 0.02; T_{amb} = 25 °C		120	185	-	
V_{CEsat}	collector-emitter saturation voltage	I_C = -0.5 A; I_B = -50 mA; t_p ≤ 300 µs; δ ≤ 0.02; T_{amb} = 25 °C		-	-65	-100	mV
		I_C = -1 A; I_B = -50 mA; t_p ≤ 300 µs; δ ≤ 0.02; T_{amb} = 25 °C		-	-130	-200	mV
		I_C = -1 A; I_B = -100 mA; pulsed; t_p ≤ 300 µs; δ ≤ 0.02; T_{amb} = 25 °C		-	-110	-170	mV
		I_C = -1.5 A; I_B = -100 mA; pulsed; t_p ≤ 300 µs; δ ≤ 0.02; T_{amb} = 25 °C		-	-165	-260	mV
R_{CEsat}	collector-emitter saturation resistance	I_C = -1 A; I_B = -100 mA; pulsed; t_p ≤ 300 µs; δ_{factor} ≤ 0.02; T_{amb} = 25 °C		-	110	170	mΩ
		I_C = -1.5 A; I_B = -100 mA; t_p ≤ 300 µs; δ_{factor} ≤ 0.02; T_{amb} = 25 °C		-	110	175	mΩ
V_{BEsat}	base-emitter saturation voltage	I_C = -0.5 A; I_B = -50 mA; T_{mb} = 25 °C; t_p ≤ 300 µs; δ_{factor} ≤ 0.02; T_{amb} = 25 °C		-	-0.85	-1	V
		I_C = -1.5 A; I_B = -100 mA; t_p = 300 µs; δ_{factor} ≤ 0.02; T_{amb} = 25 °C		-	-0.93	-1.1	V
V_{BEon}	base-emitter turn-on voltage	V_{CE} = -10 V; I_C = -1 A; pulsed; t_p ≤ 300 µs; δ_{factor} ≤ 0.02; T_{amb} = 25 °C		-	-0.75	-1.1	V
t_d	delay time	V_{CC} = -10 V; I_C = -1 A; T_{amb} = 25 °C		-	17	-	ns
t_r	rise time	I_{Bon} = -50 mA; I_{Boff} = 50 mA; T_{amb} = 25 °C		-	38	-	ns
t_{on}	turn-on time	T_{amb} = 25 °C		-	55	-	ns
t_s	storage time			-	350	-	ns
t_f	fall time			-	65	-	ns
t_{off}	turn-off time			-	415	-	ns
C_c	collector capacitance	V_{CB} = -10 V; I_E = 0 A; i_e = 0 A; f = 1 MHz; T_{amb} = 25 °C		-	30	-	pF
f_T	transition frequency	V_{CE} = -10 V; I_C = -50 mA; f = 100 MHz; T_{amb} = 25 °C		-	150	-	MHz
TR2; NPN resistor-equipped transistor							
I_{CBO}	collector-base cut-off current	V_{CB} = 50 V; I_E = 0 A; T_{amb} = 25 °C		-	-	100	nA

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
I_{CEO}	collector-emitter cut-off current	V_{CE} = 30 V; I_B = 0 A; T_{amb} = 25 °C		-	-	1	µA
		V_{CE} = 30 V; I_B = 0 A; T_j = 150 °C		-	-	50	µA
I_{EBO}	emitter-base cut-off current	V_{EB} = 5 V; I_C = 0 A; T_{amb} = 25 °C		-	-	2	mA
h_{FE}	DC current gain	V_{CE} = 5 V; I_C = 20 mA; T_{amb} = 25 °C		30	-	-	
V_{CEsat}	collector-emitter saturation voltage	I_C = 10 mA; I_B = 0.5 mA; T_{amb} = 25 °C		-	-	150	mV
$V_{I(off)}$	off-state input voltage	V_{CE} = 5 V; I_C = 1 mA; T_{amb} = 25 °C		-	1.2	0.5	V
$V_{I(on)}$	on-state input voltage	V_{CE} = 0.3 V; I_C = 20 mA; T_{amb} = 25 °C		2	1.6	-	V
R1	bias resistor 1 (input)	T_{amb} = 25 °C		1.54	2.2	2.86	kΩ
R2/R1	bias resistor ratio			0.8	1	1.2	
C_c	collector capacitance	V_{CB} = 10 V; I_E = 0 A; i_e = 0 A; f = 1 MHz; T_{amb} = 25 °C		-	-	2.5	pF



V_{CE} = -2 V
(1) T_{amb} = 100 °C
(2) T_{amb} = 25 °C
(3) T_{amb} = -55 °C

Fig. 5. TR1 (PNP): DC current gain as a function of collector current; typical values



T_{amb} = 25 °C

Fig. 6. TR1 (PNP): Collector current as a function of collector-emitter voltage; typical values

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.



V_{CE} = −2 V
(1) T_{amb} = −55 °C
(2) T_{amb} = 25 °C
(3) T_{amb} = 100 °C

Fig. 7. TR1 (PNP): Base-emitter voltage as a function of collector current; typical values



I_C/I_B = 20
(1) T_{amb} = −55 °C
(2) T_{amb} = 25 °C
(3) T_{amb} = 100 °C

Fig. 8. TR1 (PNP): Base-emitter saturation voltage as a function of collector current; typical values



I_C/I_B = 20
(1) T_{amb} = 100 °C
(2) T_{amb} = 25 °C
(3)T_{amb} = -55 °C

Fig. 9. TR1 (PNP): Collector-emitter saturation voltage as a function of collector current; typical values



T_{amb} = 25 °C
(1) I_C/I_B = 100
(2) I_C/I_B = 50
(3) I_C/I_B = 10

Fig. 10. TR1 (PNP): Collector-emitter saturation voltage as a function of collector current; typical values

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.



I_C/I_B = 20
(1)T_{amb} = 100 °C
(2) T_{amb} = 25 °C
(3) T_{amb} = -55 °C

Fig. 11. TR1 (PNP): Collector-emitter saturation resistance as a function of collector current; typical values



T_{amb} = 25 °C
(1) I_C/I_B = 100
(2) I_C/I_B = 50
(3) I_C/I_B = 10

Fig. 12. TR1 (PNP): Collector-emitter saturation resistance as a function of collector current; typical values



V_{CE} = 5 V
(1) T_{amb} = 150 °C
(2) T_{amb} = 25 °C
(3) T_{amb} = −40 °C

Fig. 13. TR2 (NPN): DC current gain as a function of collector current; typical values



V_{CE} = 0.3 V
(1) T_{amb} = -40 °C
(2) T_{amb} = 25 °C
(3) T_{amb} = 100 °C

Fig. 14. TR2 (NPN): On-state input voltage as a function of collector current; typical values

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.



V_{CE} = 5 V
(1) T_{amb} = -40 °C
(2) T_{amb} = 25 °C
(3) T_{amb} = 100 °C

Fig. 15. TR2 (NPN): Off-state input voltage as a function of collector current; typical values



I_C/I_B = 20
(1) T_{amb} = 100 °C
(2) T_{amb} = 25 °C
(3) T_{amb} = -40 °C

Fig. 16. TR2 (NPN): Collector-emitter saturation voltage as a function of collector current; typical values



I_C/I_B = 50; T_{amb} = 25 °C

Fig. 17. TR2 (NPN): Collector-emitter saturation voltage as a function of collector current; typical values

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.

11. Test information



Fig. 18. TR1: Transistor switching time definition



V_{CC} = -10 V; I_C = -1 A; I_{Bon} = -50 mA; I_{Boff} = 50 mA

Fig. 19. TR1: Test circuit for switching times

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.

12. Package outline



Fig. 20. Package outline TSOP6 (SOT457)

13. Soldering



Fig. 21. Reflow soldering footprint for TSOP6 (SOT457)

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.



Fig. 22. Wave soldering footprint for TSOP6 (SOT457)

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.

14. Revision history

Table 8. Revision history

Data sheet ID	Release date	Data sheet status	Change notice	Supersedes
PBLS6021D v.3	20260528	Product data sheet	-	PBLS6021D v.2
Modifications:	• Pinning information symbol and description is corrected.			
PBLS6021D v.2	20260223	Product data sheet	-	PBLS6021D_1
PBLS6021D_1	20090812	Product data sheet	-	-

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.

15. Legal information

Data sheet status

Document status [1][2]	Product status [3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.
[2] The term 'short data sheet' is explained in section "Definitions".
[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the internet at https://www.nexperia.com.

Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of Nexperia.

Right to make changes — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use in automotive applications — This Nexperia product has been qualified for use in automotive applications. Unless otherwise agreed in writing, the product is not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nexperia.com/profile/terms, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2026. All rights reserved

Downloaded from Arrow.com.

Contents

1. General description....1
2. Features and benefits....1
3. Applications....1
4. Quick reference data....1
5. Pinning information....2
6. Ordering information....2
7. Marking....2
8. Limiting values....2
9. Thermal characteristics....4
10. Characteristics....6
11. Test information....11
12. Package outline....12
13. Soldering....12
14. Revision history....14
15. Legal information....15

© Nexperia B.V. 2026. All rights reserved

For more information, please visit: http://www.nexperia.com
For sales office addresses, please send an email to: salesaddresses@nexperia.com
Date of release: 28 May 2026

Downloaded from Arrow.com.