



KK3A40U2N, AL Universal Terminal, 3-Conductor, 2-Hole

By Burndy

Catalog # [KK3A40U2N](#)

Aluminum Universal Terminal, 3 Conductor, 2 Hole, 300-800 kcmil, 1/2" Stud, 1.75" Stud Hole Spacing, 6 Screws, Al/Cu Rated, Tin Plated

Features

- Dual rated panelboard lugs constructed from high strength extruded aluminum alloy , electro tin-plated to provide low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Certification - UL Recognized	No
Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Buy America(n) Qualified	• Buy America Compliant (All status valid till December 2026) • Buy American Act Compliant (All status valid till December 2026) • BABA Compliant (All status valid till December 2026)
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Number Of Wires	3
Conductor - AL Str Size	• 300 kcmil • 336 kcmil • 350 kcmil • 397 kcmil • 400 kcmil • 450 kcmil • 477 kcmil • 500 kcmil • 550 kcmil • 556 kcmil



- 600 kcmil
- 636 kcmil
- 650 kcmil
- 700 kcmil
- 715 kcmil
- 750 kcmil
- 795 kcmil
- 800 kcmil

Conductor - AL Str Size Range	300-800 Kcmil
Conductor Size	300-800 KCMIL
Conductor Type	• CU C Str-Size • AL C Str-Size
Conductor - Copper Str Size Range	300-800 Kcmil

Configuration

Physical Attribute - Number of Holes	2
Connector Type	Parallel Set-Screw

Dimensions

Dimension - Pad Width inch	4.28 in
Dimension - Height mm	48 mm
Dimension - Hole Size fraction	9/16
Dimension - Height inch	1.89 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	157 mm
Dimension - Hole Size mm	14 mm
Dimension - Hole Size inch	0.56 in
Dimension - Stud Size inch	0.56 in
Dimension - Bolt Hole Size inch	0.56 in
Dimension - Bolt Size fraction	1/2
Dimension - N inch	0.63 in
Dimension - Length Overall inch	6.19 in

General

Material - Hardware Plated	Aluminum Y
Sub Brand	UNIVERSAL TERMINAL
UPC	781810600474
Type	Bolted Lugs & Terminals
Material	Aluminum

Plating Type	Tin Plated	Pallet Quantity	12
UPC 14 Digit GTIN	00781810600474	Carton Quantity	12

Logistics

Minimum Pack Quantity 1



A Hubbell brand

Product Assets

[Catalog \[English\]](#)

© 2026 Hubbell Incorporated. All rights reserved
BRDY-KK3A40U2N-SPEC-EN | REV 5/2026