PB 1021 Test Jack, PCB Mounting, Ø 2 mm, 6.3 A



See below:

Approvals and Compliances

Description

- PCB
- Test Jack , Diameter 2.0 mm
- measuring and testing during operation
- horizontal and vertical connections
- Continuous electrical connection
- Resilient contacts, gold plated

Weblinks

pdf data sheet, html datasheet, General Product Information, Approvals, Distributor-Stock-Check, Accessories, Detailed request for product

Technical Data

Diameter	2mm
Rated current	6.3A
Admissible switching power	
	220 W / max. 5 A or 75 VDC
	440 W / max. 5 A or 50 VAC
Contact resistance	$<7\text{m}\Omega$ at 20 mV
Allowable Operation Tempe-	-25°C to 70°C
rature	

Solderability	235°C / 2 sec acc. to IEC 60068-2-	
	20, Test Ta, method 1	
Resistance to Soldering Heat	260°C / 5 sec acc. to IEC 60068-2-	
	20 , Test Tb, method 1A	
Weight	0.5 g	
Material: Housing	Thermoplastic (PC), UL 94V-2	
Surface of contacts	gold plated, Thickness 0.5 µm	

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Application standards

Application standards where the product can be used


Organization	Design	Standard	Description
<u>IEC</u>	Suitable for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1. Safety requirements

Compliances

The product complies with following Guide Lines


Identification	Details	Initiator	Description
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
©	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimensions [mm]





Diagrams



Variants

Product group	Color	Order Number
Test Jack	black	0040.1021
Test Jack	red	0040.1022
Test Jack	blue	0040.1024

Availability for all products can be searched real-time: https://www.schurter.com/en/info-center/support-tools/stock-check-distributors

Packaging unit

100 Pcs

Mating Inlets/Plugs

Category / Description



Test Jacks & Probes Overview complete

PS 1061, 10 A, Test Probe

PS 1061