

DeviceDrive Click



PID: MIKROE-3663

DeviceDrive Click is a complete Cloud-on-Module solution with Wi-Fi functionality and an integrated PCB antenna. The onboard ESP-WROOM-02 module comes preloaded with DeviceDrive firmware which completely offloads Wi-Fi networking functionality from the application processor and enables features like OTA upgrade, automatic connection to the DeviceDrive Cloud and Mobile App. Each DeviceDrive click board is coming with the FREE activation your complete development and test of your application.

The ESP-WROOM-02 module uses the UART interface (with JSON command format) for communication with external devices. With this board, you are getting FREE of charge access to the Mobile App, Cloud IoT-Hub, and ESP-WROOM-02 Firmware for testing your idea.

DeviceDrives click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board™ comes as a fully tested product, ready to be used on a system equipped with the mikroBUS™ socket.

This WiFi-Click board is based on a WiFi (802.11B/G/N) module from company Devicedrive with ready Firmware, which enables a plug & play Smart onboarding. In addition, you can use the Devicedrive Playground APP and Cloud for FREE for your application R&D. When your application is developed/tested, you can deal with Devicedrive to use your own Cloud or let Devicedrive help you to build your own Azure Cloud.

If you are interested to know how to start IoT development with DeviceDrive click and ESP-WROOM-02 Client Simulator, feel free to read our [DeviceDrive Click User Manual](#).

The DeviceDrive click is a low-cost Cloud enabler device with extremely simple software

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
 ISO 14001: 2015 certification of environmental management system.
 OHSAS 18001: 2008 certification of occupational health and safety management system.




ISO 9001: 2015 certification of quality management system (QMS).

integration, that will allow you an instant connection to the DeviceDrive Cloud. The ESP-WROOM-02 module is equipped with low power MCU that runs the WiFi stack (not available for host-applications). The ESP-WROOM-02 provides unsurpassed ability to embed Wi-Fi capabilities into devices with the lowest cost, and minimal space requirement. The ESP-WROOM-021 has been designed for mobile electronics and Internet of Things (IoT) applications. The aim is to achieve the lowest power consumption possible with a combination of several proprietary techniques and very few components.

How does it work?

The DeviceDrive click is equipped with the [WRF01-M24A](#) a 802.11b/g/n module, specially programmed by the [DeviceDrive](#) company to enable direct connection to their Cloud. The module has integrated Tensilica Diamond L106 32bit cache-less microcontroller, which features extra low power consumption and like that is perfectly suited for the battery powered IoT applications.



The ESP-WROOM-02 module handles all connectivity issues so that your device can simply send JSON on the UART and get reply from your selected cloud solution. The function of the ESP-WROOM-02 is to work as a Wi-Fi adapter between your application and Cloud through simple UART serial connectivity for commands and cloud transmissions. The ESP-WROOM-02 is a part of the DeviceDrive Smart Connectivity Platform (DDCP); a set of high performance, high integration wireless SOCs, designed for space and power constrained mobile platform designers.

In order to enable easier testing of the ESP-WROOM-02 module and Cloud solution, DeviceDrives offers also ESP-WROOM-02 Client Simulator. The program communicates with the ESP-WROOM-02 through the serial ports and is suited for acting as a client and for prototyping IoT-Products.

For more information about DeviceDrive Cloud, ESP-WROOM-02 specifications and Client Simulator please visit their official page [Downloads section](#).

The ESP-WROOM-02 comes with a LinkUp™ SDK for Android for easy Wi-Fi setup using HTTP/SSL. The LinkUp™ software takes care of all the complexity of connecting any device to your selected cloud system (SSID, password, token and product key), in the most safe and easy way.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
ISO 14001: 2015 certification of environmental management system.
OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

Note, that you need to order a FREE product key from <https://manage.devicedrive.com> to redirect the data to your selected cloud. The same product key should be applied to all devices of the same type communicating with the same target cloud. You can set the product key from the mobile app or through the serial interface.

DeviceDrive Cloud

The DeviceDrive Cloud platform gives you the right tools and services to handle connections, gather and make sense of data, and provide the reliable customer experiences required for modern hardware devices. Your device sends JSON formatted data and gets JSON back from the cloud without having to worry about how it all happened. Their LinkUp SDKs lets your mobile App link the device seamlessly to the network, to the user and to the cloud.

Use their [management portal](#) to monitor and debug communication flow and direct the data to a destination of your choice for each of your products.


The DeviceDrive ecosystem consists of building blocks adjustable to the business model of each customer. It offers cloud services like OTA upgrades, Cloud Storage, Device Management, Data Analytics, VSaaS, Security and many others.

Specifications

Type	Cloud Routers,WiFi
Applications	The ESP-WROOM-02 has been designed for mobile, wearable electronics and Internet of Things (IoT) applications.
On-board modules	The WRF01-M24A module with 802.11 b/g/n protocol which handles all connectivity tasks and feature PCB antenna
Key Features	Enable easy and fast connectivity to the cloud, low power mode, simple serial interface for communication.
Interface	UART
Feature	No ClickID
Compatibility	mikroBUS™
Click board size	M (42.9 x 25.4 mm)
Input Voltage	3.3V

Pinout diagram

This table shows how the pinout on DeviceDrive click corresponds to the pinout on the mikroBUS™ socket (the latter shown in the two middle columns).

Notes	Pin					Pin	Notes
	NC	1	AN	PWM	16	NC	
Reset	RST	2	RST	INT	15	NC	

Mikroe produces entire development rootchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
 ISO 14001: 2015 certification of environmental management system.
 OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

Enable	EN	3	CS	RX	14	TX	UART Transmit
	NC	4	SCK	TX	13	RX	UART Receive
	NC	5	MISO	SCL	12	NC	
	NC	6	MOSI	SDA	11	NC	
Power Supply	3.3V	7	3.3V	5V	10	NC	
Ground	GND	8	GND	GND	9	GND	Ground

Onboard settings and indicators

Label	Name	Default	Description
LD1	PWR	-	Power LED Indicator

Software Support

We provide a library for the DeviceDrive click on our [LibStock](#) page, as well as a demo application (example), developed using MikroElektronika [compilers](#). The demo can run on all the main MikroElektronika [development boards](#).

Library Description

This library allows user to perform a control of the DeviceDrive click and communication between device and cloud. User has options to send commands, configurations, messages, files... Every response from the ESP-WROOM-02 module will be sent to the user via handler function in JSON format. On this way every response on the sent command, every indication, connection status of the local network, device status can be checked and processed by the user. This library has also some necessary and important commands to perform network connection, module configuration and messages sending. For more details check full documentation.

Key functions:

- void dd_uartDriverInit(T_DD_P gpioObj, T_DD_P uartObj) - This function initializes UART serial interface.
- void dd_send_cmd(char *cmd_string) - This function allows user to send a command to the module.
- T_DD_RETVAL dd_process(void) - This function performs a response processing.
- void dd_setup(const char *param_code, const char *param_value) - This command allows user to send setup commands to the WRF01.

Examples description

The application is composed of three sections :

- System Initialization - Initializes peripherals and pins.
- Application Initialization - Initializes UART serial interface and interrupt, executes wake up sequence and asks user which command will be performed for module setting. Also writes all possible commands to the uart terminal.
- Application Task - (code snippet) - Checks which character (command) was received from the user and executes the determined command. The response from the module will be received and processed independently on the user, did user send any of the possible commands or not. The response, module and connection status, debug and error reports, command messages will be sent to the uart terminal.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
 ISO 14001: 2015 certification of environmental management system.
 OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

Additional Functions :

- `getResponse` - Gets and stores the response from the WRF01 module (handler function).
- `processResponse` - Checks the response in the determined time interval, and when response was ready writes response to the uart terminal.
- `checkCmd` - Allows user to enter the desired answer (command), y - yes, n - no.
- `logCmd` - Writes all possible commands for the user to the uart terminal.
- `rx_isr` - Catches the response bytes from the module one by one, when module was send some bytes to the host.

The full application code, and ready to use projects can be found on our [LibStock](#) page.

Other mikroE Libraries used in the example:

- UART

Depending on the development board you are using, you may need [USB UART click](#), [USB UART 2 click](#) or [RS232 click](#) to connect to your PC, for development systems with no UART to USB interface available on the board. The terminal available in all MikroElektronika [compilers](#), or any other terminal application of your choice, can be used to read the message.

mikroSDK

This Click board™ is supported with [mikroSDK](#) - MikroElektronika Software Development Kit. To ensure proper operation of mikroSDK compliant Click board™ demo applications, mikroSDK should be downloaded from the [LibStock](#) and installed for the compiler you are using.

For more information about mikroSDK, visit the [official page](#).

Resources

[mikroBUS™](#)

[mikroSDK](#)

[Click board™ Catalog](#)

[Click Boards™](#)

Downloads

[DeviceDrive click example on Libstock](#)

[DeviceDrive click 2D and 3D files](#)

[WRF01-M24A datasheet](#)

[DeviceDrive click schematic](#)

[DeviceDrive click - Serial Specification](#)

[DeviceDrive click User Manual](#)

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
ISO 14001: 2015 certification of environmental management system.
OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).