

DELPHI Connection Systems

Catalog

Customer Service

Comparison List (0)

Samples Request

Find by Feature

Browse by Category

Browse by Application

Share

12103010

Search

Enter part number or keyword

Search Results (1)

Search

Options

1 Result(s): [All] - 12103010

☐ Compare

12103010 - Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2

☐ Compare

Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2

Part # 12103010



Question about this product?

Attributes	Documents (3)
Part # :	12103010
Part # :	12103010
Part # :	12103010
Part # :	 12103010
Part # :	12103010
Part # :	12103010
Part # :	12103010
Part # :	12103010
Part # :	12103010
Part # :	12103010
Part # :	12103010
Part # :	12103010
Part # :	12103010
Part # :	12103010
Part # :	12103010
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	 Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2

Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Description :	Battery Ring Unsealed Tin Plating Terminal, Cable Range 50.00 - 62.00 mm2
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	✔ Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Product Type :	Terminal
Status :	Active
Status :	Active
Status :	Active
Status :	✔ Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Status :	Active
Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	✔ RING

Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	RING
Terminal Family :	RING
Series :	BATT
Series :	BATT
Series :	BATT
Series :	✔ BATT
Series :	BATT
Series :	BATT
Series :	BATT
Series :	BATT
Series :	BATT
Series :	BATT
Series :	BATT
Series :	BATT
Series :	BATT
Series :	BATT
Series :	BATT
Series :	BATT
Series :	BATT
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	✔ Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Weight [g] :	16
Weight [g] :	16
Weight [g] :	16


Weight [g] :	 16
Weight [g] :	16
Weight [g] :	16
Weight [g] :	16
Weight [g] :	16
Weight [g] :	16
Weight [g] :	16
Weight [g] :	16
Weight [g] :	16
Weight [g] :	16
Weight [g] :	16
Weight [g] :	16
Weight [g] :	16
Weight [g] :	16
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	 Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Minimum Cable Diameter [mm] :	12.00
Minimum Cable Diameter [mm] :	12.00
Minimum Cable Diameter [mm] :	12.00
Minimum Cable Diameter [mm] :	 12.00
Minimum Cable Diameter [mm] :	12.00
Minimum Cable Diameter [mm] :	12.00
Minimum Cable Diameter [mm] :	12.00
Minimum Cable Diameter [mm] :	12.00
Minimum Cable Diameter [mm] :	12.00
Minimum Cable Diameter [mm] :	12.00
Minimum Cable Diameter [mm] :	12.00
Minimum Cable Diameter [mm] :	12.00
Minimum Cable Diameter [mm] :	12.00
Minimum Cable Diameter [mm] :	12.00
Maximum Cable Diameter [mm] :	16.00
Maximum Cable Diameter [mm] :	16.00
Maximum Cable Diameter [mm] :	16.00

Maximum Cable Diameter [mm] :	 16.00
Maximum Cable Diameter [mm] :	16.00
Maximum Cable Diameter [mm] :	16.00
Maximum Cable Diameter [mm] :	16.00
Maximum Cable Diameter [mm] :	16.00
Maximum Cable Diameter [mm] :	16.00
Maximum Cable Diameter [mm] :	16.00
Maximum Cable Diameter [mm] :	16.00
Maximum Cable Diameter [mm] :	16.00
Maximum Cable Diameter [mm] :	16.00
Maximum Cable Diameter [mm] :	16.00
Minimum Cable Core Cross Section [mm2] :	50.00
Minimum Cable Core Cross Section [mm2] :	50.00
Minimum Cable Core Cross Section [mm2] :	50.00
Minimum Cable Core Cross Section [mm2] :	 50.00
Minimum Cable Core Cross Section [mm2] :	50.00
Minimum Cable Core Cross Section [mm2] :	50.00
Minimum Cable Core Cross Section [mm2] :	50.00
Minimum Cable Core Cross Section [mm2] :	50.00
Minimum Cable Core Cross Section [mm2] :	50.00
Minimum Cable Core Cross Section [mm2] :	50.00
Minimum Cable Core Cross Section [mm2] :	50.00
Minimum Cable Core Cross Section [mm2] :	50.00
Minimum Cable Core Cross Section [mm2] :	50.00
Minimum Cable Core Cross Section [mm2] :	50.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	 62.00
Maximum Cable Core Cross Section [mm2] :	62.00

Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Maximum Cable Core Cross Section [mm2] :	62.00
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	✓ 10.32
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	10.32
Inside Ring Diameter [mm] :	10.32
Outside Ring Diameter [mm] :	20.60
Outside Ring Diameter [mm] :	20.60
Outside Ring Diameter [mm] :	20.60
Outside Ring Diameter [mm] :	✓ 20.60
Outside Ring Diameter [mm] :	20.60
Outside Ring Diameter [mm] :	20.60
Outside Ring Diameter [mm] :	20.60
Outside Ring Diameter [mm] :	20.60
Outside Ring Diameter [mm] :	20.60
Outside Ring Diameter [mm] :	20.60
Outside Ring Diameter [mm] :	20.60
Outside Ring Diameter [mm] :	20.60
Outside Ring Diameter [mm] :	20.60

Outside Ring Diameter [mm] :	20.60
Outside Ring Diameter [mm] :	20.60
Remarks :	Stud Size: M10
Remarks :	Stud Size: M10
Remarks :	Stud Size: M10
Remarks :	✔ Stud Size: M10
Remarks :	Stud Size: M10
Remarks :	Stud Size: M10
Remarks :	Stud Size: M10
Remarks :	Stud Size: M10
Remarks :	Stud Size: M10
Remarks :	Stud Size: M10
Remarks :	Stud Size: M10
Remarks :	Stud Size: M10
Remarks :	Stud Size: M10
Remarks :	Stud Size: M10
Remarks :	Stud Size: M10
RoHs compliant :	✔ Yes
ELV compliant :	✔ Yes

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.



[Suppliers](#) | [Terms of Use](#) | [Privacy](#) | [Mexico Privacy Statement](#) | [Cookie Policy](#) | [Sitemap](#) | [European Safe Harbor](#) | [California Supply Chains Act](#)

© Delphi Automotive LLP. All rights reserved.