

Product Navigation	Home Abou	t Us Products	Investor Relations News	Contact Us	Secure EAX
Circuit Board Indicators	6. 10				
Panel Mount Indicators	Circuit Board Indicators - Through Hole Indicators  2/N# 5530121200F 3 mm Lens				
Solid State Lighting	P/N# <b>5530121200F</b>		II Lelis		
Traffic Signals	Description Package Options	3 mm Bi-Level CBI 50 Pieces Per Bag			
Vehicle Lighting	Product Type Through Hole Indicators Sub Product Type with Bi-Level Housing				
Rail	Configuration	3 mm Lens			
Obstruction Lighting	Viewing Viewing Angle	Right Angle 60			
Hazardous Area Lighting	Test Current (mA)	10mA			
Heliport Lighting	Absolute Maximum	Ratings (Ta = 25	°)	Dietaihad	or Stock Chec
how to purchase  sales contacts  stock check	Solder Temp Operating Temp Storage Temp	260° for 5 sec -55 to +100° C -55 to +100° C		Check stock with now. 5530121200F	
Search • Product Line Search Please select a Product Line to search.	Operating Characteristics				
Circuit Board Indicators	LED Position	Found in position(s): 1	Found in position(s): 2		
find ()	Color	Red	Green		
□ Part # / Text Search	Lamp Type	Single Color	Single Color		
Part No.: Text Search:	LED Type	Standard Efficiency	Standard Efficiency		
	Intensity Min (mcd)	7.4	4.7		
	Intensity Typ (mcd)	10.0	12.6		
search()	Intensity Max (mcd)				
- guick links	Fwd Voltage Min				
Dialight Corporate Video	Fwd Voltage Typ				
	Fwd Voltage Max				
Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. View PDF File	Dom Wavelength Min (nm)				
	Dom Wavelength Typ (nm)				
	Dom Wavelength Max (nm)				
	Power Dissipation Max (mW)	100	100		
Application Notes FAQs	Backlighting				
	Pitch Between Vertical				
Dialight Ltd (UK) Dialight Garufo Dialight BLP LumiDrives	Pitch Between Horizontal				
	Lum Intensity Min				
	Lum Intensity Typ				
	Lum Intensity Max				

