



Products

Timing over Packet Networks (ToPSync)

Other products to view

Timing over Packet Networks (ToPSync)

- > **ACS1790T**  
PLL Frequency Synthesizer with Integrated VCO
- > **ACS9510**  
ToPSync® Timing-over-packet synchronization technology
- > **ACS9520T**  
ToPSync® Timing-over-packet synchronization technology
- > **ACS9550**  
ToPSync® Timing-over-packet synchronization technology slave 1588 device
- > **ACS9593T**  
ToPSync® Timing-over-packet synchronization technology slave 1588 device

**Inside Circuit**  
Newsletter

▶ Get info on product updates, design tips and more...

Home \\[Products](#) \\[Timing & Synchronization](#) \\[Timing over Packet Networks \(ToPSync\)](#) \\[ACS9522T](#)

Text Size [-] [=] [+]

[Send](#) [Print](#) [Feed](#)

Semtech ACS9522T

ToPSync® Timing-over-packet synchronization technology

[+ Add to Watch List](#)

Overview

[Diagrams & Specs](#)

[Docs & Resources](#)

[Sample & Buy](#)

Contact your local Sales Representative for full product specifications

[Datasheet](#)

[Pb Free/ROHS Status](#)

[Check distributor inventory](#)

Features

PTP timing features

- > PTP Grandmaster selection - automatic or manual PTP master/slave mode selection.
- > Powerful network delay analysis - full time-alignment in the slave over hostile networks (Layer 2 or layer 3 networks).
- > Dynamic adaptation - to network delay variations. Network loading change tolerant (e.g., ramps and steps).
- > Time alignment - better than ±1 μs on a managed 10-switch GbE network under G.826120 test conditions.\*
- > Frequency alignment - better than ±10 ppb on a managed 10-switch GbE network under G.826120 test conditions.\*

TDM timing features

- > Programmable TDM timing bandwidth - for wander and jitter tracking/attenuation, 0.1 Hz to 70 Hz in 10 steps.
- > Automatic hit-less source switchover - on loss of input.
- > Output clock phase adjustment - in 6 ps steps to ±200 ns.

Applications

- > Stratum 3, 3E, 4E, 4, SONET Minimum Clock (SMC) or SONET/SDH Equipment Clock (SEC) or Ethernet, IEEE 1588™ (2008) PTP, Synchronous Ethernet, Ethernet Equipment Clock

Packaging

- > LBGA package: 324 pin, 19 mm x 19 mm

Order Codes

- > ACS9522IFALBGT - Lead (Pb)-free, RoHS and WEEE compliant

About Semtech

[Company Overview](#)  
[Management](#)  
[Investors](#)  
[Careers](#)  
[Worldwide Locations](#)

Media Center

[Product Announcements](#)  
[Business Announcements](#)  
[Upcoming Events](#)  
[Graphics / Collateral](#)  
[Newsletter](#)

Sites / Access

[mySemtech](#)  
[m.semtech.com \(Mobile\)](#)  
[C-SIM Design Simulation](#)  
[Partner Portal](#)  
[Site Map](#)

Connect With Us

[Contact Us](#)  
[Sign Up for Newsletter](#)  
[Leave Website Feedback](#)

Follow : [Twitter](#) [YouTube](#) [RSS](#)

Semtech is a Leading Analog & Mixed Signal Products Company  
[Privacy Policy](#) | [Terms of Use](#) | [CA Transparency in Supply Chains Act](#)

©2015 Semtech Corporation. All rights reserved.