

#### **FEATURES**

- · Low profile surface mount holder for Cylindrical Lithium and alkaline batteries
- UL 94V-0 heat resistant nylon housing well suited for reflow soldering
- Battery installation and removal does not require tools
- · Securely holds battery in place
- · Accomodates cells with or without built-in PCB protection circuits
- Polarity clearly marked for orientation
- · Polarized holders available for protection against improper battery installation

.822 [71.6]

.047 [1.19]

(2) PLS

.047 [1.2] DIA. (4) PLS

.136 [3,45] (2) PLS

2.175 [55.2]-

125 [3.18] DIA. (2) PLS

.136 [3.45] -(2) PLS

.094 [2.39] 2.175 [55.2] -

### Operating Temp Range:

-60°F to +290°F (-50°C to +145°C)

#### APPLICATIONS


- · Computer memory, power backup systems
- Digital readers
- Laptop and touch pad computers
- · PLC and industrial controls
- Electronic cigarette/vapor industry



PC Battery Clip Available See Page 11.

# THRU HOLE MOUNT

### SINGLE CELL




Contacts: .012 (.30) Stainless Steel, Tin-Nickel Plate

CAT. NO. 1043 Leaf Springs

CAT. NO. 1043P Polarized Holder

CAT. NO. 1044 Solder Lugs \*see image above

Packaging Spec's: 50 pieces per tray



**SURFACE MOUNT** 


### **SPECIFICATIONS**

Base: High Temp Nylon 46, UL 94V-0 Contacts: .012 (.30) Stainless Steel, Gold Plate (Flash)


CAT. NO. 1042 Leaf Springs

CAT. NO. 1042P Polarized Holder

Packaging Spec's: 50 pieces per tray



#### **DUAL CELL**




Base: High Temp Nylon 46, UL 94V-0 Contacts: .012 (.30) Stainless Steel, Tin-Nickel Plate

CAT. NO. 1049 Dual Springs

CAT. NO. 1049P Polarized Holder

CAT. NO. 1047 Solder Lugs \*see image above

Packaging Spec's: 25 pieces per tray




#### **SPECIFICATIONS**

Base: High Temp Nylon 46, UL 94V-0 Contacts: .012 (.30) Stainless Steel, Gold Plate (Flash)

CAT. NO. 1048 Dual Springs

CAT. NO. 1048P Polarized Holder Packaging Spec's: 25 pieces per tray



## Tel (718) 956-8900 • Fax (718) 956-9040 (800) 221-5510 • kec@keyelco.com