NEUTRIK

# NC4FXX-B

4 pole female cable connector with black metal housing and gold contacts.

The next generation of the worldwide accepted standard of XLR cable connectors. The successor of the X series offers several new features which make it more reliable, easier to assemble and improves contact integrity as well cable strain relief.

## Features & Benefits

- Unique cage design of female contact for low contact resistance and high integrity
- Female contact incorporates a solder barrier to prevent solder running into the contact mating area
- Female connector with improved solid metal latch which is larger and easier to handle
- Additional ground spring contacts for better shell ground continuity
- Improved chuck type strain relief provides higher pull-out force and makes assembly easier and faster
- Boot with polyurethane gland gives high protection to cable bending stresses
- Colored rings and boots available for coding or identification
- Sleek and ergonomic design - valuable and handy
- Rugged zinc diecast shell, longlasting and dependable
- Internal thread on shell is well protected against any damage

## Technical Information


All rights reserved / 19.06.2026


Downloaded from Arrow.com.

NEUTRIK

| Product | |
|---|---|
| Title | NC4FXX-B |
| Connection Type | XLR |
| Gender | female |

| Electrical | |
|---|---|
| Capacitance between contacts | ≤ 7 pF |
| Contact resistance | ≤ 3 mΩ |
| Dielectric strength | 1,5 kVdc |
| Insulation resistance | > 10 GΩ (initial) |
| Rated current per contact | 10 A |
| Rated voltage | < 50 V |

| Mechanical | |
|---|---|
| Cable O.D. | 3.5 - 8.0 mm |
| Insertion force | ≤ 20 N |
| Withdrawal force | ≤ 20 N |
| Lifetime | > 1000 mating cycles |
| Wiresize | max. 1.5 mm² |
| Wiresize | max. 16 AWG |
| Wiring | Solder contacts |
| Locking device | Latch lock |


All rights reserved / 19.06.2026


Downloaded from Arrow.com.

NEUTRIK

| Material | |
|---|---|
| Boot | Polyurethan |
| Contacts | Brass (CuZn39Pb3) |
| Insert | Polyamide (PA66) |
| Locking element | Zinc diecast (ZnAl4Cu1) / Ck 67 (spring) |
| Locking element plating | Nickel |
| Shell | Zinc diecast (ZnAl4Cu1) |
| Shell coating | Black KTL |
| Strain relief | Polyacetal (POM) |

| Environmental | |
|---|---|
| Flammability | UL 94 V-0 |
| Standard compliance | IEC 61076-2-103 |
| Protection class | IP 40 |
| Solderability | Complies with IEC 68-2-20 |
| Temperature range | -30 °C to +80 °C |


All rights reserved / 19.06.2026


Downloaded from Arrow.com.