

YAD1010, Uninsulated Ring Terminal For 12 - 10 AWG

By Burndy Catalog # YAD1010

Uninsulated Ring Terminal For 12 - 10 AWG.

Features

- Constructed of pure electrolytic copper for maximum conductivity, low resistance and ductility for excellent crimp forming properties
- Long brazed seam barrel and deep V groove inner serrations provide optimum conductivity reliability and holding power aftercrimping
- Electro-tin plating to provide durable, long-lasting corrosion resistance
- Wire range is clearly marked on terminal for easy identification
- Inspection hold for an easy visual check of wire insertion
- Long neck terminal permits easy bending and stacking of several terminals on a common stud

Application

For control wiring and other standard duty applications

General

Catalog Number Connector Type EU RoHS Indicator Material Sub Brand Trade Name Type UPC YAD1010 Ring Terminal Yes Copper HYLUG HYLUG[™] Ring Tongue 781810806388



12 - 10 AWG

Dimensions

Dimension - Bolt Size fraction #8 - #10

Conductor Related

Conductor Size

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certification - CSA Approved	Yes
Standards - Industry Standards	UL486
Met	
Standards - RoHS Compliance	СМ
Status	
UL Listed	Yes

Logistics

Carton Quantity1000Minimum Pack Quantity1000Pallet Quantity99999

Product Assets

Catalogs - BURNDY Master Catalog - Section B - Small Terminals Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - 50094154 Specifications - YAD1010



©2025 Hubbell Incorporated. All rights reserved BRDY-YAD1010-SPEC-EN | REV 3/2025