


NOTES:
1. CONNECTOR MEETS APPLICABLE REQUIREMENTS OF MIL-C-55116.

R E V I S I O N S			
LTR	DESCRIPTION	DATE	APP
-	INITIAL RELEASE ECN 6616	3/24/05	ALL
A	ADD ITEMS 14&15, CHANGE 66-1P1 TO 66-8P1 ECN 6623	3/31/05	ALL
B	52-5P1 WAS 1P1, 56-1P2 WAS 16P1 ECN 6897	8/29/07	JE



ITEM	DESCRIPTION	PART NO.	QTY.	
1	SPRING	52-3P1	1	ⓑ
2	SHELL (SEE TABLE)	12-453	1	
3	INSERT ASSEMBLY	105-3G1	1	
4	SLEEVE	66-8P1	1	Ⓐ
5	GASKET	42-1P1	1	
6	NUT, ADAPTER	33-16P1	1	
7	FERRULE, SHIELD	32-40P1	1	
8	GROMMET (SEE TABLE)	41-1	1	
9	WASHER, FLAT	56-1P2	1	ⓑ
10	NUT, CABLE	30-1P1	1	
11	JAM NUT	23-15P1	1	
12	GASKET	42-111P1	1	
13	ORANGE DOPE	A2-000-9204	A/R	
14	GASKET	42-36P1	2	Ⓐ
15	FRONT INSERT	AI-000-1877	1	Ⓐ

GC328G5	CABLE O.D.	41-1	12-453
-4	.300/.280	P1	P4
-5	.330/.310	P2	P5
-3	.260/.240	P3	P3
-1	.175/.155	P4	P1
-2	.238/.218	P5	P2

TOLERANCES UNLESS OTHERWISE SPECIFIED	WPI SALEM FSCM 4Q3V3		CORPORATE HEADQUARTERS 23 Front St. Salem, N.J. 08079	
1/X = +/- 1/64	GENERAL CONNECTOR FSCM 25330		BY: ALL TITLE: THREADED GC328 W/ SHIELD ADAPTER	
.XX = +/- .010				
.XXX = +/- .005				
.XXXX = +/- .0005	GARRY ELECTRONICS FSCM 19112		APPD: CPF	PART #: GC328G5
ANGLES = +/- 0°-30°		DATE: 3/24/05 SCALE: 2 : 1		