



Product Navigation

- Home
- About Us
- Products
- Investor Relations
- News
- Contact Us
- Secure EAX

Circuit Board Indicators

Panel Mount Indicators

Solid State Lighting

Traffic Signals

Vehicle Lighting

Rail


Obstruction Lighting


Hazardous Area Lighting


Heliport Lighting

how to purchase

 sales contacts

 stock check

 search

 Product Line Search

Please select a Product Line to search.

Circuit Board Indicators


find

Part # / Text Search

Part No.:

Text Search:

search

 quick links

Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes
FAQs

Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives

Circuit Board Indicators - Through Hole Indicators


P/N# 5600301F

Bi-Pin LED Lamp Single Color

Description	Bi Pin LED Lamp
Package Options	25 Pieces Per Bag
Product Type	Through Hole Indicators
Sub Product Type	Discrete LED
Configuration	Bi-Pin LED Lamp
Lamp Type	Single Color
Viewing	Top View
Viewing Angle	70
Test Current (mA)	10mA

Absolute Maximum Ratings (Ta = 25 °)

Reverse Current	10 @ Vr = 12
Derating	from 46Â° @ .74 A/Â°C
Solder Temp	230Â° for 7 sec
Operating Temp	-55 to +100° C
Storage Temp	-55 to +100° C



Operating Characteristics

LED Position	
Color	Yellow
Lamp Type	Single Color
LED Type	High Efficiency
Intensity Min (mcd)	4.5
Intensity Typ (mcd)	
Intensity Max (mcd)	28.0
Fwd Voltage Min	
Fwd Voltage Typ	
Fwd Voltage Max	
Dom Wavelength Min (nm)	587
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	130
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Distributor Stock Check

Check stock with our distributors now.

5600301F

check stock