


SCN-IT-FLT10.4-004-003-B-R

① TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN.
GLASS IS BEVELED UNDER THE TRANSDUCERS.

- | CONNECTION CHART | | | |
|------------------|----------------|------------------|--------------|
| PIN | SIGNAL | INSULATION COLOR | JACKET COLOR |
| 1 | GROUND | OVERALL SHIELD | |
| 2 | KEY | | |
| 3 | Y RECEIVE (+) | BLU | BLK |
| 4 | Y TRANSMIT (+) | BLU | GRY |
| 5 | Y RECEIVE (-) | BLK | BLK |
| 6 | Y TRANSMIT (-) | YEL | GRY |
| 7 | GROUND | INNER SHIELD | |
| 8 | X TRANSMIT (-) | RED | RED |
| 9 | X RECEIVE (-) | RED | BLK |
| 10 | X TRANSMIT (+) | GRN | RED |
| 11 | X RECEIVE (+) | WHT | BLK |
| 12 | KEY | | |



CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE (+)	BLU	BLK
4	Y TRANSMIT (+)	BLU	GRY
5	Y RECEIVE (-)	BLK	BLK
6	Y TRANSMIT (-)	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT (-)	RED	RED
9	X RECEIVE (-)	RED	BLK
10	X TRANSMIT (+)	GRN	RED
11	X RECEIVE (+)	WHT	BLK
12	KEY		