

Product data sheet

Specifications



Rack PDU,Basic,Zero U,12.5kW,
208V,(30)C13,(6)C19;3ft input Cord

AP7568

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	0.9 m
Number of cables	1
Provided equipment	Cord retention bracket(s) Documentation CD Installation guide Rack mounting brackets Toolless mounting kit

Complementary

Input Voltage	208 V 3 phases
Height	177.8 cm
Width	5.6 cm
Output Voltage	208 V
Depth	8.9 cm
Net weight	6.95 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Max line current	35 A
Input current limits	35 A
Load capacity	12500 VA
Network frequency	50/60 Hz
Number of input connectors	1 CS8365
Outlet type and quantity	30 IEC 60320 C13 6 IEC 60320 C19

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Product certifications	cUL listed UL listed
Standards	CSA C22.2 No. 60950-1-03 UL 60950-1
Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	210.8 cm
Package 1 Width	12.7 cm
Package 1 Length	15.2 cm
Package 1 Weight	10.17 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	179
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration
Halogen content performance	Product contains halogen above thresholds

Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes

Image of product / Alternate images

Alternative



