

Part Number: 5026030670

Product Description: 2.00mm Pitch, Micro-Latch PCB Header, Single Row, Vertical, Through Hole, Gold (Au) Plating, 6 Circuits,


Tray

Series Number: 502603

**Status:** Active

**Product Category: PCB Headers and** 

Receptacles



#### **Documents & Resources**

#### **Drawings**

5026030670\_sd.pdf

3D Models and Design Files

5026030670\_stp.zip

#### **Specifications**

5026039200-SPK-200.pdf 510650001-PS-000.pdf 510651001-PS-000.pdf

## **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Not Contained per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

### **Part Details**

#### General

Status	Active
Category	PCB Headers and Receptacles
Series	502603
Description	2.00mm Pitch, Micro-Latch PCB Header, Single Row, Vertical, Through Hole, Gold (Au) Plating, 6 Circuits, Tray
Application	Signal, Wire-to-Board
Component Type	PCB Header
Product Name	Micro-Latch
UPC	800756695242

### **Electrical**

Current - Maximum per Contact	2.0A
Voltage - Maximum	250V

## **Physical**

Breakaway	No
Circuits (Loaded)	6
Circuits (maximum)	6
Color - Resin	Natural
Durability (mating cycles max)	30
First Mate / Last Break	No
Glow-Wire Capable	No
Lock to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Gold

Material - Resin	Polyamide
Net Weight	209.300/mg
Number of Rows	1
Orientation	Vertical
Packaging Type	Tray
PC Tail Length	3.50mm
PCB Locator	No
PCB Retention	Yes
PCB Thickness - Recommended	1.60mm
Pitch - Mating Interface	2.00mm
Plating min - Mating	0.100µm
Polarized to Mating Part	Yes
Polarized to PCB	No
Shrouded	Partial
Stackable	No
Temperature Range - Operating	-55° to +105°C
Termination Interface Style	Through Hole

# Mates With / Use With

## Mates with Part(s)

Description	Part Number
Micro-Latch Single Row Receptacle Housings	<u>51065</u>

This document was generated on Apr 25, 2025