

NOTES:

1. MATERIALS AND FINISHES:
SMP STR PLUG - BeCu, GOLD PLATING
CABLE - 0.047" CONFORMABLE

2. ELECTRICAL:
A. IMPEDANCE: 50 OHM

3. PACKAGING:
A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL RF, 95-725-119-XXX AND DATE CODE".

THIRD ANGLE PROJ.

REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
A	RELEASE TO MFG.	11-Jun-19	11801	SKP

INTERFACE PER
MIL-STD-348
SERIES: SMP PLUG
TYP(2)

LENGTH 'L' (SEE TABLE)

WHITE HEAT SHRINK TUBE
WITH BLACK MARKING

MARKING:
AMPHENOL RF

0.750±0.050
[19,05±1,27]

LOCATE APPROXIMATELY
AT CENTER AS SHOWN

SCALE 0.700

LENGTH TABLE

PART NUMBER (IMPERIAL)	PART NUMBER (METRIC)	LENGTH 'L' IN INCHES [METERS]
-	95-725-119M005	1.97 [0.050]
95-725-119-003	-	3.00 [0.076]
-	95-725-119M010	3.94 [0.100]
95-725-119-004	-	4.00 [0.102]
95-725-119-005	-	5.00 [0.127]
-	95-725-119M015	5.91 [0.150]
95-725-119-006	-	6.00 [0.152]
95-725-119-007	-	7.00 [0.178]
-	95-725-119M020	7.87 [0.200]
95-725-119-008	-	8.00 [0.203]
95-725-119-009	-	9.00 [0.229]
-	95-725-119M025	9.84 [0.250]
95-725-119-010	-	10.00 [0.254]
95-725-119-011	-	11.00 [0.279]
-	95-725-119M030	11.81 [0.300]
95-725-119-012	-	12.00 [0.305]
95-725-119-018	-	18.00 [0.457]
-	95-725-119M050	19.69 [0.500]
95-725-119-024	-	24.00 [0.610]
-	95-725-119M075	29.53 [0.750]
95-725-119-036	-	36.00 [0.914]
-	95-725-119M100	39.37 [1.000]
95-725-119-048	-	48.00 [1.219]
-	95-725-119M200	78.74 [2.000]
-	95-725-119M400	157.48 [4.000]

TOLERANCE TABLE

LENGTH IN INCHES/FT [METERS]	TOLERANCE
0" - 23.90" [0 - 0.607]	±0.25" [0.006]
24.00" - 59.00" [0.610 - 1.499]	±0.50" [0.013]
5.0' - 24.9' [1.524 - 7.617]	±2.5%
25.0' & UP [7.620 & UP]	±5.0%

DESIGN REQUIREMENTS:

☒ FREQUENCY: DC - 20 GHz

☒ CONTINUITY

☐ VSWR: ____ MAX.

☒ HI-POT: 500 VRMS

☐ INS. LOSS: ____ dB MAX.

☐ OTHER

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:
2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES
±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL
SEE NOTES

REFERENCE
EAR # 9091

CONFIGURATION LEVEL: In Work

FINISH

DRAWN
KRISHNA S

ENGINEER
KRISHNA S

APPROVED
K.CAPOZZI

CAD FILE

DATE
21-May-19

DATE
21-May-19

DATE
11-Jun-19

TITLE
SMP STR PLUG TO
SMP STR PLUG USNG
0.047" CONFORMABLE CABLE
VARIOUS LENGTH

SCALE: 3.6:1.0

SHEET 2 OF 2

DWG SIZE
B

REV
A

Amphenol RF
www.amphenolrf.com

DRAWING NO.95-725-119-XXX

ITEM NO.95-725-119-XXX

PART NO.95-725-119-XXX

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

Downloaded from [Arrow.com](#)