



MOLEX INCORPORATED
LISLE, ILL. 60532 U.S.A.

APPLICATION TOOLING
SPECIFICATION SHEET

TOOL & ENG. #: HAND TOOL CR-5907 ORDER #: 11-01-0189

TERMINAL SPECIFICATION

SERIES - VER.	WIRE SIZE		MM ²		INCH		DIAMETER		STRIP LENGTH	
	AWG	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MM
5103	28	.28	.33	.047	.075	1.20	1.90	.100	.125	3.17

TOOLING INFORMATION (REF 11-11-0316)

#	DESCRIPTION	ENG. NUMBER	ORDER NUMBER
01	COLLET JAW	CR60922A101	11-11-0317
02	AXLE - LOWER	CR60922A102	11-11-0318
03	FRAME (UPPER) - HANDLE GRIPS NOT INCL.	CR60922A103	11-11-0319
04	SPRING	CR60922A104	11-11-0320
05	HANDLE GRIP	CR60922A105	11-11-0321
06	AXLE - UPPER	CR60922A106	11-11-0322
07	FRAME (LOWER) - HANDLE GRIPS NOT INCL.	CR60922A107	11-11-0323
08	SPRING	CR60922A108	11-11-0324
09	LOCATOR	TL5907A2	11-11-0326
10	C-RING	CR60922A109	11-11-0325
11	C-RING	CR60922A112	11-11-0328

CRIMP SPECIFICATION

SET	AWG	CRIMP HEIGHT (REF.)		CRIMP WIDTH (REF.)		PULL FORCE MINIMUM	
		INCH	MM	IN	MM	LBS.	KG'S
A	22	.0264	.0303	.67	.77	.055	1.45
A	24	.0260	.0300	.66	.76	.055	1.45
B	26	.0260	.0300	.66	.76	.055	1.45
B	28	.0255	.0295	.65	.75	.055	1.45

NOTES:


- A. REPLACES JHTR 5907 HAND TOOL.
B. TOOL SHOULD NOT BE USED FOR WIRE GAUGES OUTSIDE OF TERMINAL SPECIFICATIONS.
C. TOOL SHOULD BE USED ONLY FOR TERMINAL SPECIFIED ON THIS SHEET.
D. THIS TOOL IS NOT ADJUSTABLE FOR CRIMP HEIGHT - VARIATIONS IN TOOLS, TERMINALS, WIRE STRANDING, & INSULATION MAY EFFECT CRIMP HEIGHT. PULL FORCE SHOULD BE USED AS THE FINAL CRITERIA FOR AN ACCEPTABLE CRIMP.
E. THIS TOOL IS PRIMARILY INTENDED FOR STANDARD CONDUCTOR SIZES. IT MAY NOT GIVE A GOOD INSULATION CRIMP SUPPORT FOR ALL INSULATION SIZES.

REV.
SHT.

FILE NAME CR5907.S80	DATE 04/13/93	REV. A U94011
DRAWN BY: SMT	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	SHT. 01

DRWG. NO.

DRWG. NO.



CRIMP SPECIFICATION

DRWG. NO.

A. REPLACES JHTR 5907 HAND TOOL.
B. TOOL SHOULD NOT BE USED FOR WIRE GAUGES OUTSIDE OF TERMINAL SPECIFICATIONS.
C. TOOL SHOULD BE USED ONLY FOR TERMINAL SPECIFIED ON THIS SHEET.
D. THIS TOOL IS NOT ADJUSTABLE FOR CRIMP HEIGHT - VARIATIONS IN TOOLS, TERMINALS, WIRE STRANDING, & INSULATION MAY EFFECT CRIMP HEIGHT. PULL FORCE SHOULD BE USED AS THE FINAL CRITERIA FOR AN ACCEPTABLE CRIMP.
E. THIS TOOL IS PRIMARILY INTENDED FOR STANDARD CONDUCTOR SIZES. IT MAY NOT GIVE A GOOD INSULATION CRIMP SUPPORT FOR ALL INSULATION SIZES.

Downloaded from Arrow.com.