

Product data sheet

Specifications

Rack ATS, 2U 230V, 32A, IEC309-32A In, (16)C13, (2)C19 Out



AP7724

⚠ Discontinued on: Jun 14, 2022

⚠ Discontinued

Overview

Lead time Usually in Stock

Main

Main Input Voltage	200 V 208 V 230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60309 32 A 2P + E
Number of rack unit	2U
Cable length	2.4 m
Number of cables	2
Provided equipment	Documentation CD Rack mounting brackets RS-232 configuration cable Warranty card

Physical

Height	8.8 cm
Width	43.2 cm
Depth	23.6 cm
Net weight	6.86 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Network frequency	50/60 Hz
Max line current	32 A
Input current limits	32 A

Output

Max current draw	32 A
Number of power socket outlets	16 IEC 60320 C13 2 IEC 60320 C19

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Protection type	Circuit breaker
-----------------	-----------------

Conformance

Standards	EN 55022 class A FCC part 15 class A
-----------	---

Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.6 cm
Package 1 Width	58.9 cm
Package 1 Length	35.6 cm
Package 1 Weight	9.34 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile
Use Better	
Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
Use Again	
Repack and remanufacture	
End of life manual availability	End of Life Information
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

